

## Label - MM-EML (EX18)R C1 YE/BK - 1116114

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Label, Roll, yellow/black, unlabeled, can be labeled with: THERMOMARK GO, THERMOMARK GO.K, THERMOFOX, mounting type: adhesive, lettering field size: continuous x 16 mm

### Product Description


The MM-EML... polyester self-adhesive labels are available as continuous media for equipment marking.

### Your advantages

- Easy and efficient material cartridge system: Includes both the material to be printed and the corresponding ink ribbon
- The self-adhesive material in continuous format is particularly suitable for the professional and permanent marking of various components and equipment in control cabinet, controller, and systems manufacturing
- Thanks to the continuous format, a label of the appropriate length can be created flexibly for the relevant application
- The material is cUL certified
- High-quality and solvent-resistant marking solution for industrial applications that is created by means of thermal transfer printing



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 063151 047962
GTIN	4063151047962
Weight per Piece (excluding packing)	68.000 g
Weight per piece (including packing)	79.400 g
Custom tariff number	96121010
Country of origin	China
Note	Made to Order (non-returnable)

### Technical data

#### Dimensions

Length (b)	8 m
Width (a)	18 mm

#### Ambient conditions

# Label - MM-EML (EX18)R C1 YE/BK - 1116114

## Technical data

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 150 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

### General

Color	yellow/black
Components	free from silicone, halogen, and cadmium
Material	Polyester
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Marking mounting type	adhesive

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Classifications

### eCl@ss

eCl@ss 9.0	27400629
------------	----------

## Approvals

### Approvals

### Approvals

### cULus Recognized

### Ex Approvals

### Approval details

cULus Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	MH48542
------------------	---	---	---------