

## Fabric label - MM-EMLC (EX14)R C1 WH/BK - 1116134

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Fabric label, Roll, white/black, unlabeled, can be labeled with: THERMOMARK GO, THERMOMARK GO.K, THERMOFOX, mounting type: adhesive, lettering field size: continuous x 12 mm

### Your advantages

- ✔ Easy and efficient material cartridge system: Includes both the material to be printed and the corresponding ink ribbon
- ✔ The self-adhesive material in continuous format is particularly suitable for the professional and permanent marking of various components and equipment in control cabinet, controller, and systems manufacturing
- ✔ The label material consists of a textile foil with very low restoring forces
- ✔ Enables labels to be stuck over edges and curves
- ✔ Thanks to the continuous format, a label of the appropriate length can be created flexibly for the relevant application
- ✔ The material is UL certified
- ✔ High-quality and solvent-resistant marking solution for industrial applications that is created by means of thermal transfer printing



### Key Commercial Data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 1 pc                                                                                                    |
| GTIN                                 | <br>4 063151 040437 |
| GTIN                                 | 4063151040437                                                                                           |
| Weight per Piece (excluding packing) | 45.000 g                                                                                                |
| Weight per piece (including packing) | 55.700 g                                                                                                |
| Custom tariff number                 | 96121010                                                                                                |
| Country of origin                    | China                                                                                                   |
| Note                                 | Made to Order (non-returnable)                                                                          |

### Technical data

#### Dimensions

|            |       |
|------------|-------|
| Length (b) | 6 m   |
| Width (a)  | 14 mm |

#### Ambient conditions

# Fabric label - MM-EMLC (EX14)R C1 WH/BK - 1116134

## Technical data

### Ambient conditions

|                                 |                                                                                                                   |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation) | 0 °C ... 80 °C                                                                                                    |
| Recommended storage conditions  | 5 - 35°C / 30 - 80 % relative humidity. Storage in a cool and dry place in the original packaging is recommended. |

### General

|                       |                                          |
|-----------------------|------------------------------------------|
| Color                 | white/black                              |
| Components            | free from silicone, halogen, and cadmium |
| Material              | PA                                       |
| Wipe resistance       | DIN EN 61010-1 (VDE 0411-1)              |
| Marking mounting type | adhesive                                 |

### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 9.0 | 27400629 |
|------------|----------|

## Approvals

### Approvals

---

#### Approvals

UL Recognized

---

Ex Approvals

---

### Approval details

|               |  |                                                                                                                                                       |               |
|---------------|--|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| UL Recognized |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE MH 48542 |
|---------------|--|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|

---