

Shrink sleeve - MM-WMS-2 6,4 (EX10)R C1 YE/BK - 1116187

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Shrink sleeve, Roll, yellow/black, unlabeled, can be labeled with: THERMOMARK GO, THERMOFOX, mounting type: slide-on, cable diameter range: 3.2 ... 6.4 mm, lettering field size: continuous x 8.5 mm

Your advantages

- ✓ Easy and efficient material cartridge system: Includes both the material to be printed and the corresponding ink ribbon
- ✓ No visible difference between retrospective marking and existing markings created with a desktop roll printer
- ✓ The conductor to be marked is simply threaded through the shrink sleeve, which is fixed to the conductor by heating the sleeve accordingly
- ✓ The shrink sleeve material provides additional electrical insulation and mechanical protection for conductors
- ✓ Thanks to the continuous format, a shrink sleeve marker of the appropriate length can be created flexibly for the relevant application
- ✓ The material is cUL certified
- ✓ High-quality and solvent-resistant marking solution for industrial applications that is created by means of thermal transfer printing



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| GTIN |  4 063151 041625 |
| GTIN | 4063151041625 |
| Weight per Piece (excluding packing) | 39.000 g |
| Weight per piece (including packing) | 50.200 g |
| Custom tariff number | 96121010 |
| Country of origin | China |
| Note | Made to Order (non-returnable) |

Technical data

Dimensions

| | |
|----------------|-------------------|
| Length (b) | 1.8 m |
| Width (a) | 11.5 mm |
| Cable diameter | 3.2 mm ... 6.4 mm |

Ambient conditions

Shrink sleeve - MM-WMS-2 6,4 (EX10)R C1 YE/BK - 1116187

Technical data

Ambient conditions

| | |
|---------------------------------|---|
| Ambient temperature (operation) | -55 °C ... 125 °C |
| Recommended storage conditions | 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended. |

General

| | |
|-----------------------|--|
| Color | yellow/black |
| Type | Shrink sleeve |
| Components | free from silicone, halogen, and cadmium |
| Material | Polyolefine |
| Shrink rate | 2:1 |
| Marking mounting type | slide-on |
| R22 | HL 3 |

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27400401 |
| eCl@ss 11.0 | 27281102 |
| eCl@ss 9.0 | 27400401 |

Approvals


Approvals

Approvals

cULus Recognized

Ex Approvals

Approval details

| | | | |
|------------------|---|---|---------|
| cULus Recognized |  | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | E310982 |
|------------------|---|---|---------|