

# Shrink sleeve - MM-WMS-2 9,5 (EX16)R C1 YE/BK - 1116189

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Shrink sleeve, Roll, yellow/black, unlabeled, can be labeled with: THERMOMARK GO, THERMOFOX, mounting type: slide-on, cable diameter range: 4.8 ... 9.5 mm, lettering field size: continuous x 12.5 mm

## Your advantages

- ✓ Easy and efficient material cartridge system: Includes both the material to be printed and the corresponding ink ribbon
- ✓ No visible difference between retrospective marking and existing markings created with a desktop roll printer
- ✓ The conductor to be marked is simply threaded through the shrink sleeve, which is fixed to the conductor by heating the sleeve accordingly
- ✓ The shrink sleeve material provides additional electrical insulation and mechanical protection for conductors
- ✓ Thanks to the continuous format, a shrink sleeve marker of the appropriate length can be created flexibly for the relevant application
- ✓ The material is cUL certified
- ✓ High-quality and solvent-resistant marking solution for industrial applications that is created by means of thermal transfer printing



## Key Commercial Data

Packing unit	1 pc
GTIN	 4 063151 042103
GTIN	4063151042103
Weight per Piece (excluding packing)	47.000 g
Weight per piece (including packing)	59.000 g
Custom tariff number	96121010
Country of origin	China
Note	Made to Order (non-returnable)

## Technical data

### Dimensions

Length (b)	1.8 m
Width (a)	16.5 mm
Cable diameter	4.8 mm ... 9.5 mm

### Ambient conditions

# Shrink sleeve - MM-WMS-2 9,5 (EX16)R C1 YE/BK - 1116189

## Technical data

### Ambient conditions

Ambient temperature (operation)	-55 °C ... 125 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

### General

Color	yellow/black
Type	Shrink sleeve
Components	free from silicone, halogen, and cadmium
Material	Polyolefine
Shrink rate	2:1
Marking mounting type	slide-on
R22	HL 3

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Classifications

### eCl@ss

eCl@ss 10.0.1	27400401
eCl@ss 11.0	27281102
eCl@ss 9.0	27400401

## Approvals


### Approvals

#### Approvals

cULus Recognized

#### Ex Approvals

### Approval details

cULus Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	E310982
------------------	---	---	---------