

## Toolbox - CRIMPFOX 4 IN 1 SET - 1200102

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Tool for processing ferrules according to DIN 46228-4, 0.5 mm<sup>2</sup> to 2.5 mm<sup>2</sup>, equipped with pressure lock, cutting, stripping, twisting, and crimping unit, with three magazines including a strip each of ferrules from 0.5 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>, packaged in a robust plastic case

### Your advantages

- ✔ Integrated pressure lock ensures consistently high-quality crimping
- ✔ Up to 30% time savings since the process steps required for assembling conductors can be carried out using only one tool
- ✔ Multifunctional crimping pliers for the processing of Taped ferrules according to DIN 46228-4
- ✔ Robust and durable due to use of resistant plastics and annealed metals
- ✔ Visualized process flows directly on the pliers simplify operation



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 042398
GTIN	4055626042398
Weight per Piece (excluding packing)	727.700 g
Weight per piece (including packing)	735.200 g
Custom tariff number	82032000
Country of origin	Germany

### Technical data

#### Dimensions

Length (b)	180 mm
Width (a)	31.5 mm
Height (c)	100 mm
Stripping length	8 mm

# Toolbox - CRIMPFOX 4 IN 1 SET - 1200102

## Technical data

### General

Compression	Indent crimp
Type of contact	Ferrules
Min. AWG, flexible, multi-strand	14
AWG max., flexible, multi-strand	20
Min. cross section	0.5 mm <sup>2</sup>
Max. cross section	2.5 mm <sup>2</sup>
AWG min	20
AWG max	14
Maximum stripping length	11 mm
Weight	600 g
Min. cross section	0.5 mm <sup>2</sup>
Max. cross section	2.5 mm <sup>2</sup>
AWG min	20
AWG max	14

### Environmental Product Compliance

California Proposition 65	Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration
---------------------------	---

## Classifications

### eCl@ss

eCl@ss 10.0.1	21043811
eCl@ss 5.0	27400200
eCl@ss 5.1	27400200
eCl@ss 6.0	21043800
eCl@ss 7.0	21043811
eCl@ss 8.0	21043811
eCl@ss 9.0	21043811

### ETIM

ETIM 4.0	EC000168
ETIM 5.0	EC000168
ETIM 6.0	EC000168
ETIM 7.0	EC000168

### UNSPSC

UNSPSC 13.2	27111518
UNSPSC 18.0	27111518
UNSPSC 19.0	27111518
UNSPSC 20.0	27111518
UNSPSC 21.0	27111518

# Toolbox - CRIMPFOX 4 IN 1 SET - 1200102

## Approvals

Approvals

---

Approvals

EAC

---

Ex Approvals

---

## Approval details

EAC		RU x- DE.xx08.B.02974
-----	--	--------------------------

## Accessories

### Accessories

#### Cable end sleeve

Ferrule - Al 0,5-8 WH S1 - 1200104



Taped ferrules, 0.5 mm<sup>2</sup>, sleeve length 8 mm, with plastic collar, according to DIN 46228-4, white, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 50 sleeves per strip.

Ferrule - Al 0,75- 8 GY S1 - 1200105



Taped ferrules, 0.75 mm<sup>2</sup>, sleeve length 8 mm, with plastic collar, according to DIN 46228-4, gray, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 50 sleeves per strip.

Ferrule - Al 1,0-8 RD S1 - 1200106



Taped ferrules, 1.0 mm<sup>2</sup>, sleeve length 8 mm, with plastic collar, according to DIN 46228-4, red, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 50 sleeves per strip.

## Toolbox - CRIMPFOX 4 IN 1 SET - 1200102

### Accessories

#### Ferrule - AI 1,5-8 BK S1 - 1200107



Taped ferrules, 1.5 mm<sup>2</sup>, sleeve length 8 mm, with plastic collar, according to DIN 46228-4, black, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 50 sleeves per strip.

---

#### Ferrule - AI 2,5-8 BU S1 - 1200108



Taped ferrules, 2.5 mm<sup>2</sup>, sleeve length 8 mm, with plastic collar, according to DIN 46228-4, blue, for processing with the CRIMPFOX 4 IN 1, 10 strips each with 40 sleeves per strip.

---

#### Ferrule - AI 0,75- 8 BU S1 - 1200163



Ferrule, Dimensions according to DIN 46228-4, with color-coded plastic collars according to NF C 63-023:1994-02, for processing with the CRIMPFOX 4 in 1, sleeve length: 8 mm, length: 14 mm, color: blue, number of strips: 10, number of sleeves per strip: 50

---

#### Ferrule - AI 2,5-8 GY S1 - 1200164



Ferrule, Dimensions according to DIN 46228-4, with color-coded plastic collars according to NF C 63-023:1994-02, for processing with the CRIMPFOX 4 in 1, sleeve length: 8 mm, length: 14 mm, color: gray, number of strips: 10, number of sleeves per strip: 40

---

### Magazine

#### Magazine - CRIMPFOX 4 IN 1/MAG - 1200103



Ferrule magazine for CRIMPFOX 4 IN 1, for ferrules with insulating collars from 0.5 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>, with a length of 8 mm

---