


## Screwdriver - SF-BIT-HEX 2-89 S - 1200300

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Screw bit, hexagon, E6.3-1/4" drive, size: Hex 2 x 89 mm, hardened, suitable for holder according to DIN 3126-F6.3/ISO 1173

### Key Commercial Data

|                                      |  |
|--------------------------------------|--|
| Packing unit                         | 5 pc   |
| Minimum order quantity               | 5 pc   |
| GTIN                                 | <br>4 055626 444642 |
| GTIN                                 | 4055626444642  |
| Weight per Piece (excluding packing) | 8.570 g  |
| Weight per piece (including packing) | 8.570 g  |
| Custom tariff number                 | 82079030   |
| Country of origin                    | Czech Republic   |
| Note                                 | Made to Order (non-returnable)   |

### Technical data

|              |                    |
|--------------|--------------------|
| Product type | Screwdriver tools  |
| Approval     | EAC                |
| Isolation    | no                 |
| Drive        | External hexagonal |

### Drawings

# Screwdriver - SF-BIT-HEX 2-89 S - 1200300

Pictogram



## Classifications

eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 21044290 |
| eCl@ss 7.0    | 21044290 |
| eCl@ss 9.0    | 21044290 |

## Approvals

Approvals

---

Approvals

EAC

# Screwdriver - SF-BIT-HEX 2-89 S - 1200300

## Approvals

---

Ex Approvals

---

## Approval details

|     |   |                          |
|-----|---|--------------------------|
| EAC |  | RU C-<br>DE.AI30.B.01750 |
|-----|---|--------------------------|

## Accessories

Accessories

Screwdriver tools

Screwdriver - SF-M BH - 1212070



Bit screwdriver, with 1/4" quick-action chuck, handle length 119 mm, 2-component handle, with non-slip grip, suitable for bits according to DIN 3126-C 6.3 and E 6.3/ISO 1173, magnetic