

## Crimping tool, pneumatic - ZAP 25 T - 1203123

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Pneumatic crimping pliers, as table top version, for ferrules in accordance with DIN 46228-1: 1992-08 and DIN 46228-4: 1990-09, for conductor cross section 0.25 - 2.5 mm<sup>2</sup>

### Your advantages

- ✓ These crimping pliers have been specially developed for pre-assembling conductors
- ✓ The crimping process is activated by a foot valve
- ✓ Two integrated recesses allow quick access to the ferrules



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 018092
GTIN	4017918018092
Weight per Piece (excluding packing)	2,908.000 g
Weight per piece (including packing)	2,908.000 g
Custom tariff number	84671900
Country of origin	Germany

### Technical data

#### Dimensions

Length (b)	200 mm
Width (a)	140 mm
Height (c)	70 mm
Stripping length	0 mm

#### General

Compression	trapezoidal
Min. AWG, flexible, multi-strand	14
AWG max., flexible, multi-strand	24

# Crimping tool, pneumatic - ZAP 25 T - 1203123

## Technical data

### General

Pressure range	4 bar ... 6 bar
Air consumption per compression	0.2 l
Power consumption	0 W
Weight	1 kg
Min. cross section	0.25 mm <sup>2</sup>
Max. cross section	2.5 mm <sup>2</sup>

## Classifications

### eCl@ss

eCl@ss 10.0.1	17130101
eCl@ss 4.0	21040300
eCl@ss 4.1	21040300
eCl@ss 5.0	21040300
eCl@ss 5.1	17130100
eCl@ss 6.0	17130100
eCl@ss 7.0	17130101
eCl@ss 8.0	17130101
eCl@ss 9.0	17130101

### ETIM

ETIM 2.0	EC001186
ETIM 3.0	EC001186
ETIM 4.0	EC001186
ETIM 5.0	EC000168
ETIM 6.0	EC002778
ETIM 7.0	EC002778

### UNSPSC

UNSPSC 6.01	27112118
UNSPSC 7.0901	27111518
UNSPSC 11	23171604
UNSPSC 12.01	27111518
UNSPSC 13.2	27111518

## Approvals

### Approvals

---

Approvals

EAC

## Crimping tool, pneumatic - ZAP 25 T - 1203123

### Approvals

---

Ex Approvals

---

### Approval details

EAC



RU C-  
DE.A\*30.B.01744