


Cable gland - G-INS-M16-S68N-NNES-S - 1411162

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, cable gland material: Nickel-plated brass, external cable diameter 5 mm ... 10 mm, shielding: No, connecting thread: M16 x 1.5, color: silver

Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 10 STK |
| GTIN |  4 046356 922975 |
| GTIN | 4046356922975 |
| Weight per Piece (excluding packing) | 27.140 g |
| Weight per piece (including packing) | 27.140 g |
| Custom tariff number | 74199990 |
| Country of origin | Turkey |

Technical data

Dimensions

| | |
|---------------------------------|-------------------------------|
| Length | 34 mm |
| Wrench size, union nut | 20 mm |
| Wrench size, support | 20 mm |
| Hexagon angular dimension | 22 mm |
| Length of the connecting thread | 7 mm |
| Feed-through hole diameter | 16.1 mm ... 16.3 mm |
| External cable diameter | 5 mm ... 10 mm |
| | 6 mm ... 10 mm (for UL 514 B) |

Ambient conditions

| | |
|----------------------|---------------------------------|
| Degree of protection | IP69 (DIN EN 60529 / IEC 60529) |
| | IP68 (5 bar, 30 min.) |
| | IP66 |
| | 4X |

Cable gland - G-INS-M16-S68N-NNES-S - 1411162

Technical data

Ambient conditions

| | |
|---------------------------------|----------------------------|
| Ambient temperature (operation) | -20 °C ... 100 °C (static) |
|---------------------------------|----------------------------|

General

| | |
|--------------------------------|---|
| No. of conductors | 1 |
| Cable gland material | Nickel-plated brass |
| Material, insert | Polyamide 6 |
| Cable seal material | Neoprene |
| Shielded | No |
| Torque | 7 Nm (Union nut: EN 62444) |
| | 7 Nm (Support: EN 62444) |
| | 8 Nm (for UL514 B: union nut) |
| Color | silver |
| Impact category | 6 |
| Execution of the strain relief | A |
| Assembly instructions | 1) Mount screw connection support in the housing using the correct torque 2) Insert cable 3) Tighten union nut using the correct torque |
| Manufacturer | BIMED |
| Manufacturer Designation | BMBC-E1 |

Standards and Regulations


| | |
|--------------|----|
| Halogen-free | no |
|--------------|----|

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Drawings

Dimensional drawing



Dimensional drawing

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 5.1 | 27081002 |
|------------|----------|

Cable gland - G-INS-M16-S68N-NNES-S - 1411162

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 6.0 | 27081002 |
| eCl@ss 8.0 | 27149109 |
| eCl@ss 9.0 | 27144432 |

ETIM

| | |
|----------|----------|
| ETIM 4.0 | EC000441 |
| ETIM 5.0 | EC000441 |
| ETIM 6.0 | EC000441 |

UNSPSC

| | |
|-------------|----------|
| UNSPSC 13.2 | 39121311 |
|-------------|----------|

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Approval details

| | | | |
|---------------|--|---|---------|
| UL Recognized | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | E199260 |
|---------------|--|---|---------|

| | | | |
|----------------|--|---|---------|
| cUL Recognized | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | E199260 |
|----------------|--|---|---------|

| | | | |
|------------------|--|---|--|
| cULus Recognized | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | |
|------------------|--|---|--|

Accessories

Accessories

Flat nut

Cable gland - G-INS-M16-S68N-NNES-S - 1411162

Accessories

Counter nut - A-INL-M16-N-S - 1411241



Counter nut, Brass, nickel-plated, for threads M16 x 1.5, color: silver

Sealing plugs

Closing cap - SEALING PLUG 8X16 RD - 1400257



Closing cap