

Relay base - ECOR-3-BSC1-RT/3X21 - 2907522


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



ECOR-3 relay base, for octal relays with three changeover contacts, bolt connection, for mounting on NS 35/7,5



Key Commercial Data

Packing unit	10 pc
Minimum order quantity	10 pc
GTIN	 4 055626 214399
GTIN	4055626214399
Weight per Piece (excluding packing)	61.200 g
Weight per piece (including packing)	61.200 g
Custom tariff number	85366990
Country of origin	China

Technical data

Dimensions

Width	42.3 mm
Height	54.7 mm
Depth with retaining bracket	91 mm (EL3-M52)

Ambient conditions

Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 55 °C

General

Nominal voltage U_N	250 V AC/DC
Nominal current I_N	10 A
Color	gray
Mounting position	any

Relay base - ECOR-3-BSC1-RT/3X21 - 2907522

Technical data

Connection data

Connection name	Input side
Connection method	Bolt connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section solid	2x 0.2 mm ² ... 2.5 mm ² (without ferrule)
	2x 0.2 mm ² ... 1.5 mm ² (with ferrule)
Conductor cross section flexible	2x 0.2 mm ² ... 2.5 mm ² (without ferrule)
	2x 0.2 mm ² ... 1.5 mm ² (with ferrule)

Connection data 2

Connection name	Output side
Connection method	Bolt connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section solid	2x 0.2 mm ² ... 2.5 mm ² (without ferrule)
	2x 0.2 mm ² ... 1.5 mm ² (with ferrule)
Conductor cross section flexible	2x 0.2 mm ² ... 2.5 mm ² (without ferrule)
	2x 0.2 mm ² ... 1.5 mm ² (with ferrule)

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 5.0	27371600
eCl@ss 5.1	27371603
eCl@ss 6.0	27371600
eCl@ss 7.0	27371603
eCl@ss 8.0	27371603
eCl@ss 9.0	27371603

ETIM

ETIM 2.0	EC001456
ETIM 3.0	EC001456
ETIM 4.0	EC001456
ETIM 5.0	EC001456
ETIM 6.0	EC001456
ETIM 7.0	EC001456

Relay base - ECOR-3-BSC1-RT/3X21 - 2907522

Classifications

UNSPSC

UNSPSC 13.2	39122326
UNSPSC 18.0	39122335
UNSPSC 19.0	39122335
UNSPSC 20.0	39122335
UNSPSC 21.0	39122335

Approvals

Approvals


Approvals


CSA / UL Recognized / cUL Recognized / EAC / cULus Recognized


Ex Approvals


Approval details

CSA		http://www.csagroup.org/services-industries/product-listing/	70066743
-----	---	---	----------

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 113228
---------------	---	---	---------------

cUL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 113228
----------------	---	---	---------------

EAC			RU C- DE.**08.B.01419
-----	---	--	--------------------------

cULus Recognized			
------------------	---	--	--

Accessories

Accessories

Relay base - ECOR-3-BSC1-RT/3X21 - 2907522

Accessories

Bridge


Wire bridge - DB 50- 90 BU - 2821180

Wire bridge, color: blue



Wire bridge - DB 50- 90 BK - 2820916

Wire bridge, color: black



Wire bridge - DB 50- 90 GY - 2820929

Wire bridge, color: gray



Retaining bracket

Relay retaining bracket - EL3-M52 - 2833628



Relay retaining bracket, wiring to suit relay base RIF-3 and PR3, for 52 mm high octal relay

Necessary add-on products

Single relay - REL-OR3-BL/L-24DC/3X21 - 2906307



Plug-in octal relays in basic design with power contacts, 3 PDTs, test button, mechanical switch position indicator, polarity: A1+, A2-, input voltage: 24 V DC

Relay base - ECOR-3-BSC1-RT/3X21 - 2907522

Accessories

Single relay - REL-OR3-BL/L-230AC/3X21 - 2906308



Plug-in octal relays in basic design with power contacts, 3 PDTs, test button, mechanical switch position indicator, input voltage: 230 V AC

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>