

SIPLUS ET 200S 2AO U high feature -25...+60°C based on  
6ES7135-4LB02-0AB0



### Supply voltage

#### Load voltage L+

- Rated value (DC) 24 V
- Reverse polarity protection Yes

### Input current

from load voltage L+ (without load), max.	80 mA
from backplane bus 3.3 V DC, max.	10 mA

### Power loss

Power loss, max.	1.2 W
------------------	-------

### Address area

Address space per module	
• Address space per module, max.	4 byte

### Analog outputs

Number of analog outputs	2
Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	25 mA
Cycle time (all channels) max.	0.5 ms; At max. 0.5 µF

<b>Output ranges, voltage</b>	
• 1 V to 5 V	Yes
• -5 V to +5 V	Yes
• -10 V to +10 V	Yes
<b>Connection of actuators</b>	
• for voltage output two-wire connection	Yes
• for voltage output four-wire connection	Yes
<b>Load impedance (in rated range of output)</b>	
• with voltage outputs, min.	1 kΩ
• with voltage outputs, capacitive load, max.	0.5 µF
<b>Destruction limits against externally applied voltages and currents</b>	
• Voltages at the outputs towards MANA	15 V; max. 15 V continuous; 75 V for max. 1 s (mark to space ratio 1:20)
<b>Cable length</b>	
• shielded, max.	200 m; 100 m if $T_{wa} < 2 \text{ ms}$
<b>Analog value generation for the outputs</b>	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit; 15 bit + sign
<b>Settling time</b>	
• for resistive load	0.2 ms
• for capacitive load	0.5 ms; At max. 0.5 µF
• for inductive load	0.5 ms
<b>Errors/accuracies</b>	
Operational error limit in overall temperature range	
• Voltage, relative to output range, (+/-)	0.1 %
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to output range, (+/-)	0.05 %
<b>Interrupts/diagnostics/status information</b>	
Diagnostic messages	
• Diagnostic information readable	Yes
• Short-circuit	Yes
• Group error	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
<b>Parameter</b>	
Remark	7 byte
Diagnostics short-circuit	Disable / enable
Output type/range	deactivated / 1 to 5 V / ±10 V / ±5 V
Group diagnostics	Disable / enable

Response to CPU/master STOP	Output current and de-energized/substitute a value/keep last value	
Potential separation		
Potential separation analog outputs		
• between the channels	No	
• between the channels and backplane bus	Yes	
• Between the channels and load voltage L+	Yes	
Isolation		
Isolation tested with	500 V DC	
Ambient conditions		
Ambient temperature during operation		
• min.	-25 °C; = Tmin	
• max.	60 °C; = Tmax	
Altitude during operation relating to sea level		
• Installation altitude above sea level, max.	5 000 m	
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)	
Relative humidity		
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)	
Resistance		
Use in stationary industrial systems		
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request	
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *	
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *	
Use on ships/at sea		
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request	
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *	
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *	
Usage in industrial process technology		
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)	
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)	

**Remark**

— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04

\* The supplied plug covers must remain in place over the unused interfaces during operation!

**Dimensions**

Width	15 mm
Height	81 mm
Depth	52 mm

**Weights**

Weight, approx.	40 g
-----------------	------

**last modified:** 05/09/2020