

SIPLUS S7-1200 SB 1231 1AI RTD -40 ... +60°C, start up -25°C,  
with conformal coating based on 6ES7231-5PA30-0XB0 . SIPLUS  
S7-1200, analog input, SB 1231RTD, 1 AI RTD, PT 100 and PT1000



### General information

|                          |                          |
|--------------------------|--------------------------|
| Product type designation | SB 1231, AI 1x16 bit RTD |
|--------------------------|--------------------------|

### Supply voltage

|                  |      |
|------------------|------|
| Rated value (DC) | 24 V |
|------------------|------|

### Input current

|                                 |       |
|---------------------------------|-------|
| Current consumption, typ.       | 5 mA  |
| from backplane bus 5 V DC, typ. | 20 mA |

### Power loss

|                  |       |
|------------------|-------|
| Power loss, typ. | 0.5 W |
|------------------|-------|

### Analog inputs

|  |                                    |
|--|------------------------------------|
| Number of analog inputs  | 1; Resistance thermometer          |
| permissible input voltage for current input<br>(destruction limit), max. | ±35 V                              |
| Technical unit for temperature measurement<br>adjustable                 | Degrees Celsius/degrees Fahrenheit |

### Input ranges

|           |     |
|-----------|-----|
| • Voltage | Yes |
| • Current | No  |

|   |   |
|---|---|
| • Thermocouple  | No  |
| • Resistance thermometer  | Yes; Platinum (Pt)                                      |
| • Resistance  | Yes; 150 Ω, 300 Ω, 600 Ω                                |
| <b>Input ranges (rated values), voltages</b>  |   |
| • -80 mV to +80 mV<br>— Input resistance (-80 mV to +80 mV)                                   | >= 10 MΩ  |
| <b>Input ranges (rated values), resistance thermometer</b>                                    |   |
| • Pt 100<br>— Input resistance (Pt 100)   | Yes<br>100 Ω  |
| • Pt 1000<br>— Input resistance (Pt 1000)   | Yes<br>1 000 Ω  |
| • Pt 200<br>— Input resistance (Pt 200)   | Yes<br>200 Ω  |
| • Pt 500<br>— Input resistance (Pt 500)   | Yes<br>500 Ω  |
| <b>Input ranges (rated values), resistors</b>   |   |
| • 0 to 150 ohms   | Yes   |
| • 0 to 300 ohms   | Yes   |
| • 0 to 600 ohms   | Yes   |
| <b>Thermocouple (TC)</b>  |   |
| <b>Temperature compensation</b>   |   |
| — parameterizable   | No  |
| <b>Analog outputs</b>   |   |
| Number of analog outputs  | 0   |
| <b>Analog value generation for the inputs</b>   |   |
| Measurement principle   | integrating   |
| <b>Integration and conversion time/resolution per channel</b>                                 |   |
| • Resolution with overrange (bit including sign), max.  | 15 bit; + sign  |
| • Integration time, parameterizable   | No  |
| • Interference voltage suppression for interference frequency f1 in Hz                        | 85 dB at 10 / 50 / 60 / 400 Hz                          |
| <b>Errors/accuracies</b>  |   |
| Temperature error (relative to input range), (+/-)  | 25 °C ±0.1%, up to 55 °C ±0.25% total measurement range |
| Repeat accuracy in steady state at 25 °C (relative to output range), (+/-)                    | 0.05 %  |
| <b>Interference voltage suppression for f = n x (f1 +/- 1 %), f1 = interference frequency</b> |   |
| • Common mode interference, min.  | 120 dB  |
| <b>Interrupts/diagnostics/status information</b>  |   |
| Alarms  | Yes   |
| Diagnostics function  | Yes; Can be read out                                    |

|   |   |
|---|---|
| <b>Alarms</b>   |   |
| • Diagnostic alarm  | Yes   |
| <b>Diagnostic messages</b>  |   |
| • Wire-break  | Yes   |
| <b>Diagnostics indication LED</b>                                   |   |
| • for status of the inputs  | Yes   |
| • for maintenance   | Yes   |
| <b>Ambient conditions</b>   |   |
| <b>Free fall</b>  |   |
| • Fall height, max.   | 0.3 m; five times, in product package   |
| <b>Ambient temperature during operation</b>                         |   |
| • min.  | -40 °C; = Tmin (incl. condensation/frost); start-up @ -25 °C  |
| • max.  | 60 °C; = Tmax   |
| • vertical installation, min.                                       | -40 °C; = Tmin; Startup @ -25 °C  |
| • vertical installation, max.                                       | 50 °C; = Tmax   |
| <b>Ambient temperature during storage/transportation</b>            |   |
| • min.  | -40 °C  |
| • max.  | 70 °C   |
| <b>Altitude during operation relating to sea level</b>              |   |
| • Installation altitude above sea level, max.                       | 5 000 m   |
| • Ambient air temperature-barometric pressure-altitude              | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) //<br>Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) //<br>Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m) |
| <b>Relative humidity</b>  |   |
| • With condensation, tested in accordance with IEC 60068-2-38, max. | 100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation   |
| <b>Resistance</b>   |   |
| <b>Coolants and lubricants</b>                                      |   |
| — Resistant to commercially available coolants and lubricants       | Yes; Incl. diesel and oil droplets in the air   |
| <b>Use in stationary industrial systems</b>                         |   |
| — to biologically active substances according to EN 60721-3-3       | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request  |
| — to chemically active substances according to EN 60721-3-3         | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *  |
| — to mechanically active substances according to EN 60721-3-3       | Yes; Class 3S4 incl. sand, dust, *  |
| <b>Use on ships/at sea</b>  |   |
| — to biologically active substances according to EN 60721-3-6       | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request   |
| — to chemically active substances according to EN 60721-3-6         | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *  |

|   |   |
|---|---|
| — to mechanically active substances according to EN 60721-3-6   | Yes; Class 6S3 incl. sand, dust; *  |
| <b>Usage in industrial process technology</b>   |   |
| — Against chemically active substances acc. to EN 60654-4   | Yes; Class 3 (excluding trichlorethylene)   |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04                            | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil) |
| <b>Remark</b>   |   |
| — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04             | * The supplied plug covers must remain in place over the unused interfaces during operation!  |
| <b>Conformal coating</b>  |   |
| • Coatings for printed circuit board assemblies acc. to EN 61086  | Yes   |
| • Protection against fouling acc. to EN 60664-3   | Yes; Type 1 protection  |
| • Military testing according to MIL-I-46058C, Amendment 7   | Yes; Discoloration of coating possible during service life  |
| • Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A | Yes; Conformal coating, Class A   |
| <b>Connection method</b>  |   |
| required front connector  | Yes   |
| <b>Mechanics/material</b>   |   |
| Enclosure material (front)  |   |
| • Plastic   | Yes   |
| <b>Dimensions</b>   |   |
| Width   | 38 mm   |
| Height  | 62 mm   |
| Depth   | 21 mm   |
| <b>Weights</b>  |   |
| Weight, approx.   | 35 g  |
| <b>last modified:</b>   | 05/15/2020  |