

SIPLUS S7-1200 SM 1232 -40...+70°C with conformal coating based on 6ES7232-4HD32-0XB0 . S7-1200, Analog output, SM 1232, 4 AO, +/-10 V, 14-bit resolution: or 0-20 mA, 13-bit resolution:



General information	
Product type designation	SM 1232, AQ 4x14 bit
Supply voltage	
Rated value (DC)	24 V
Input current	
Current consumption, typ.	45 mA
from backplane bus 5 V DC, typ.	80 mA
Power loss	
Power loss, typ.	1.5 W
Analog outputs	
Number of analog outputs	4; Current or voltage
Output ranges, voltage	
• -10 V to +10 V	Yes
Output ranges, current	
• 0 to 20 mA	Yes
Load impedance (in rated range of output)	
• with voltage outputs, min.	1 000 Ω

- with current outputs, max.

600 Ω

Analog value generation for the outputs

Integration and conversion time/resolution per channel

- Resolution (incl. overrange)

Voltage: 14 bit; Current : 13 bit

Errors/accuracies

Temperature error (relative to output range), (+/-)

25 °C ±0.3%, to 55 °C ±0.6% total measurement range

Basic error limit (operational limit at 25 °C)

- Voltage, relative to output range, (+/-)
- Current, relative to output range, (+/-)

0.3 %

0.3 %

Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, f_1 = interference frequency

- Common mode voltage, max.

12 V

Interrupts/diagnostics/status information

Alarms

Yes

Diagnostics function

Yes

Alarms

- Diagnostic alarm

Yes

Diagnostic messages

- Monitoring the supply voltage
- Wire-break
- Short-circuit

Yes

Yes

Yes

Diagnostics indication LED

- for status of the outputs
- for maintenance

Yes

Yes

Degree and class of protection

IP degree of protection

IP20

Ambient conditions

Free fall

- Fall height, max.

0.3 m; five times, in product package

Ambient temperature during operation

- min.
- max.

-40 °C; = Tmin (incl. condensation/frost); start-up @ -25 °C

70 °C; = Tmax

Ambient temperature during storage/transportation

- min.
- max.

-40 °C

70 °C

Altitude during operation relating to sea level

- Installation altitude above sea level, max.
- Ambient air temperature-barometric pressure-altitude

5 000 m

Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) //
Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)

Relative humidity

<ul style="list-style-type: none"> • Operation at 25 °C without condensation, max. • With condensation, tested in accordance with IEC 60068-2-38, max. 	<p>95 %</p> <p>100 %; RH incl. condensation/frost (no commissioning under condensation conditions)</p>
Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
Conformal coating	
<ul style="list-style-type: none"> • Coatings for printed circuit board assemblies acc. to EN 61086 • Protection against fouling acc. to EN 60664-3 • Military testing according to MIL-I-46058C, Amendment 7 • Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A 	<p>Yes</p> <p>Yes; Type 1 protection</p> <p>Yes; Discoloration of coating possible during service life</p> <p>Yes; Conformal coating, Class A</p>
Connection method	
required front connector	Yes
Mechanics/material	
Enclosure material (front)	

• Plastic

Yes

Dimensions

Width	45 mm
Height	100 mm
Depth	75 mm

Weights

Weight, approx. 180 g

last modified: 05/15/2020