

SIPLUS S7-300 SM 326F DI8 NAMUR for medial exposure with conformal coating based on 6ES7326-1RF01-0AB0 . Digital "input ""SM 326, 8 DI; 24 V DC," "NAMUR,""" fail-safe NAMUR input" for SIMATIC S7 F-systems, up to Category 4 (EN 954-1)/ SIL3 (IEC 61508)/PLE (ISO 13849), 1x 40-pole



### Supply voltage

Reverse polarity protection	Yes
-----------------------------	-----

### Input current

from load voltage L+ (without load), max.	160 mA
from backplane bus 5 V DC, max.	90 mA

### Encoder supply

Number of outputs	8
Type of output voltage	8.2 V DC

### Power loss

Power loss, typ.	4.5 W
------------------	-------

### Digital inputs

Number of digital inputs	8
--------------------------	---

### Number of simultaneously controllable inputs

all mounting positions

— up to 40 °C, max.	8
— up to 60 °C, max.	8

### Input voltage

• Type of input voltage	DC
<b>Input current</b>	
• for signal "0", max. (permissible quiescent current)	0.35 to 1.2 mA
• for signal "1", typ.	2.1 to 7 mA
<b>Input delay (for rated value of input voltage)</b>	
for NAMUR inputs	
— at "0" to "1", max.	1.2 to 3 ms
— at "1" to "0", max.	1.2 to 3 ms
<b>Cable length</b>	
• shielded, max.	200 m
• unshielded, max.	100 m
<b>Interrupts/diagnostics/status information</b>	
<b>Alarms</b>	
• Diagnostic alarm	Yes; Parameterizable
<b>Diagnostics indication LED</b>	
• Fail-safe operation	Yes
• Group error SF (red)	Yes
<b>Ex(i) characteristics</b>	
Module for Ex(i) protection	Yes
<b>Maximum values of input circuits (per channel)</b>	
• Co (permissible external capacity), max.	3 µF
• Io (short-circuit current), max.	13.9 mA
• Lo (permissible external inductivity), max.	80 mH
• Po (power of load), max.	33.1 mW
• Uo (output no-load voltage), max.	10 V
• Um (fault voltage), max.	60 V DC/30 V AC
• Ta (permissible ambient temperature), max.	60 °C
<b>Potential separation</b>	
<b>Potential separation digital inputs</b>	
• between the channels	Yes
• between the channels and backplane bus	Yes
• between the channels and the power supply of the electronics	Yes
<b>Standards, approvals, certificates</b>	
CE mark	Yes
<b>Highest safety class achievable in safety mode</b>	
• acc. to EN 954	Cat. 4
• Performance level according to ISO 13849-1	PLe
• SIL acc. to IEC 61508	SIL 2 (single-channel), SIL 3 (two-channel)

Ambient conditions	
Ambient temperature during operation	
• min.	0 °C; = Tmin
• max.	60 °C; = Tmax
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	2 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m)
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
Connection method	
required front connector	1x 40-pin
Dimensions	
Width	80 mm
Height	125 mm
Depth	120 mm
Weights	

---

Weight, approx.

482 g

**last modified:**

05/15/2020