

Product type designation

SIPLUS SINAUT ST7, TIM 3V-IE

SIPLUS ST7 TIM 3V-IE -25...+70 °C with conformal coating based on 6NH7800-3BA00 . communication module for "SIMATIC S7-300 and C7; with" one RS232 interface for SINAUT communication via classic WAN and an RJ45 interface for SINAUT communication via an IP-based network (WAN or LAN)



Transfer rate

Transfer rate

- | | |
|---|--------------------|
| <ul style="list-style-type: none"> • for Industrial Ethernet | 10 ... 100 Mbit/s |
| <ul style="list-style-type: none"> • acc. to RS 232 | 50 ... 38400 bit/s |

Interfaces

Number of interfaces / acc. to Industrial Ethernet	1
Number of electrical connections	
<ul style="list-style-type: none"> • for external data transmission / acc. to RS 232 	1
<ul style="list-style-type: none"> • for power supply 	1
Type of electrical connection	
<ul style="list-style-type: none"> • of Industrial Ethernet interface 	RJ45 port
Type of electrical connection	
<ul style="list-style-type: none"> • at interface 1 / for external data transmission 	9 pin Sub-D-connector (RS232)
<ul style="list-style-type: none"> • for power supply 	2-pole plugable terminal block
design of the removable storage / C-PLUG	No

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
---	----

Supply voltage	24 V
Supply voltage	20.4 ... 28.8 V
Supply voltage / external / at DC / Rated value	24 V
Supply voltage / external / at DC / rated value	20.4 ... 28.8 V
Relative symmetrical tolerance / at DC	
• at 5 V	5 %
Relative positive tolerance / at DC / at 24 V	5 %
Relative negative tolerance / at DC / at 24 V	5 %
Consumed current	
• from backplane bus / at DC / at 24 V / maximum	0.2 A
• from external supply voltage / at DC / at 24 V / maximum	0.2 A
Power loss [W]	5.8 W
Product extension / optional / Backup battery	No

Ambient conditions	
Ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Installation altitude / at height above sea level / maximum	5000 m
Ambient condition / relating to ambient temperature - air pressure - installation altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
• with condensation / acc. to IEC 60068-2-38 / maximum	100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation
Chemical resistance / to commercially available cooling lubricants	Yes; incl. airborne diesel and oil droplets
Resistance to biologically active substances	
• conformity acc. to EN 60721-3-3	Yes; Class 3B2 mold and fungal spores (excluding fauna), Class 3B3 on request
• conformity acc. to EN 60721-3-6	Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)
Resistance to chemically active substances	
• conformity acc. to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray in accordance with EN 60068-2-52 (Severity 3). The supplied plug covers must remain in place on the unused interfaces during operation.
• conformity acc. to EN 60721-3-6	Yes
Resistance to mechanically active substances	
• conformity acc. to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.

<ul style="list-style-type: none"> conformity acc. to EN 60721-3-6 	Yes; Class 6S3 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
Coating / for equipped printed circuit board / acc. to EN 61086	Yes; Class 2 for high availability
Type of coating / protection against pollution according to EN 60664-3	Yes; Protection of the type 1
Type of test / of the coating / acc. to MIL-I-46058C	Yes; Coating discoloration during service life possible
Product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies acc. to IPC-CC-830A	Yes; Conformal coating, class A
Protection class IP	IP20

Design, dimensions and weights

Module format	Compact module S7-300 single width
Width	40 mm
Height	125 mm
Depth	120 mm
Net weight	0.2 kg

Product features, product functions, product components / general

Number of units <ul style="list-style-type: none"> per CPU / maximum 	1
Wire length <ul style="list-style-type: none"> with RS 232 interface / maximum 	6 m

Performance data / S7 communication

Number of possible connections / for S7 communication <ul style="list-style-type: none"> maximum with PG connections / maximum with OP connections / maximum 	12 4 8
Service <ul style="list-style-type: none"> SINAUT ST7 via S7 communication PG/OP communication 	Yes Yes

Performance data / multi-protocol mode

Number of active connections / with multi-protocol mode	12
---	----

Performance data / telecontrol

Suitability for use <ul style="list-style-type: none"> Node station substation TIM control center 	No Yes Yes
Protocol / is supported <ul style="list-style-type: none"> SINAUT ST1 protocol SINAUT ST7 protocol 	Yes Yes

Storage capacity	
<ul style="list-style-type: none"> Note 	TD7onCPU: at least 20 KB, actual requirement determined by data volume and functional scope TD7onTIM: 0 bytes in most favorable case
Product feature / Buffered message frame memory	No
Transmission format	
<ul style="list-style-type: none"> for SINAUT ST1 protocol with polling / 11 bit 	Yes
<ul style="list-style-type: none"> for SINAUT ST1 protocol with spontaneous / 10-bit or 11-bit 	Yes
<ul style="list-style-type: none"> for SINAUT ST7 protocol with multi-master polling / 10-bit 	Yes
<ul style="list-style-type: none"> for SINAUT ST7 protocol with polling or spontaneous / 10-bit or 11-bit 	Yes
Operating mode for scanning of data transmission	
<ul style="list-style-type: none"> with dedicated line/radio link / with SINAUT ST1 protocol 	Polling, polling with time slot procedure
<ul style="list-style-type: none"> with dedicated line/radio link / with SINAUT ST7 protocol 	Polling, polling with time slot procedure, multi-master polling with time slot procedure
<ul style="list-style-type: none"> with dial-up network / with SINAUT ST1 protocol 	spontaneous
<ul style="list-style-type: none"> with dial-up network / with SINAUT ST7 protocol 	spontaneous
Hamming distance	
<ul style="list-style-type: none"> for SINAUT ST1 protocol 	4
<ul style="list-style-type: none"> for SINAUT ST7 protocol 	4

Product functions / management, configuration, engineering

Configuration software	
<ul style="list-style-type: none"> required 	SINAUT ST7 ES
<ul style="list-style-type: none"> for CPU configuring / required / SINAUT TD7 block library for CPU 	Yes
<ul style="list-style-type: none"> for PG configuring / required / SINAUT ST7 configuration software for PG 	Yes
Storage location / of TIM configuration data	on the CPU

Product functions / Security

Operating mode / Virtual Private Network (VPN)	Yes
Type of authentication / with Virtual Private Network / PSK	Yes

Further information / Internet-Links

Internet-Link	
<ul style="list-style-type: none"> to website: Selector SIMATIC NET SELECTION TOOL 	http://www.siemens.com/snst
<ul style="list-style-type: none"> to website: Industrial communication 	http://www.siemens.com/simatic-net
<ul style="list-style-type: none"> to website: Industry Mall 	http://www.siemens.com/industrial-controls/mall

- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/automation/net/catalog>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<http://support.automation.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a comprehensive industrial security concept. Siemens products and solutions undergo continuous development with this factor in mind. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Products used from other manufacturers should also be taken into account here. You can find more information on Industrial Security at <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for our product-specific newsletter. You can find more information on this at <http://support.automation.siemens.com>. Version 3.4
14.11.2013- Siemens AG, I IA L CG, Nuremberg

last modified:

05/25/2020