

Industrial USB hub 4 with 4 USB 2.0 sockets, for access to the USB interface of a installed device, without opening the control cabinet, Mounting onto standard rail possible, suitable for Standard USB interfaces Further information, Quantity and content: see technical data



General information	
Product type designation	Industrial USB Hub 4
Installation type/mounting	
Rail mounting	Yes; Standard - DIN rail
Mounting in landscape format possible	Yes
Supply voltage	
Type of supply voltage	24 V DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Interfaces	
Number of USB interfaces	4; Type USB 2.0, 500 mA each; e.g. connection of mouse, keyboard, printer, USB stick, USB IPC flash drive
Degree and class of protection	
IP (at the front)	IP65
IP (rear)	IP20
Standards, approvals, certificates	

CE mark	Yes
cULus	Yes; UL for US, UL for Canada
RCM (formerly C-TICK)	Yes; C-Tick
KC approval	No
Suitable for safety functions	No

Ambient conditions

Ambient temperature during operation	
<ul style="list-style-type: none"> • Operation (vertical installation) <ul style="list-style-type: none"> — For vertical installation, min. — For vertical installation, max. 	0 to +50 °C 0 °C 50 °C
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> • min. • max. 	-20 °C 60 °C
Relative humidity	
<ul style="list-style-type: none"> • Operation, max. 	90 %

Mechanics/material

Enclosure material (front)	
<ul style="list-style-type: none"> • Plastic 	Yes

Dimensions

Width of the housing front	212 mm
Height of housing front	156 mm
Overall depth	50 mm

Weights

Weight without packaging	460 g
--------------------------	-------

Scope of supply

Delivery quantity in pieces	1; Content: 1x USB Hub 4, 10x plastic mounting clip, 1x female 2-pin connector
-----------------------------	--

Other

Merchandise	Yes
Manufacturer name	SIEMENS AG
Manufacturer's address	Gleiwitzerstraße 555, 90475 Nuremberg, Germany
Target devices	for access to the USB interface of a built-in device without having to open the control cabinet, mounting on standard rail possible, suitable for standard USB interfaces
Note:	TP1500 Comfort Outdoor, TP700 Comfort Outdoor: Observe the temperature range

Usable in the following products

<ul style="list-style-type: none"> • Product 1 • Product 2 • Product 3 • Product 4 	6AV6642-* 6AV6643-0* 6AV6643-7BA00-* 6AV6643-7CD00-*
--	---

- Product 5
- Product 6
- Product 7
- Product 8
- Product 9
- Product 10
- Product 11
- Product 12
- Product 13
- Product 14
- Product 15
- Product 16

last modified:

6AV6643-7DD00-*
6AV6644-*
6AV6640-0CA11-*
6av2124-0*
6AV2124-1*
6AV2124-2*
6AV6643-8*
6AV2123-2*
6AV2128-3*
[6AV2143-8GB50-0AA0](#)
[6AV2143-8JB50-0AA0](#)
[6AV2143-8MB50-0AA0](#)

05/28/2020