

USB keyboard INT, KV25605 INOX with IP67 USB connector type A, inclusive protective cap, vandalproof, desktop keyboard for devices with suitable interface, keyboard bottom with mounting option, additional information, amount and content see technical data



General information	
Product type designation	USB keyboard international US
Control elements	
Version of actuating element	Long-stroke key with 2 mm contact travel
Operating principle of the actuating element	Carbon pellet on gold-plated PCB
Input device	
<ul style="list-style-type: none"> <li>• Scroll wheel</li> <li>• Movement tracking</li> </ul>	No; Cursor control possible, left and right mouse button Capacitive touchpad
Keyboard fonts	
<ul style="list-style-type: none"> <li>• Design</li> <li>• Keyboard assignment</li> <li>• Color of the buttons</li> <li>• Color of the key inscription</li> <li>• Key illumination</li> <li>• Function keys                             <ul style="list-style-type: none"> <li>— Number of function keys</li> <li>— Number of function keys with LEDs</li> <li>— Programmable</li> </ul> </li> </ul>	Keyboard with long-stroke keys 86 (International QWERTY, US version) Stainless steel Black, laser-inscribed No Yes 12 0 No

• Number pad	Yes; Integrated into key layout
• Status LED displays	Yes; Num, FN, Shift, Scroll lock
— for number pad	Yes
— for Shift keys	Yes
<b>Connection type</b>	
• USB	Yes; USB 2.0 type A
• PS/2	No
• Cable length	0 m; See cable length
<b>Frame size/design</b>	
• Standard	Yes; For industrial applications
<b>Installation type/mounting</b>	
Mounting	Desktop, PRO support arm, drawer
Mounting type	Suitable for PRO devices
<b>Supply voltage</b>	
Rated value (DC)	5 V; 4.35 V to 5.25 V (USB)
<b>Input current</b>	
Current consumption (rated value)	55 mA; including touchpad and LED
<b>Battery</b>	
Battery-operated	No; maintenance-free
<b>Interfaces</b>	
Number of USB interfaces	1; USB 2.0 (IP67 plug enclosure)
<b>EMC</b>	
Emission of radio interference acc. to EN 55 011	
• Limit class A, for use in industrial areas	Yes; EN 55022, EN 55024
<b>Degree and class of protection</b>	
IP65 (all-round)	Yes
IP (at the front)	USB plug, meets IP67 with screws, if only inserted then without IP
<b>Standards, approvals, certificates</b>	
CE mark	Yes
UL approval	Yes; Available soon
cULus	Yes; Available soon
EAC (formerly Gost-R)	Yes; Available soon
CCC	No; not necessary
RoHS conformity	Yes
China RoHS compliance	Yes; Available soon
Suitable for safety functions	No
<b>Ambient conditions</b>	
Suited for indoor use	Yes
Suited for outdoor use	No; > 0 °C possible under certain conditions

<b>Ambient temperature during operation</b>	
• min.	0 °C
• max.	60 °C
<b>Ambient temperature during storage/transportation</b>	
• min.	-25 °C
• max.	85 °C
<b>Relative humidity</b>	
• Operation, max.	80 %; no condensation
• Condensation permissible	No
<b>Operating systems</b>	
<b>Runs under operating system</b>	
• Windows CE	Yes
• Windows Vista	Yes
• Windows XP	Yes
• Windows 7	Yes
• Windows 8	Yes
• Windows 10	Yes
<b>Cables</b>	
Cable length	0.4 m; USB
<b>Mechanics/material</b>	
<b>Material</b>	
• Stainless steel	Yes; Front stainless steel AISI 304
Enclosure material (rear)	aluminum
Material of the front ring	Generally silicone-free PORON seal
Enclosure color (front)	INOX AISI 304
Enclosure color (rear)	Aluminum paint
<b>Torques/forces</b>	
• Breakdown torque	1.5 N·m; Switching force buttons 1.5 N to 1.8 N
<b>Service life</b>	
• Number of operating cycles, keys	20 000 000; Operations (minimum)
<b>Dimensions</b>	
Width	369 mm
Height	18 mm
Depth	130 mm; Without cable outlet (with + 3 cm)
<b>Scope of supply</b>	
Delivery quantity in pieces	1
<b>Other</b>	
printable with laser printer	No; Layout change possible, one-off costs around € 2 000
Merchandise	Yes; GETT KV27610 / VES001681
Manufacturer name	GETT Gerätetechnik GmbH

Manufacturer's address	Mittlerer Ring 1, 08233 Treuen (Vogtland), Germany
Target devices	For SIMATIC HMI devices and IPCs with the appropriate slot
<b>Usable in the following products</b>	
• Product 1	6AV2124-*
• Product 2	6AV2125-*
• Product 3	6AV2145-*
• Product 4	6AV7250-*
• Product 5	6AV7251-*
• Product 6	6AV7863-7*
• Product 7	6AV2128-3*
• Product 8	<a href="#">6AV6642-0BD01-3AX0</a>
• Product 9	<a href="#">6AV6642-0BC01-1AX1</a>
• Product 10	<a href="#">6AV6642-0DC01-1AX0</a>
• Product 11	<a href="#">6AV6642-0DA01-1AX0</a>
• Product 12	<a href="#">6AV6642-0EA01-3AX0</a>
• Product 13	<a href="#">6AV6545-0CC10-0AX0</a>
• Product 14	6AV6545-0AH10-0AX*
• Product 15	<a href="#">6AV6545-0DA10-0AX0</a>
• Product 16	<a href="#">6AV6545-0DB10-0AX0</a>
• Product 17	6AV6643-*
• Product 18	6AV6644-*

**last modified:**

05/28/2020