

USB keyboard INT for 4:3 PRO devices, in stainless steel, RAL9023 (gray), with numerical keypad, inclination adjustable Further information, Quantity and content: see technical data



## General information

Product type designation      USB-INOX keyboard PRO, mouse keys

## Control elements

### Keyboard fonts

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• Design</li> <li>• Keyboard assignment</li> <li>• Color of the buttons</li> <li>• Color of the key inscription</li> <li>• Key illumination</li> <li>• Function keys                             <ul style="list-style-type: none"> <li>— Number of function keys</li> </ul> </li> <li>• Number pad</li> <li>• Status LED displays                             <ul style="list-style-type: none"> <li>— for number pad</li> <li>— for Shift keys</li> </ul> </li> </ul> | <p>Keyboard with short-stroke keys</p> <p>English</p> <p>Stainless steel</p> <p>Black</p> <p>No</p> <p>12</p> <p>Yes; Free-standing</p> <p>Yes; Num, Caps and Scroll</p> <p>Yes</p> <p>Yes</p> |
|--|--|

### Connection type

- |   |                              |
|---|------------------------------|
| <ul style="list-style-type: none"> <li>• USB</li> <li>• PS/2</li> </ul> | <p>Yes; Type A</p> <p>No</p> |
|---|------------------------------|

• Cable length	1.5 m; Typical
<b>Frame size/design</b>	
• Standard	Yes; For industrial applications
• Ergonomic	Yes; 90° adjustable / tiltable
<b>Ergonomics</b>	
• Trackball rest	No
• Adjustable height	Yes; By adjusting inclination angle 0° to 90°
<b>Installation type/mounting</b>	
Mounting	Max. load bearing capacity of 2 kg
Mounting type	Suitable for PRO devices
Mounting position	Horizontal
maximum permissible angle of inclination without external ventilation	90°; Between 0° and 90° in steps of 15°
<b>Supply voltage</b>	
Type of supply voltage	via USB
<b>Input current</b>	
Current consumption (rated value)	100 mA; Typical
<b>Degree and class of protection</b>	
IP65 (all-round)	Yes
Splashproof	Yes
<b>Standards, approvals, certificates</b>	
CE mark	Yes
RoHS conformity	Yes
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
• min.	0 °C
• max.	45 °C
• Operation (vertical installation)	
— For vertical installation, min.	0 °C
— For vertical installation, max.	45 °C
• Operation (max. tilt angle)	
— At maximum tilt angle, min.	0 °C
— At maximum tilt angle, min.	45 °C
• Operation (max. tilt angle, portrait format)	
— At maximum tilt angle, min.	0 °C
— At maximum tilt angle, min.	45 °C
<b>Ambient temperature during storage/transportation</b>	
• min.	0 °C
• max.	50 °C
<b>Relative humidity</b>	

- Operation, max.
- Condensation permissible

80 %; no condensation  
No; Condensation not permissible

## Operating systems

### Runs under operating system

- |                 |     |
|-----------------|-----|
| • Windows CE    | Yes |
| • Windows Vista | Yes |
| • Windows XP    | Yes |
| • Windows 7     | Yes |
| • Windows 8     | Yes |
| • Windows 10    | Yes |

## Mechanics/material

### Material

- |                   |                              |
|-------------------|------------------------------|
| • Aluminum        | Yes; Powder-coated, RAL 9023 |
| • Stainless steel | Yes; Keyboard itself         |

### Service life

- |                                    |                                  |
|------------------------------------|----------------------------------|
| • Number of operating cycles, keys | 10 000 000; Operations (minimum) |
|------------------------------------|----------------------------------|

## Dimensions

Width	481 mm
Height	20 mm
Depth	171.6 mm

## Weights

Weight without packaging	3 600 g
Weight incl. packaging	5 300 g

## Scope of supply

Delivery quantity in pieces	1; With support arm bracket
-----------------------------	-----------------------------

## Other

Merchandise	Yes; Sasse no. 1580.9905879
Manufacturer name	Sasse Elektronik GmbH
Manufacturer's address	Berliner Straße 12, 91126 Schwabach, Germany
Target devices	Merchandise suitable for 4:3 PRO devices

**last modified:** 06/12/2020