

SITOP PSU8600 3AC 20A/4X5A PN
 SITOP PSU8600 3AC 20A/4x5A PN Stabilized power supply Input:
 400-500 V 3 AC output: 24 V DC/20 A/4x 5 A with PN/IE connection
 Integrated web server OPC UA server integrated



Input	
Input	3-phase AC
Rated voltage value V_{in} rated	400 ... 500 V
Voltage range AC	320 ... 575 V
<ul style="list-style-type: none"> Note 	Derating 320 ... 360 and 530 ... 575 V
Wide-range input	Yes
Mains buffering	at $V_{in} = 400$ V; Prioritized supply Output 1 at power failure can be selected via DIP switch
Mains buffering at I_{out} rated, min.	15 ms; at $V_{in} = 400$ V; Prioritized supply Output 1 at power failure can be selected via DIP switch
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
Input current	
<ul style="list-style-type: none"> at rated input voltage 400 V at rated input voltage 500 V 	1.4 A 1.1 A
Switch-on current limiting (+25 °C), max.	14 A
I^2t , max.	1.2 A ² ·s
Built-in incoming fuse	none

Protection in the mains power input (IEC 898)	Required: 3-pole connected miniature circuit breaker 6 ... 16 A characteristic C or circuit breaker 3RV2011-1DA10 (setting 3 A) or 3RV2711-1DD10 (UL 489)
---	---

Output	
Output	Controlled, isolated DC voltage
Number of outputs	4
Rated voltage Vout DC	24 V
Output voltage	
<ul style="list-style-type: none"> • at output 1 at DC Rated value • at output 2 at DC Rated value • at output 3 at DC Rated value • at output 4 at DC Rated value 	24 V 24 V 24 V 24 V
Total tolerance, static ±	3 %
Static mains compensation, approx.	0.2 %
Static load balancing, approx.	0.1 %
Residual ripple peak-peak, max.	100 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	200 mV
Adjustment range	4 ... 28 V
Product function Output voltage adjustable	Yes
Output voltage setting	via potentiometer or IE/PN interface; Derating > 24 V: 4%/V; max. 120 W per output, max. 480 W overall system
Status display	3-color LED for operating state device; LED for operating mode manual/remote; 4 LEDs for communication PROFINET; 3-color LED per output for operating state output; LED green for parallel operation Output 1 and 2 / 3 and 4
Signaling	Relay contact (changeover contact, contact current capacity DC 60 V/0.3 A) for "Operating state OK"
On/off behavior	No overshoot of Vout (soft start)
Startup delay, max.	1 s; Without on-delay of the outputs
connection of outputs operating	Simultaneous connecting-in of all outputs after device booting or delay time of 25 ms, 100 ms or "load-optimized" for sequential cutting-in of the outputs via DIP switches can be set
Voltage increase time of the output voltage maximum	500 ms
Rated current value Iout rated	20 A
Output current	
<ul style="list-style-type: none"> • per output • at output 1 Rated value • at output 2 Rated value • at output 3 Rated value • at output 4 Rated value 	5 A 5 A 5 A 5 A 5 A
Current range	0 ... 20 A
<ul style="list-style-type: none"> • Note 	+50 ... +60 °C: Derating 2.5%/K; no derating in connection with expansion module CNX8600 and total load of the outputs at the basic device max. 240 W

Supplied active power typical	480 W
Product feature parallel switching of outputs	Yes; Parallel circuit Output 1 with 2 or Output 3 with 4 can be selected via DIP switch
Parallel switching for enhanced performance	No

Efficiency

Efficiency at V_{out} rated, I_{out} rated, approx.	93 %
Power loss at V_{out} rated, I_{out} rated, approx.	34 W
Power loss [W] during no-load operation maximum	12 W

Closed-loop control

Dynamic mains compensation (V_{in} rated $\pm 15\%$), max.	0.1 %
Dynamic load smoothing (I_{out} : 50/100/50 %), $U_{out} \pm$ typ.	0.4 %
Setting time maximum	10 ms

Protection and monitoring

Output overvoltage protection	< 35 V
Property of the output Short-circuit proof	Yes
Short-circuit protection	electronic overload cut-off; optionally constant current operation can be selected for Output 4 via DIP switches
adjustable response value current of current-dependent overload trip	0.5 ... 5 A
type of threshold value setting	via potentiometer or IE/PN interface
characteristics of electronic overload switch-off	$I_a > 1.0 \dots < 1.5 \times I_a$ threshold permissible for 5 s; I_a limit (= $1.5 \times I_a$ threshold) permissible for 200 ms
characteristics of constant current operation	I_a limit (= $1.5 \times I_a$ threshold) permissible for 5 s, afterwards I_a threshold continuous
Reset	via sensor per output or IE/PN interface
Remote reset	Non-electrically isolated 24 V input (signal level "high" at > 15 V)
Overcurrent overload capability in normal operation	Total system overloadable 150% I_a rated to 5 s/min
Overload/short-circuit indicator	3-color LED for operating state device; 3-color LED per output for operating state output

Interface

Specification interface	Ethernet/PROFINET
-------------------------	-------------------

Safety

Primary/secondary isolation	Yes
Galvanic isolation	Safety extra-low output voltage U_{out} acc. to EN 60950-1 and EN 50178
Protection class	Class I
Leakage current	
• maximum	3.5 mA
Degree of protection (EN 60529)	IP20

Approvals

CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
Explosion protection	IECEx Ex nA nC IIC T4 Gc; ATEX (EX) II 3G Ex nA nC IIC T4 Gc; cCSAus (CSA C22.2 No. 213, ANSI/ISA-12.12.01) Class I, Div. 2, Group ABCD, T4
FM approval	-
CB approval	Yes
Marine approval	ABS, DNV GL

EMC

Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

environmental conditions

Ambient temperature	
<ul style="list-style-type: none"> • during operation — Note • during transport • during storage 	<p>-25 ... +60 °C with natural convection</p> <p>-40 ... +85 °C</p> <p>-40 ... +85 °C</p>
Humidity class according to EN 60721	Climate class 3K3, 5 ... 95% no condensation

Mechanics

Connection technology	Plug-in terminals with screwed connection
Connections	
<ul style="list-style-type: none"> • Supply input • Output • Auxiliary • signaling contact 	<p>L1, L2, L3, PE: Plug-in terminal with 1 screwed connection each for 0.2 ... 4 mm² single-wire / fine stranded</p> <p>1, 2, 3, 4: Two plug-in terminals (1, 2 and 3, 4) with 2 screwed connections each for 0.2 ... 2.5 mm²; 0 V: Plug-in terminal with 3 screwed connections for 0.2 ... 4 mm²</p> <p>RST (Reset): Plug-in terminal (together with alarm signal) with 1 screwed connection for 0.2 ... 1.5 mm²</p> <p>11, 12, 14 (alarm signal): Plug-in terminal (together with Reset) with 1 screwed connection each for 0.2 ... 1.5 mm²</p>
Product function	
<ul style="list-style-type: none"> • removable terminal at input • removable terminal at output 	<p>Yes</p> <p>Yes</p>
Design of the interface for communication	PROFINET/Ethernet: two RJ45 sockets (2-port switch)
Suitability for interaction modular system	Yes
Width of the enclosure	100 mm
Height of the enclosure	125 mm
Depth of the enclosure	150 mm
Required spacing	
<ul style="list-style-type: none"> • top • bottom 	<p>50 mm</p> <p>50 mm</p>

<ul style="list-style-type: none"> • left • right 	0 mm
Weight, approx.	0 mm
Product feature of the enclosure housing for side-by-side mounting	2 kg
Installation	Yes
Electrical accessories	Snaps onto DIN rail EN 60715 35x15
Mechanical accessories	Expansion modules CNX8600, buffer modules BUF8600, module UPS8600
MTBF at 40 °C	Device identification label 20 mm × 7 mm, TI-grey 3RT2900-1SB20
Other information	243 178 h
	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)