

SIMATIC DP, ET 200ECO PN, 8 DI 24 V DC; 4xM12, Duplicate assignment, Degree of protection IP67



General information

Vendor identification (VendorID)	002AH
Device identifier (DeviceID)	0306H

Supply voltage

Rated value (DC)	24 V
Reverse polarity protection	Yes

Input current

Current consumption, typ.	100 mA
---------------------------	--------

Encoder supply

Number of outputs	4
24 V encoder supply	
<ul style="list-style-type: none"> Short-circuit protection 	Yes; Electronic
<ul style="list-style-type: none"> Output current, max. 	100 mA; per output

Power loss

Power loss, typ.	5.5 W
------------------	-------

Digital inputs

Number of digital inputs	8
--------------------------	---

• in groups of	2
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 60 °C, max.	8
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	-3 to +5V
• for signal "1"	+11 to +30V
Input current	
• for signal "1", typ.	7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	typically 3 ms
— at "1" to "0", max.	typically 3 ms
Cable length	
• unshielded, max.	30 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Interfaces	
Transmission procedure	100BASE-TX
Number of PROFINET interfaces	1
1. Interface	
Interface types	
• integrated switch	Yes
• M12 port	Yes
Interface types	
M12 port	
• Autonegotiation	Yes
• Autocrossing	Yes
• Transmission rate, max.	100 Mbit/s
Protocols	
Supports protocol for PROFINET IO	Yes
PROFINET CBA	No
PROFIsafe	No
PROFINET IO Device	

Services	
— IRT with the option "high flexibility"	Yes
— Prioritized startup	Yes
Redundancy mode	
Media redundancy	
— MRP	Yes
Open IE communication	
• TCP/IP	No
• SNMP	Yes
• DCP	Yes
• LLDP	Yes
• ping	Yes
• ARP	Yes
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnostic messages	
• Diagnostic information readable	Yes
• Monitoring the supply voltage	Yes; green "ON" LED
• Wire-break in signal transmitter cable	Yes
• Short-circuit encoder supply	Yes; Per channel group
• Group error	Yes; Red/yellow "SF/MT" LED
Potential separation	
between the load voltages	Yes
between load voltage and all other switching components	No
between Ethernet and electronics	Yes
Potential separation channels	
• between the channels	No
Isolation	
tested with	
• 24 V DC circuits	707 V DC (type test)
• Test voltage for interface, rms value [Vrms]	1 500 V; According to IEEE 802.3
Degree and class of protection	
IP degree of protection	IP65/67
Connection method	
Design of electrical connection	4/5-pin M12 circular connectors
Dimensions	
Width	30 mm

Height	200 mm
Depth	49 mm
Weights	
Weight, approx.	550 g
last modified:	06/09/2020