

SIMATIC DP, Electronic modules for ET 200 PRO 4 AI RTD High Feature, Pt100; PT200; PT500; Pt1000; NI100; NI200; NI500; NI1000; Channel diagnostics; incl. bus module, Connection module IO 6ES7194-4..00-0AA0 order separately



Figure similar

Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes; against destruction
Input current	
from supply voltage 1L+, max.	27 mA; Typical
from backplane bus 3.3 V DC, max.	10 mA; Typical
Power loss	
Power loss, typ.	0.7 W
Address area	
Address space per module	
• Address space per module, max.	8 byte
Analog inputs	
Number of analog inputs	4
Cycle time (all channels) max.	83 ms; 83 ms at 50 Hz; 69 ms at 60 Hz
Technical unit for temperature measurement adjustable	Yes; Degrees Celsius/degrees Fahrenheit

Input ranges (rated values), resistance thermometer	
• Cu 10	No
• Ni 100	Yes
— Input resistance (Ni 100)	10 000 kΩ
• Ni 1000	Yes
— Input resistance (Ni 1000)	10 000 kΩ
• Ni 120	Yes
— Input resistance (Ni 120)	10 000 kΩ
• Ni 200	Yes
— Input resistance (Ni 200)	10 000 kΩ
• Ni 500	Yes
— Input resistance (Ni 500)	10 000 kΩ
• Pt 100	Yes
— Input resistance (Pt 100)	10 000 kΩ
• Pt 1000	Yes
— Input resistance (Pt 1000)	10 000 kΩ
• Pt 200	Yes
— Input resistance (Pt 200)	10 000 kΩ
• Pt 500	Yes
— Input resistance (Pt 500)	10 000 kΩ
Input ranges (rated values), resistors	
• 0 to 150 ohms	Yes
— Input resistance (0 to 150 ohms)	10 000 kΩ
• 0 to 300 ohms	Yes
— Input resistance (0 to 300 ohms)	10 000 kΩ
• 0 to 600 ohms	Yes
— Input resistance (0 to 600 ohms)	10 000 kΩ
• 0 to 3000 ohms	Yes
— Input resistance (0 to 3000 ohms)	10 000 kΩ
Characteristic linearization	
• parameterizable	Yes
Cable length	
• shielded, max.	30 m
Analog value generation for the inputs	
Measurement principle	integrating
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	15 bit; at 150, 300, 600 und 3 000 ohms; otherwise 15 bits + sign
• Integration time (ms)	20 / 16,667
• Interference voltage suppression for interference frequency f1 in Hz	50 / 60 Hz

• Conversion time (per channel)	20.625 ms; 20.625 ms at 50 Hz; 17.25 ms at 60 Hz
Smoothing of measured values	
• parameterizable	Yes
• Step: None	Yes; 1x cycle time
• Step: low	Yes; 4x cycle time
• Step: Medium	Yes; 16x cycle time
• Step: High	Yes; 64x cycle time
Encoder	
Connection of signal encoders	
• for resistance measurement with two-wire connection	Yes; Line resistances are also measured
• for resistance measurement with three-wire connection	Yes
• for resistance measurement with four-wire connection	Yes
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.05 %
Temperature error (relative to input range), (+/-)	0.002 %/K
Crosstalk between the inputs, min.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.015 %
Operational error limit in overall temperature range	
• Resistance thermometer, relative to input range, (+/-)	0.175 %
Basic error limit (operational limit at 25 °C)	
• Resistance thermometer, relative to input range, (+/-)	0.125 %
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, f_1 = interference frequency	
• Series mode interference (peak value of interference < rated value of input range), min.	50 dB
• Common mode interference (USS < 2.5 V), min.	70 dB; Interference voltage < 5 V
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes; Parameterizable
• Hardware interrupt	No
Diagnostic messages	
• Diagnostic information readable	Yes
• Wire-break	Yes
• Overflow/underflow	Yes
Diagnostics indication LED	

- Group error SF (red)

Yes

Parameter

Measurement type/range

R4L / R3L / R2L / TR4L / TR3L / TR2L

Potential separation

Potential separation analog inputs

- between the channels
- between the channels and backplane bus

No

Yes

Isolation

Isolation tested with

707 V DC (type test)

Dimensions

Width

45 mm

Height

130 mm

Depth

35 mm

Weights

Weight, approx.

150 g

last modified:

06/09/2020