

SIMATIC S7-300, temperature Control Unit FM 355-2 C, 4 channels, continuous, 4 AI+8 DI+4 AO incl. multi-language configuration package, Manual and Getting Started (de, de, fr, en it) on CD-ROM



Figure similar

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
Input current	
from load voltage L+ (without load), max.	310 mA; Typ. 260 mA
from backplane bus 5 V DC, max.	75 mA; typ. 50 mA
Power loss	
Power loss, typ.	6.5 W
Power loss, max.	7.8 W
Digital inputs	
Number of digital inputs	8
Input characteristic curve in accordance with IEC 61131, type 2	Yes
Input voltage	

• Rated value (DC)	24 V
• for signal "0"	-3 to +5V
• for signal "1"	13 to 30V
Input current	
• for signal "1", typ.	7 mA
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Analog inputs	
Number of analog inputs	4
permissible input voltage for voltage input (destruction limit), max.	20 V
permissible input current for current input (destruction limit), max.	40 mA
Input ranges	
• Voltage	Yes
• Current	Yes
• Thermocouple	Yes
• Resistance thermometer	Yes
Input ranges (rated values), voltages	
• 0 to +10 V	Yes
— Input resistance (0 to 10 V)	100 k Ω
• -1.75 V to +11.75 V	Yes
— Input resistance (-1.75 V to +11.75 V)	100 k Ω
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	50 Ω
• 0 to 23.5 mA	Yes
— Input resistance (0 to 23.5 mA)	50 Ω
• -3.5 mA to +23.5 mA	Yes
— Input resistance (-3.5 mA to +23.5 mA)	50 Ω
• 4 mA to 20 mA	Yes
— Input resistance (4 mA to 20 mA)	50 Ω
Input ranges (rated values), thermocouples	
• Type B	Yes
— Input resistance (Type B)	10 M Ω
• Type E	Yes
— Input resistance (Type E)	10 M Ω
• Type J	Yes
— Input resistance (type J)	10 M Ω
• Type K	Yes
— Input resistance (Type K)	10 M Ω

• Type R	Yes
— Input resistance (Type R)	10 M Ω
• Type S	Yes
— Input resistance (Type S)	10 M Ω
Input ranges (rated values), resistance thermometer	
• Pt 100	Yes
— Input resistance (Pt 100)	10 M Ω
Thermocouple (TC)	
Temperature compensation	
— internal temperature compensation	Yes
— external temperature compensation with Pt100	Yes
Characteristic linearization	
• parameterizable	Yes
Cable length	
• shielded, max.	200 m; 50 m at 80 mV and thermocouples
Analog outputs	
Number of analog outputs	4
Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	25 mA
Current output, no-load voltage, max.	18 V
Output ranges, voltage	
• 0 to 10 V	Yes
• -10 V to +10 V	Yes
Output ranges, current	
• 0 to 20 mA	Yes
• 4 mA to 20 mA	Yes
Connection of actuators	
• for voltage output two-wire connection	Yes
• for current output two-wire connection	Yes
Load impedance (in rated range of output)	
• with voltage outputs, min.	1 k Ω
• with voltage outputs, capacitive load, max.	1 μ F
• with current outputs, max.	500 Ω
• with current outputs, inductive load, max.	1 mH
Cable length	
• shielded, max.	200 m; 50 m at 80 mV and thermocouples
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	14 bit

Analog value generation for the outputs

Settling time

- | | |
|-----------------------|--------|
| • for resistive load | 0.1 ms |
| • for capacitive load | 3.3 ms |
| • for inductive load | 0.5 ms |

Encoder

Connection of signal encoders

- | | |
|--|-----|
| • for voltage measurement | Yes |
| • for current measurement as 4-wire transducer | Yes |

Connectable encoders

- | | |
|---|--------|
| • 2-wire sensor | Yes |
| — permissible quiescent current (2-wire sensor), max. | 1.5 mA |

Errors/accuracies

Operational error limit in overall temperature range

- | | |
|--|---------------------------------|
| • Voltage, relative to input range, (+/-) | 0.6 %; ± 0.6 to ± 0.7 % |
| • Current, relative to input range, (+/-) | 0.6 %; ± 0.6 to ± 0.7 % |
| • Resistance thermometer, relative to input range, (+/-) | 0.6 %; ± 0.6 to ± 0.7 % |
| • Voltage, relative to output range, (+/-) | 0.5 % |
| • Current, relative to output range, (+/-) | 0.6 % |

Basic error limit (operational limit at 25 °C)

- | | |
|--|-----------------------------------|
| • Voltage, relative to input range, (+/-) | 0.04 %; ± 0.04 to ± 0.5 % |
| • Current, relative to input range, (+/-) | 0.04 %; ± 0.04 to ± 0.5 % |
| • Resistance thermometer, relative to input range, (+/-) | 0.04 %; ± 0.04 to ± 0.5 % |
| • Voltage, relative to output range, (+/-) | 0.4 % |
| • Current, relative to output range, (+/-) | 0.5 % |

Interrupts/diagnostics/status information

- | | |
|-------------------------------|----------------------|
| Substitute values connectable | Yes; Parameterizable |
|-------------------------------|----------------------|

Integrated Functions

- | | |
|---------|----|
| Counter | No |
|---------|----|

Control technology

- | | |
|-------------------------------------|---|
| • Number of closed-loop controllers | 4 |
|-------------------------------------|---|

Potential separation

Potential separation controller

- | | |
|--|------------------|
| • between the channels | No |
| • between the channels and backplane bus | Yes; Optocoupler |

Isolation

- | | |
|-----------------------|----------|
| Isolation tested with | 500 V DC |
|-----------------------|----------|

Connection method

required front connector 2x 20-pin

Dimensions

Width 80 mm

Height 125 mm

Depth 120 mm

Weights

Weight, approx. 470 g

last modified: 06/09/2020