

SIMATIC S7-400, analog input SM 431, isolated 8 AI, resolution 14 bit, U/I/Resistor/Thermocouple/Pt100



Figure similar

Supply voltage

Load voltage L+

- Rated value (DC) 24 V; Only required for supplying 2-wire transmitters
- Reverse polarity protection Yes

Input current

from load voltage L+ (without load), max.	200 mA; for 8 connected, fully controlled 2-wire transmitters
from backplane bus 5 V DC, max.	600 mA

Power loss

Power loss, typ.	3.5 W
------------------	-------

Analog inputs

Number of analog inputs	8
• For voltage/current measurement	8
• For resistance measurement	4
permissible input voltage for voltage input (destruction limit), max.	18 V; 18 V continuous, 75 V for 1 ms (mark to space ratio 1:20)

permissible input current for current input (destruction limit), max.	40 mA; Permanent
Input ranges	
• Voltage	Yes
• Current	Yes
• Thermocouple	Yes
• Resistance thermometer	Yes
• Resistance	Yes
Input ranges (rated values), voltages	
• 1 V to 5 V	Yes
— Input resistance (1 V to 5 V)	1 MΩ
• -1 V to +1 V	Yes
— Input resistance (-1 V to +1 V)	1 MΩ
• -10 V to +10 V	Yes
— Input resistance (-10 V to +10 V)	1 MΩ
• -2.5 V to +2.5 V	Yes
— Input resistance (-2.5 V to +2.5 V)	1 MΩ
• -250 mV to +250 mV	Yes
— Input resistance (-250 mV to +250 mV)	1 MΩ
• -5 V to +5 V	Yes
— Input resistance (-5 V to +5 V)	1 MΩ
• -500 mV to +500 mV	Yes
— Input resistance (-500 mV to +500 mV)	1 MΩ
• -80 mV to +80 mV	Yes
— Input resistance (-80 mV to +80 mV)	1 MΩ
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	50 Ω
• 4 mA to 20 mA	Yes
— Input resistance (4 mA to 20 mA)	50 Ω
Input ranges (rated values), thermocouples	
• Type B	Yes
— Input resistance (Type B)	1 MΩ
• Type E	Yes
— Input resistance (Type E)	1 MΩ
• Type J	Yes
— Input resistance (type J)	1 MΩ
• Type K	Yes
— Input resistance (Type K)	1 MΩ
• Type L	Yes
— Input resistance (Type L)	1 MΩ

• Type N	Yes
— Input resistance (Type N)	1 MΩ
• Type R	Yes
— Input resistance (Type R)	1 MΩ
• Type S	Yes
— Input resistance (Type S)	1 MΩ
• Type T	Yes
— Input resistance (Type T)	1 MΩ
• Type U	Yes
— Input resistance (Type U)	1 MΩ
Input ranges (rated values), resistance thermometer	
• Ni 100	Yes
— Input resistance (Ni 100)	1 MΩ
• Ni 1000	Yes
— Input resistance (Ni 1000)	1 MΩ
• Pt 100	Yes
— Input resistance (Pt 100)	1 MΩ
• Pt 1000	Yes
• Pt 10000	Yes
• Pt 200	Yes
— Input resistance (Pt 200)	1 MΩ
• Pt 500	Yes
— Input resistance (Pt 500)	1 MΩ
Input ranges (rated values), resistors	
• 0 to 48 ohms	Yes
— Input resistance (0 to 48 ohms)	1 MΩ
• 0 to 150 ohms	Yes
— Input resistance (0 to 150 ohms)	1 MΩ
• 0 to 300 ohms	Yes
— Input resistance (0 to 300 ohms)	1 MΩ
• 0 to 600 ohms	Yes
— Input resistance (0 to 600 ohms)	1 MΩ
• 0 to 6000 ohms	Yes; Usable up to 5000 Ohm
— Input resistance (0 to 6000 ohms)	1 MΩ
Thermocouple (TC)	
Temperature compensation	
— parameterizable	Yes
— internal temperature compensation	No
— external temperature compensation with Pt100	Yes
— external temperature compensation with compensations socket	Yes

— dynamic reference temperature value	Yes
Characteristic linearization	
• parameterizable	Yes
Cable length	
• shielded, max.	200 m; 50 m with thermocouples and input ranges $\leq 80 \text{ mV}$
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	14 bit; with activated filtering: 16 bit
• Integration time, parameterizable	Yes
• Basic conversion time (ms)	20.1 / 23.5 ms
• Integration time (ms)	16.7 / 20 ms
• Interference voltage suppression for interference frequency f_1 in Hz	50 / 60 Hz
Encoder	
Connection of signal encoders	
• for voltage measurement	Yes; possible
• for current measurement as 2-wire transducer	Yes
• for current measurement as 4-wire transducer	Yes
• for resistance measurement with two-wire connection	Yes; Line resistances are also measured
• for resistance measurement with three-wire connection	Yes
• for resistance measurement with four-wire connection	Yes
Errors/accuracies	
Operational error limit in overall temperature range	
• Voltage, relative to input range, (+/-)	0.38 %; $\pm 0.38\% \text{ at } \pm 80 \text{ mV}; \pm 0.35\% \text{ at } \pm 250 \text{ mV}, \pm 500 \text{ mV}, \pm 1 \text{ V}, \pm 2.5 \text{ V}, \pm 5 \text{ V}, 1 \text{ to } 5 \text{ V}, \pm 10 \text{ V}$
• Current, relative to input range, (+/-)	0.35 %; $\pm 20 \text{ mA}, 0 \text{ to } 20 \text{ mA}, 4 \text{ to } 20 \text{ mA}$
• Resistance, relative to input range, (+/-)	0.5 %
• Resistance thermometer, relative to input range, (+/-)	0.5 %
• Thermocouple, relative to input range, (+/-)	TC Type B ($\pm 14.8 \text{ K}$), TC Type R ($\pm 9.4 \text{ K}$), TC Type S ($\pm 10.6 \text{ K}$), TC Type T ($\pm 2.2 \text{ K}$), TC Type E ($\pm 4.0 \text{ K}$), TC Type J ($\pm 5.2 \text{ K}$), TC Type K ($\pm 7.6 \text{ K}$), TC Type U ($\pm 3.5 \text{ K}$), TC Type L ($\pm 5.1 \text{ K}$), TC Type N ($\pm 5.5 \text{ K}$)
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to input range, (+/-)	0.15 %; $\pm 0.15\% (\pm 250 \text{ mV}, \pm 500 \text{ mV}, \pm 1 \text{ V}, \pm 2.5 \text{ V}, \pm 5 \text{ V}, 1 \text{ to } 5 \text{ V}, \pm 10 \text{ V}); \pm 0.17\% (\pm 80 \text{ mV})$
• Current, relative to input range, (+/-)	0.15 %; $\pm 20 \text{ mA}, 0 \text{ to } 20 \text{ mA}, 4 \text{ to } 20 \text{ mA}$

• Resistance, relative to input range, (+/-)	0.15 %; ±0.15 % at 0 to 48 ohms (4-conductor measurement), 0 to 150 ohms (4-conductor measurement), 0 to 300 ohms (4-conductor measurement), 0 to 600 ohms (4-conductor measurement), 0 to 5000 ohms (4-conductor measurement, in range of 6000 ohms); ±0.3 % at 0 to 300 ohms (3-conductor measurement), 0 to 600 ohms (3-conductor measurement), 0 to 5000 ohms (3-conductor measurement, in range of 6000 ohms)
• Resistance thermometer, relative to input range, (+/-)	0.3 %
• Thermocouple, relative to input range, (+/-)	TC Type B (±8.2 K), TC Type R (±5.2 K), TC Type S (±5.9 K), TC Type T (±1.2 K), TC Type E (±1.8 K), TC Type J (±2.3 K), TC Type K (±3.4 K), TC Type U (±1.8 K), TC Type L (±2.3 K), TC Type N (±2.9 K)

Interrupts/diagnostics/status information

Diagnostics function	No
----------------------	----

Potential separation

Potential separation analog inputs	
• Potential separation analog inputs	Yes; internal/external
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes

Isolation

Isolation tested with	2 120 V DC between bus and L+/M; 2 120 V DC between bus and analog section; 500 V DC between bus and local ground; 500 V DC between analog section and L+/M; 2 120 V DC between analog section and local ground; 2 120 V DC between L+/M and local ground
-----------------------	---

Dimensions

Width	25 mm
Height	290 mm
Depth	210 mm

Weights

Weight, approx.	500 g
-----------------	-------

last modified:

06/09/2020