

SIMATIC S7-1500 Analog output module AQ8xU/I HS, 16 bit resolution, accuracy 0.3%, 8 channels in groups of 8; Diagnostics; Substitute value 8 channels in 0.125 ms Oversampling; Delivery including infeed element, shield bracket and shield terminal: Front connector (screw terminals or push-in) to be ordered separately



Figure similar

| General information  |                   |
|--|-------------------|
| Product type designation   | AQ 8xU/I HS       |
| HW functional status   | FS01              |
| Firmware version   | V2.1.0            |
| <ul style="list-style-type: none"> <li>FW update possible</li> </ul>                                     | Yes               |
| Product function   |                   |
| <ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>   | Yes; I&M0 to I&M3 |
| <ul style="list-style-type: none"> <li>Prioritized startup</li> </ul>                                    | No                |
| <ul style="list-style-type: none"> <li>Output range scalable</li> </ul>                                  | No                |
| Engineering with   |                   |
| <ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul> | V14 / -           |
| <ul style="list-style-type: none"> <li>STEP 7 configurable/integrated from version</li> </ul>            | V5.5 SP3 / -      |
| <ul style="list-style-type: none"> <li>PROFIBUS from GSD version/GSD revision</li> </ul>                 | V1.0 / V5.1       |
| <ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>                 | V2.3 / -          |
| Operating mode   |                   |
| <ul style="list-style-type: none"> <li>Oversampling</li> </ul>   | Yes               |

- MSO

Yes

### CiR – Configuration in RUN

|                                    |     |
|------------------------------------|-----|
| Reparameterization possible in RUN | Yes |
| Calibration possible in RUN        | Yes |

### Supply voltage

|                                     |        |
|-------------------------------------|--------|
| Type of supply voltage              | DC     |
| Rated value (DC)                    | 24 V   |
| permissible range, lower limit (DC) | 20.4 V |
| permissible range, upper limit (DC) | 28.8 V |
| Reverse polarity protection         | Yes    |

### Input current

|                           |                             |
|---------------------------|-----------------------------|
| Current consumption, max. | 260 mA; with 24 V DC supply |
|---------------------------|-----------------------------|

### Power

|  |        |
|--|--------|
| Power available from the backplane bus | 1.15 W |
|--|--------|

### Power loss

|                  |     |
|------------------|-----|
| Power loss, typ. | 7 W |
|------------------|-----|

### Analog outputs

|   |   |
|---|---|
| Number of analog outputs                    | 8   |
| Voltage output, short-circuit protection    | Yes   |
| Voltage output, short-circuit current, max. | 45 mA   |
| Current output, no-load voltage, max.       | 20 V  |
| Cycle time (all channels), min.             | 125 µs; independent of number of activated channels |

### Output ranges, voltage

|                  |     |
|------------------|-----|
| • 0 to 10 V      | Yes |
| • 1 V to 5 V     | Yes |
| • -5 V to +5 V   | No  |
| • -10 V to +10 V | Yes |

### Output ranges, current

|                    |     |
|--------------------|-----|
| • 0 to 20 mA       | Yes |
| • -20 mA to +20 mA | Yes |
| • 4 mA to 20 mA    | Yes |

### Connection of actuators

|   |     |
|---|-----|
| • for voltage output two-wire connection  | Yes |
| • for voltage output four-wire connection | Yes |
| • for current output two-wire connection  | Yes |

### Load impedance (in rated range of output)

|   |        |
|---|--------|
| • with voltage outputs, min.                  | 1 kΩ   |
| • with voltage outputs, capacitive load, max. | 100 nF |
| • with current outputs, max.                  | 500 Ω  |
| • with current outputs, inductive load, max.  | 1 mH   |

|  |  |
|--|--|
| <b>Cable length</b>  |  |
| • shielded, max.   | 200 m  |
| <b>Analog value generation for the outputs</b>                             |  |
| <b>Integration and conversion time/resolution per channel</b>              |  |
| • Resolution with overrange (bit including sign), max.                     | 16 bit   |
| • Conversion time (per channel)  | 50 µs; independent of number of activated channels |
| <b>Settling time</b>   |  |
| • for resistive load   | 30 µs; see additional description in the manual    |
| • for capacitive load  | 100 µs; see additional description in the manual   |
| • for inductive load   | 100 µs; see additional description in the manual   |
| <b>Errors/accuracies</b>   |  |
| Output ripple (relative to output range, bandwidth 0 to 50 kHz), (+/-)     | 0.02 %   |
| Linearity error (relative to output range), (+/-)                          | 0.15 %   |
| Temperature error (relative to output range), (+/-)                        | 0.002 %/K  |
| Crosstalk between the outputs, max.  | -100 dB  |
| Repeat accuracy in steady state at 25 °C (relative to output range), (+/-) | 0.05 %   |
| <b>Operational error limit in overall temperature range</b>                |  |
| • Voltage, relative to output range, (+/-)                                 | 0.3 %  |
| • Current, relative to output range, (+/-)                                 | 0.3 %  |
| <b>Basic error limit (operational limit at 25 °C)</b>                      |  |
| • Voltage, relative to output range, (+/-)                                 | 0.2 %  |
| • Current, relative to output range, (+/-)                                 | 0.2 %  |
| <b>Isochronous mode</b>  |  |
| Execution and activation time (TCO), min.                                  | 100 µs   |
| Bus cycle time (TDP), min.   | 250 µs   |
| <b>Interrupts/diagnostics/status information</b>                           |  |
| Diagnostics function   | Yes  |
| Substitute values connectable  | Yes  |
| <b>Alarms</b>  |  |
| • Diagnostic alarm   | Yes  |
| <b>Diagnostic messages</b>   |  |
| • Monitoring the supply voltage  | Yes  |
| • Wire-break   | Yes; Only for output type "current"                |
| • Short-circuit  | Yes; Only for output type "voltage"                |
| • Overflow/underflow   | Yes  |
| <b>Diagnostics indication LED</b>  |  |
| • RUN LED  | Yes; green LED                                     |
| • ERROR LED  | Yes; red LED                                       |

- |  |                |
|--|----------------|
| • Monitoring of the supply voltage (PWR-LED) | Yes; green LED |
| • Channel status display                     | Yes; green LED |
| • for channel diagnostics                    | Yes; red LED   |
| • for module diagnostics                     | Yes; red LED   |

### Potential separation

#### Potential separation channels

- |  |     |
|--|-----|
| • between the channels                     | No  |
| • between the channels, in groups of       | 8   |
| • between the channels and backplane bus   | Yes |
| • Between the channels and load voltage L+ | Yes |

### Permissible potential difference

|                           |        |
|---------------------------|--------|
| between S- and MANA (UCM) | 8 V DC |
|---------------------------|--------|

### Isolation

|                       |                      |
|-----------------------|----------------------|
| Isolation tested with | 707 V DC (type test) |
|-----------------------|----------------------|

### Ambient conditions

#### Altitude during operation relating to sea level

- |   |  |
|---|--|
| • Installation altitude above sea level, max. | 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual |
|---|--|

### Dimensions

|        |        |
|--------|--------|
| Width  | 35 mm  |
| Height | 147 mm |
| Depth  | 129 mm |

### Weights

|                 |       |
|-----------------|-------|
| Weight, approx. | 325 g |
|-----------------|-------|

|                       |            |
|-----------------------|------------|
| <b>last modified:</b> | 06/22/2020 |
|-----------------------|------------|