

SIMATIC S7-1500, CM PTP RS422/485 BA Communication module for Serial connection RS422,RS485 Freeport, 3964 (R), USS, 19200 Kbit/s, 15-Pin D-sub socket



Figure similar

General information	
Product type designation	CM PtP RS 422 / 485 BA
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M 0
<ul style="list-style-type: none"> Fast startup 	Yes
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version 	V12 / V12
<ul style="list-style-type: none"> STEP 7 configurable/integrated from version 	V5.5 SP2 with GSD file
<ul style="list-style-type: none"> PROFIBUS from GSD version/GSD revision 	- / -
<ul style="list-style-type: none"> PROFINET from GSD version/GSD revision 	V2.3
Installation type/mounting	
Rail mounting	Yes; S7-1500 mounting rail
Supply voltage	
Type of supply voltage	system power supply
Input current	

Current consumption (rated value)	43 mA; From the backplane bus
Power	
Power available from the backplane bus	0.65 W
Power loss	
Power loss, typ.	0.6 W
Address area	
Address space per module	
• Inputs	8 byte
Interface types	
RS 485	
• Transmission rate, max.	19.2 kbit/s
• Cable length, max.	1 200 m
RS 422	
• Transmission rate, max.	19.2 kbit/s
• Cable length, max.	1 200 m
• 4-wire full duplex connection	Yes
• 4-wire multipoint connection	No
Protocols	
Integrated protocols	
Freeport	
— Telegram length, max.	1 kbyte
— Bits per character	7 or 8
— Number of stop bits	1 or 2 bit
— Parity	None, even, odd, always 1, always 0, any
3964 (R)	
— Telegram length, max.	1 kbyte
— Bits per character	7 or 8
— Number of stop bits	1 or 2 bit
— Parity	None, even, odd, always 1, always 0, any
Telegram buffer	
• Buffer memory for telegrams	2 kbyte
• Number of telegrams which can be buffered	255
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes
• Hardware interrupt	No
Diagnostic messages	
• Wire-break	Yes
Diagnostics indication LED	

- | | |
|----------------|-----------------|
| • RUN LED | Yes; green LED |
| • ERROR LED | Yes; red LED |
| • Receive RxD | Yes; Yellow LED |
| • Transmit TxD | Yes; Yellow LED |

Potential separation

between backplane bus and interface	Yes
-------------------------------------	-----

Isolation

Isolation tested with	707 V DC (type test)
-----------------------	----------------------

Ambient conditions

Ambient temperature during operation

- | | |
|---------------------------------|-------|
| • horizontal installation, min. | 0 °C |
| • horizontal installation, max. | 60 °C |
| • vertical installation, min. | 0 °C |
| • vertical installation, max. | 40 °C |

Decentralized operation

to SIMATIC S7-300	Yes
to SIMATIC S7-400	Yes
to SIMATIC S7-1500	Yes
to standard PROFINET controller	Yes

Dimensions

Width	35 mm
Height	147 mm
Depth	127 mm

Weights

Weight, approx.	0.22 kg
-----------------	---------

last modified: 06/22/2020