

SIDOOR MDG3 L geared motor, shaft on the left with slot and fitted key A3x5 according to DIN 6888, max. 180 kg of mass to be moved, IP56, 2x M12 for separate motor connection cable, 30 V DC, -20 to +50 °C



### General information

Product type designation	MDG3 L
--------------------------	--------

### Supply voltage

Rated value (DC)	30 V
------------------	------

### Input current

Operational current (rated value)	4 A
-----------------------------------	-----

### Power

Active power input	120 W
--------------------	-------

### Mechanical data

Torque of the rotary operating mechanism (rated value)	3 N·m
--	-------

Speed, max.	0.65 m/s
-------------	----------

Mass to be moved, max.	180 kg
------------------------	--------

Gear unit	Yes
-----------	-----

Gear ratio	15
------------	----

Number of pulses per revolution, max.	100
---------------------------------------	-----

Fixed output gear	No
-------------------	----

Degree and class of protection	
IP degree of protection	
• of the motor	IP56
• of the gear unit	IP56

Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
EAC (formerly Gost-R)	Yes
China RoHS compliance	Yes

Ambient conditions	
Ambient temperature during operation	
• min.	-20 °C
• max.	50 °C
Ambient temperature during storage/transportation	
• Storage, min.	-40 °C
• Storage, max.	85 °C

Cables	
Fixed connecting cable	No

Dimensions	
Diameter of output gear, min.	28 mm
Diameter of output gear, max.	122 mm
Height of motor	98 mm
Length of motor	264 mm
Diameter of motor	63 mm
Width of gearbox	85 mm
<b>last modified:</b>	06/22/2020