

SIDOOR MED280 Direct operating mechanism, max. 280 kg door weight, Cable length 1.5 m, 24VDC, -25-+70 °C



### General information

Product type designation	MED280
--------------------------	--------

### Supply voltage

Rated value (DC)	24 V
------------------	------

### Input current

Operational current (rated value)	9.7 A
-----------------------------------	-------

### Power

Active power input	233 W
--------------------	-------

### Mechanical data

Torque of the rotary operating mechanism (rated value)	4.7 N·m
--	---------

Speed, max.	0.8 m/s
-------------	---------

Number of pulses per revolution, max.	1 024
---------------------------------------	-------

Weight of door, max.	280 kg
----------------------	--------

### Degree and class of protection

IP degree of protection	IP54
• of the motor	

Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
EAC (formerly Gost-R)	Yes
TÜV Inspectorate approval	Yes
China RoHS compliance	Yes

Ambient conditions	
Ambient temperature during operation	
• min.	-25 °C
• max.	70 °C
Ambient temperature during storage/transportation	
• Storage, min.	-40 °C
• Storage, max.	85 °C

Dimensions	
Width of motor	160 mm
Height of motor	140 mm
Length of motor	56 mm
• including drive pinion	91 mm
<b>last modified:</b>	06/22/2020