

Product description

Protective barrel for lens with exchangeable front panel made of glass
 MV500 protective lens barrel glass Degree of protection IP67 for MV500 devices Front pane: glass Enclosure: metal For lens length without/with built-in ring light 48.5 mm/23.9 mm For lens width without/with built-in ring light 60.4 mm/41.6 mm Suitable for lenses (MLFB): 6GF9001-1BL01,...-1BF01, ...- 1BG01,...- 1BH01,...- 1BJ01 6GF3540-8EA03-0LL0; Suitable lamps (MLFB): 6GF3540-8DA33, ...8DA41, ...8D42; WxHxD (external, mm) 65x65x65 Scope of delivery: Protective barrel with mounted O-ring and pane;



Suitability for use	For lenses up to 57 mm in length
Mechanical data	
Material	Aluminum/glass
Color	black
Ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> during operation 	0 ... 50 °C
<ul style="list-style-type: none"> during storage 	-30 ... +70 °C
<ul style="list-style-type: none"> during transport 	-30 ... +70 °C
Design, dimensions and weights	
Height	66 mm
Diameter	65 mm
Further information / Internet-Links	
Internet-Link	
<ul style="list-style-type: none"> to website: TIA Selection Tool 	http://www.siemens.com/tia-selection-tool

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

last modified:

<https://support.industry.siemens.com/WW/view/en/67384964>

<http://www.siemens.com/codereader>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

05/08/2020