

Product type designation

Code Reader MV550 H

SIMATIC MV550 H optical reader Resolut.:1280x1024Px; PN and GigE; 2-fold Ethernet: 100 MB(POE),GigE !no switch=>data separation!; Function: 1D/2D code reading; Image field and distance: Variable (dep. on lens); PoE; IP67 with 6GF3540-8AC11; Delivery: Reader and SD card adapter (w/o card);



Suitability for operation

1D codes: Int. 2/5, Code 128, Code 93, Code 39, Code 32, EAN 13, EAN 8, UPC-A, UPC-E, GS1, Pharmacode, Postnet, 2D codes: DMC, dot code, PDF417 (without: Truncated, Micro and Macro), Q R (without: Micro and Macro), verification uncalibrated

Interfaces

Type of electrical connection

- of Industrial Ethernet interface
- of the RS 422 interface
- of the RS 232 interface
- for supply voltage
- at the digital inputs/outputs

M12, d-coded, PoE

M12, 12-pin, male

M12, 12-pin, male

M12, 12-pin, male

M12, 12-pin, male

Number of digital inputs

1

Number of digital outputs

3

Digital input version

1 fast trigger input

Digital output version

1 fast strobe output, 2 potential-free outputs (NPN- PNP-capable)

Optical data

Design of image sensor / of the camera

CMOS-Chip, 1280 x 1024

Type of image capture

Global shutter with manual or automatic exposure time

| | |
|---------------------------------------|--|
| Range | 70 ... 3000 mm |
| Range / Note | Using C-mount lenses and lens accessories, the range can be exactly matched to the application |
| Type of light source | Integrated lighting or external lighting according to accessories list |
| Image acquisition frequency / maximum | 33 Hz |
| Code reading rate / maximum | 80 1/s |
| Type of focusing | Manual adjustment on the lens |

Supply voltage, current consumption, power loss

| | |
|--|-------------------------|
| Supply voltage | |
| <ul style="list-style-type: none"> • at DC / Rated value • at DC | 24 V 19.2 ... 28.8 V |
| Consumed current / at DC / at 24 V | |
| <ul style="list-style-type: none"> • typical • maximum | 0.2 A 2 A |
| Buffering time / in the event of power failure / minimum | 0.01 s |

Mechanical data

| | |
|----------|-------------------|
| Material | Die-cast aluminum |
| Color | petrol blue |

Ambient conditions

| | |
|--|---|
| Ambient temperature | |
| <ul style="list-style-type: none"> • during operation • during storage • during transport | 0 ... 50 °C -30 ... +70 °C -30 ... +70 °C |
| Relative humidity / at 25 °C / without condensation / during operation / maximum | 95 % |
| Protection class IP | IP67 |
| Shock resistance | According to IEC 60068-2 |
| Shock acceleration | 300 m/s ² |
| Vibrational acceleration | 40 m/s ² |

Design, dimensions and weights

| | |
|---------------|---------------|
| Width | 68 mm |
| Height | 122 mm |
| Depth | 45 mm |
| Net weight | 0.55 kg |
| Mounting type | 4 x M4 screws |

Product features, product functions, product components / general

| | |
|---|----|
| Protocol / is supported / Media Redundancy Protocol (MRP) | No |
| Product function / of the PROFINET IO device / is supported / H-Sync forwarding | No |
| Protocol / is supported | |

- LLDP
- PROFINET IO protocol
- TCP/IP
- SNMP v1
- SNMP v2
- SNMP v3
- DCP
- EtherNet/IP protocol
- OPC UA

Yes
Yes
Yes
Yes
No
No
Yes
No
No

Product feature / silicon-free

Yes

Standards, specifications, approvals

MTBF

66 y

Further information / Internet-Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<https://support.industry.siemens.com/cs/ww/en/view/67384964>
<http://www.siemens.com/codereader>
<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

last modified:

05/08/2020