

PS2 membrane keyboard DE, with touch pad, desktop keyboard for devices with corresponding interface Further information, Quantity and content: see technical data



Figure similar

General information	
Product type designation	PS/2 membrane keyboard DEU
Control elements	
Keyboard fonts	
<ul style="list-style-type: none"> • Design • Keyboard assignment • Key illumination • Function keys <ul style="list-style-type: none"> — Number of function keys — Programmable • Number pad • Status LED displays <ul style="list-style-type: none"> — for number pad — for Shift keys 	Membrane keyboard B3F, 101/102 or 104/105 OMRON No 12 Yes Yes Yes; Num, Caps and Scroll Yes Yes
Connection type	
<ul style="list-style-type: none"> • USB 	Yes; With PS/2 USB adapter (not included in the scope of supply)

<ul style="list-style-type: none"> • PS/2 	Yes
<ul style="list-style-type: none"> • Cable length 	1.75 m
Frame size/design	
<ul style="list-style-type: none"> • Standard 	Yes; For industrial applications
Installation type/mounting	
Rack mounting	No; Desktop housing
Input current	
Current consumption (rated value)	25 mA; Typical
Battery	
Battery-operated	No; maintenance-free
EMC	
Emission of radio interference acc. to EN 55 011	
<ul style="list-style-type: none"> • Limit class A, for use in industrial areas 	Yes
Degree and class of protection	
IP65 (all-round)	Yes
Splashproof	Yes
Standards, approvals, certificates	
CE mark	Yes
RoHS conformity	Yes
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> • min. 	0 °C
<ul style="list-style-type: none"> • max. 	40 °C
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> • min. 	-10 °C
<ul style="list-style-type: none"> • max. 	50 °C
Relative humidity	
<ul style="list-style-type: none"> • Operation, max. 	90 %; no condensation
<ul style="list-style-type: none"> • Condensation permissible 	No
Operating systems	
Runs under operating system	
<ul style="list-style-type: none"> • Windows CE 	Yes
<ul style="list-style-type: none"> • Windows Vista 	Yes
<ul style="list-style-type: none"> • Windows XP 	Yes
<ul style="list-style-type: none"> • Windows 7 	Yes
<ul style="list-style-type: none"> • Windows 10 	Yes
Mechanics/material	
Material	
<ul style="list-style-type: none"> • Plastic 	Yes; AUTOTEX (R) V150

• Sheet steel	No
Enclosure material (front)	
• Plastic	Yes; AUTOTEX (R) V150
Service life	
• Number of operating cycles, keys	1 000 000; Operations (minimum)
Dimensions	
Width	478.5 mm
Height	28 mm
Depth	180 mm
Weights	
Weight without packaging	2 260 g
Weight incl. packaging	2 410 g
Scope of supply	
Delivery quantity in pieces	1; Membrane keyboard with mouse pad
Other	
Merchandise	Yes; TIPRO no. K-547
Manufacturer name	TIPRO Representative Office
Manufacturer's address	Vogelweg 20, 31785 Hameln, Germany
Target devices	Suitable for IPC and HMI devices with the corresponding interfaces (see manual)
Note:	Suitable PS/2 USB adapter (keyboard/mouse): 1x USB 1.1, plug A on 2x PS/2 sockets, 0.20 m, black; manufacturer: Renkforce; supply by Conrad Elektronik, order no.: 1360251 - 62
Usable in the following products	
• Product 1	6AV2124-0GC13-0AX0
• Product 2	6AV2124-0QC13-0AX0
last modified:	06/22/2020