SIEMENS

Data sheet 6GF6710-3AE

PS2 keyboard 19" DE, with touch pad, removable keyboard for devices with corresponding interface Further information, Quantity and content: see technical data



Figure similar

General information	
Product type designation	PS/2 built-in keyboard DEU
Control elements	
Keyboard fonts	
• Design	Membrane keyboard
 Keyboard assignment 	B3F, 101/102 or 104/105 OMRON
 Key illumination 	No
Function keys	
 Number of function keys 	12
— Programmable	Yes
Number pad	Yes
 Status LED displays 	Yes; Num, Caps and Scroll
— for number pad	Yes
— for Shift keys	Yes
Connection type	
• USB	Yes; With PS/2 USB adapter (not included in the scope of supply)

• PS/2	Yes
Frame size/design	
Standard	Yes; For industrial applications
Installation type/mounting	
Rack mounting	No; Built-in keyboard, 19" rack
1	
Input current Current consumption (rated value)	25 mA; Typical
Current consumption (rated value)	20 ma, Typicai
Battery	
Battery-operated	No; maintenance-free
EMC	
Emission of radio interference acc. to EN 55 011	
Limit class A, for use in industrial areas	Yes
Dograp and class of protection	
Degree and class of protection IP (at the front)	IP65
IP (rear)	IP20
Splashproof	Yes
	,
Standards, approvals, certificates	
CE mark	Yes
RoHS conformity	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	40 °C
Ambient temperature during storage/transportation	
• min.	-10 °C
• max.	50 °C
Relative humidity	
Operation, max.	90 %; no condensation
 Condensation permissible 	No
Operating systems	
Runs under operating system	
Windows CE	Yes
Windows Vista	Yes
Windows XP	Yes
• Windows 7	Yes
• Windows 10	Yes
Mechanics/material Material	
Sheet steel	Yes
5 611001 51001	

Enclosure material (front)	
Plastic	Yes; AUTOTEX (R) V150
Service life	()
Number of operating cycles, keys	1 000 000; Operations (minimum)
Dimensions	
Width	482.6 mm
Height	42.5 mm
Depth	177.8 mm
Weights	
Weight without packaging	1 480 g
Weight incl. packaging	1 665 g
Scope of supply	
Delivery quantity in pieces	1; Built-in keyboard rack mounting
Other	
Merchandise	Yes; TIPRO no. K-647 (K-847)
Manufacturer name	TIPRO Representative Office
Manufacturer's address	Vogelweg 20, 31785 Hameln, Germany
Target devices	Suitable for IPC and HMI devices with the corresponding interfaces (see manual)
Note:	Suitable PS/2 USB adapter (keyboard/mouse): 1x USB 1.1, plug A on 2x PS/2 sockets, 0.20 m, black; manufacturer: Renkforce; supply by Conrad Elektronik, order no.: 1360251 - 62
Usable in the following products	
• Product 1	6AV2124-0GC13-0AX0
• Product 2	6AV2124-0QC13-0AX0
last modified:	06/22/2020