

Product type designation

CP 5711

Communications processor CP 5711 USB adapter (USB V2.0) for connection of a PG or Notebook to PROFIBUS or MPI; contain 2 m USB cable



Transfer rate

Transfer rate

- at the 1st interface / acc. to PROFIBUS

9.6 kbit/s ... 12 Mbit/s

Interfaces

Number of electrical connections

- at the 1st interface / acc. to PROFIBUS
- for power supply

1

1

Number of interfaces / acc. to USB

1

Type of electrical connection

- at the 1st interface / acc. to PROFIBUS
- for power supply
- of the USB interface

9-pin Sub-D socket (RS 485)

2-pole terminal block

Standard-B socket with mechanical interlock

Standard for interfaces / USB 2.0

Yes

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Type of voltage supply / optional external supply

Yes

Supply voltage

<ul style="list-style-type: none"> • from USB • external • external • Note 	5 V 24 V 18 ... 30 V Supplied directly from USB provided that supply from PC is adequate; alternative external supply is possible
Relative symmetrical tolerance / at DC	
<ul style="list-style-type: none"> • at 5 V • at 24 V 	5 % 5 %
Consumed current	
<ul style="list-style-type: none"> • from USB • from external supply voltage / at DC / at 24 V / maximum 	0.5 A 0.3 A
Power loss [W]	2.5 W

Ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> • during operation • during storage • during transport 	0 ... 60 °C -40 ... +60 °C -40 ... +60 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	85 %
Protection class IP	IP20

Design, dimensions and weights	
Module format	USB V2.0 adapter
Width	85 mm
Height	137 mm
Depth	35 mm
Net weight	300 g
Mounting type	Mounting on DIN rail with optional mounting rail support
Mounting type / 35 mm DIN rail mounting	Yes

Product features, product functions, product components / general	
Number of plug-in cards of same design / plug-in / per PC station	1
Number of units / Note	-

Performance data

Performance data / open communication	
Software / for open communication / by means of SEND/RECEIVE / required	Yes, SOFTNET-PB DP / SOFTNET-PB DP Slave / SOFTNET-PB S7
Number of possible connections / for open communication / by means of SEND/RECEIVE / maximum	50

Performance data / PROFIBUS DP

Software / for DP master function / required	Yes, SOFTNET-PB DP
Service / as DP master	
• DPV0	Yes
• DPV1	No
• DPV2	No
Number of DP slaves / on DP master / usable	64
Amount of data	
• of the address area of the inputs / as DP master / total	15616 byte
• of the address area of the outputs / as DP master / total	15616 byte
• of the address area of the inputs / per DP slave	244 byte
• of the address area of the outputs / per DP slave	244 byte
• of the address area of the diagnostic data / per DP slave	244 byte
Software / for DP slave function / required	Yes, SOFTNET-PB DP slave
Service / as DP slave	
• DPV0	Yes
• DPV1	No
Amount of data	
• of the address area of the inputs / as DP slave / total	122 byte
• of the address area of the outputs / as DP slave / total	122 byte
Performance data / S7 communication	
Software / for S7 communication / required	Yes, SOFTNET-PB S7
Number of possible connections / for S7/PG communication / maximum	8
Performance data / multi-protocol mode	
Number of configurable connections / per PC station	207
Product functions / management, configuration, engineering	
Configuration software / required	Included in the scope of delivery of the required software product
Product functions / Diagnostics	
Product function	
• Port diagnostics	Yes
Standards, specifications, approvals	
Standard	
• for EMC	2004/108/EC
• for safety / from CSA and UL	CAN/CSA C22.2 & UL 60950-1
• for emitted interference	EN 61000-6-3, EN 61000-6-4

<ul style="list-style-type: none"> • for interference immunity 	EN 61000-6-1, EN 61000-6-2
Certificate of suitability	
<ul style="list-style-type: none"> • CE marking 	Yes
<ul style="list-style-type: none"> • C-Tick 	Yes

accessories	
accessories	optional: MPI cable, mounting rail support

Further information / Internet-Links	
Internet-Link	
<ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL 	http://www.siemens.com/snst
<ul style="list-style-type: none"> • to website: Industrial communication 	http://www.siemens.com/simatic-net
<ul style="list-style-type: none"> • to website: Industry Mall 	http://www.siemens.com/industrial-controls/mall
<ul style="list-style-type: none"> • to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
<ul style="list-style-type: none"> • to website: Image database 	http://automation.siemens.com/bilddb
<ul style="list-style-type: none"> • to website: CAx Download Manager 	http://www.siemens.com/cax
<ul style="list-style-type: none"> • to website: Industry Online Support 	https://support.industry.siemens.com

Security information	
Security information	<p>Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)</p>

last modified: 05/08/2020