

Product type designation

Product description

PB BFOC Plug PCF

BFOC screw-connector for PCF-fibre optic cable with plastic Cladding
BFOC plug PCF for on-site mounting to PCF FOC cables Pack: 20 units +cleaning cloths



Figure similar

Suitability for use	For connection of PCF fiber-optic cables
Transfer rate	
Transfer rate / with PROFIBUS	9.6 kbit/s ... 12 Mbit/s
Interfaces	
Number of optical interfaces / for fiber optic cable	1
Design of the optical interface / for network components or terminal equipment	BFOC connector
Type of electrical connection / FastConnect	No
Mechanical data	
Material / of the enclosure	Metal and plastic
Locking mechanism design	Bayonet
Design, dimensions and weights	
Type of cable outlet	180° cable outlet
Width	10 mm
Height	10 mm

Depth	10 mm
Net weight	8 g

Ambient conditions

Protection class IP	IP20
---------------------	------

Product features, product functions, product components / general

Product feature	
• silicon-free	Yes
Product component	
• strain relief	Yes

Standards, specifications, approvals

Certificate of suitability	
• RoHS conformity	Yes
• UL approval	No
• Railway application in accordance with EN 50155	No

Further information / Internet-Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

last modified: 03/23/2020