

SCALANCE X108PoE unmanaged IE switch, 2x 10/100 Mbit/s RJ45 Power-over-Ethernet ports and 6x 10/100 Mbit/s RJ45 ports, LED diagnostics, error signaling contact with set button, Redundant power supply Manual available as a download



Product type designation	SCALANCE X108PoE
Transfer rate	
Transfer rate	10 Mbit/s, 100 Mbit/s
Interfaces / for communication / Integrated	
Number of electrical connections	
<ul style="list-style-type: none"> • for network components or terminal equipment • for Power-over-Ethernet / for network components or terminal equipment 	6; RJ45 with securing collar 2
Number of 100 Mbit/s SC ports	
<ul style="list-style-type: none"> • for multimode 	0
Interfaces / other	
Number of electrical connections	
<ul style="list-style-type: none"> • for signaling contact • for power supply • for redundant voltage supply 	1 1 1
Type of electrical connection	
<ul style="list-style-type: none"> • for signaling contact • for power supply 	2-pole terminal block 4-pole terminal block

Signal inputs/outputs	
Operating voltage / of the signaling contacts	
<ul style="list-style-type: none"> • at DC / Rated value 	24 V
Operating current / of the signaling contacts	
<ul style="list-style-type: none"> • at DC / maximum 	0.1 A
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage	
<ul style="list-style-type: none"> • external 	24 V
<ul style="list-style-type: none"> • external / minimum 	18 V
<ul style="list-style-type: none"> • external / maximum 	32 V
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	4 A / 125 V
Consumed current / maximum	1.7 A
Power loss [W]	
<ul style="list-style-type: none"> • at DC / at 24 V 	10 W
Supplied active power / of PSE / with PoE	
<ul style="list-style-type: none"> • per port / maximum 	15.4 W
<ul style="list-style-type: none"> • total / maximum 	30.8 W
Ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> • during operation 	-20 ... +60 °C
<ul style="list-style-type: none"> • during storage 	-40 ... +80 °C
<ul style="list-style-type: none"> • during transport 	-40 ... +80 °C
<ul style="list-style-type: none"> • Note 	At 55 °C ambient temperature on both sides 40 mm distance to adjacent devices
Relative humidity	
<ul style="list-style-type: none"> • at 25 °C / without condensation / during operation / maximum 	95 %
Protection class IP	IP30
Design, dimensions and weights	
Design	compact
Width	60 mm
Height	125 mm
Depth	124 mm
Net weight	0.9 kg
Product feature / conformal coating	No
Mounting type	
<ul style="list-style-type: none"> • 35 mm DIN rail mounting 	Yes
<ul style="list-style-type: none"> • wall mounting 	Yes
<ul style="list-style-type: none"> • S7-300 rail mounting 	Yes

- S7-1500 rail mounting

No

Product functions / management, configuration, engineering

Product function	
<ul style="list-style-type: none"> • multiport mirroring 	No
<ul style="list-style-type: none"> • CoS 	Yes
Product function / switch-managed	No

Product functions / redundancy

Product function	
<ul style="list-style-type: none"> • Parallel Redundancy Protocol (PRP)/operation in the PRP-network 	Yes
<ul style="list-style-type: none"> • Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA) 	No

Standards, specifications, approvals

Standard	
<ul style="list-style-type: none"> • for FM 	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4
<ul style="list-style-type: none"> • for hazardous zone 	EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X
<ul style="list-style-type: none"> • for safety / from CSA and UL 	UL 60950-1, CSA C22.2 No. 60950-1
<ul style="list-style-type: none"> • for hazardous zone / from CSA and UL 	UL 1604 and UL 2279-15 (Hazardous Location), Class 1 / Division 2 / Group A, B, C, D / T.., Class 1 / Zone 2 / Group IIC / T..
<ul style="list-style-type: none"> • for emitted interference 	EN 61000-6-4:2001
<ul style="list-style-type: none"> • for interference immunity 	EN 61000-6-2:2001
MTBF	61.64 y

Standards, specifications, approvals / CE

Certificate of suitability / CE marking	Yes
---	-----

Standards, specifications, approvals / other

Certificate of suitability	EN 61000-6-2:2001, EN 61000-6-4:2001
<ul style="list-style-type: none"> • C-Tick 	Yes
<ul style="list-style-type: none"> • E1 approval 	No
<ul style="list-style-type: none"> • E1 approval 	No
<ul style="list-style-type: none"> • Railway application in accordance with EN 50155 	Yes
<ul style="list-style-type: none"> • KC approval 	Yes

Standards, specifications, approvals / marine classification

Marine classification association	
<ul style="list-style-type: none"> • American Bureau of Shipping Europe Ltd. (ABS) 	Yes
<ul style="list-style-type: none"> • Bureau Veritas (BV) 	Yes
<ul style="list-style-type: none"> • Det Norske Veritas (DNV) 	No
<ul style="list-style-type: none"> • Germanische Lloyd (GL) 	No

- | | |
|--|-----|
| • DNV GL | Yes |
| • Lloyds Register of Shipping (LRS) | Yes |
| • Nippon Kaiji Kyokai (NK) | Yes |
| • Polski Rejestr Statkow (PRS) | Yes |
| • Royal Institution of Naval Architects (RINA) | Yes |

Standards, specifications, approvals / Product conformity

- | | |
|--|-----|
| Product conformity | |
| • acc. to IEEE 802.3af-Power-over-Ethernet | Yes |

Further information / Internet-Links

- | | |
|---|---|
| Internet-Link | |
| • to website: Selector SIMATIC NET SELECTION TOOL | http://www.siemens.com/snst |
| • to website: Industrial communication | http://www.siemens.com/simatic-net |
| • to website: Industry Mall | https://mall.industry.siemens.com |
| • to website: Information and Download Center | http://www.siemens.com/industry/infocenter |
| • to website: Image database | http://automation.siemens.com/bilddb |
| • to website: CAx Download Manager | http://www.siemens.com/cax |
| • to website: Industry Online Support | https://support.industry.siemens.com |

Security information

Security information	<p>Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)</p>
----------------------	---

last modified: 05/13/2020