



SCALANCE XP208EEC, managed IE switch with railway approval (EN 50155, EN 45545); 8x 10/100 Mbps M12 ports, IP65, LED diagnostics, error signaling contact, Redundant power supply, PROFINET IO device, network management, operable in redundant ring, Dust caps, incl. electronic Manual on CD-ROM, C-plug optional

Product type designation	SCALANCE XP208EEC
Transfer rate	
Transfer rate	10 Mbit/s, 100 Mbit/s
Interfaces / for communication / Integrated	
Number of electrical connections	
• for network components or terminal equipment	8
Number of 10/100 Mbit/s M12-ports (D-coded) / Integrated	8
Interfaces / other	
Number of electrical connections	
• for operator console	1
• for signaling contact	1
• for power supply	1
• for redundant voltage supply	1
Type of electrical connection	
• for operator console	5 pin M12 socket (A coded)
• for signaling contact	5-pin M12 connector (B-coded)
• for power supply	4-pin M12 plug (A-coded)

design of the removable storage	
<ul style="list-style-type: none"> • C-PLUG 	Yes
Signal inputs/outputs	
Operating voltage / of the signaling contacts	
<ul style="list-style-type: none"> • at DC / Rated value 	24 V
Operating current / of the signaling contacts	
<ul style="list-style-type: none"> • at DC / maximum 	0.1 A
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage	
<ul style="list-style-type: none"> • external 	24 V
<ul style="list-style-type: none"> • external / minimum 	19.2 V
<ul style="list-style-type: none"> • external / maximum 	28.8 V
Supply voltage / 1 / Rated value	XP-200EEC with EN 50155 supports the voltage range 16.8 ... 30 V DC
<ul style="list-style-type: none"> • Consumed current / 1 / at rated supply voltage / maximum 	0.2 A
<ul style="list-style-type: none"> • Power loss [W] / 1 / Rated value 	4.8 W
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	5 A / 60 V
Consumed current / maximum	0.21 A
Power loss [W]	
<ul style="list-style-type: none"> • at DC / at 24 V 	5 W
Ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> • during operation 	-40 ... +70 °C
<ul style="list-style-type: none"> • during storage 	-40 ... +70 °C
<ul style="list-style-type: none"> • during transport 	-40 ... +70 °C
<ul style="list-style-type: none"> • Note 	EEC variants with EN 50155 support for 10 minutes: -40 °C ... +85 °C
Relative humidity	
<ul style="list-style-type: none"> • at 25 °C / without condensation / during operation / maximum 	95 %
Protection class IP	IP65
Design, dimensions and weights	
Design	compact
Width	200 mm
Height	200 mm
Depth	49 mm
Net weight	1.8 kg
Product feature / conformal coating	Yes
Material / of the enclosure	Aluminum

Mounting type	ET200pro module carrier
<ul style="list-style-type: none"> • wall mounting 	Yes

Product features, product functions, product components / general

Cascading in the case of a redundant ring / at reconfiguration time of ≤ 0.3 s	50
Cascading in cases of star topology	any (depending only on signal propagation time)

Product functions / management, configuration, engineering

Product function	
<ul style="list-style-type: none"> • CLI • web-based management • MIB support • TRAPs via email • Configuration with STEP 7 • RMON • Port mirroring • multiport mirroring • CoS • with IRT / PROFINET IO switch • PROFINET IO diagnosis 	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>No</p> <p>Yes</p>
PROFINET conformity class	B
Product function / switch-managed	Yes
Telegram length / for Ethernet / maximum	1518 byte
Protocol / is supported	
<ul style="list-style-type: none"> • Telnet • HTTP • HTTPS • TFTP • FTP • BOOTP • DCP • LLDP • EtherNet/IP • SNMP v1 • SNMP v2 • SNMP v3 • IGMP (snooping/querier) 	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>No</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p>
Identification & maintenance function	
<ul style="list-style-type: none"> • I&M0 - device-specific information • I&M1 – higher-level designation/location designation 	<p>Yes</p> <p>Yes</p>

Product functions / Diagnostics

Product function	
• Port diagnostics	Yes
• Statistics Packet Size	Yes
• Statistics packet type	Yes
• Error statistics	Yes
• SysLog	Yes
• loopback diagnostics	Yes

Product functions / VLAN

Product function	
• VLAN - port based	Yes
• VLAN - protocol-based	No
• VLAN - IP-based	No
• VLAN dynamic	No
Number of VLANs / maximum	4094

Product functions / DHCP

Product function	
• DHCP server	Yes
• DHCP client	Yes
• DHCP Option 82	Yes
• DHCP Option 66	Yes
• DHCP Option 67	Yes

Product functions / redundancy

Product function	
• of the PROFINET IO device / is supported / PROFINET system redundancy (S2)	Yes
• Ring redundancy	Yes
• High Speed Redundancy Protocol (HRP)	Yes
• high speed redundancy protocol (HRP) with redundancy manager	Yes
• high speed redundancy protocol (HRP) with standby redundancy	Yes
Protocol / is supported / Media Redundancy Protocol (MRP)	Yes
Product function	
• media redundancy protocol (MRP) with redundancy manager	Yes
• of the PROFINET IO device / is supported / H-Sync forwarding	Yes
• redundancy procedure RSTP	Yes
• redundancy procedure MSTP	Yes
• Passive listening	Yes

Product functions / Security

Product function	
<ul style="list-style-type: none"> • RADIUS client 	Yes
Protocol / is supported	
<ul style="list-style-type: none"> • SSH 	Yes
<ul style="list-style-type: none"> • SSL 	Yes

Product functions / time

Product function	
<ul style="list-style-type: none"> • SICLOCK support 	Yes
<ul style="list-style-type: none"> • NTP-client 	Yes
<ul style="list-style-type: none"> • SNTP client 	Yes
Protocol / is supported	
<ul style="list-style-type: none"> • NTP 	Yes
<ul style="list-style-type: none"> • SNTP 	Yes

System modification during operation

Product function / configuration in RUN via CiR/H-CiR	Yes
---	-----

Standards, specifications, approvals

Standard	
<ul style="list-style-type: none"> • for FM 	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4
<ul style="list-style-type: none"> • for hazardous zone 	EN 60079-0 : 2006, EN 60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
<ul style="list-style-type: none"> • for safety / from CSA and UL 	UL 60950-1, CSA C22.2 No. 60950-1
<ul style="list-style-type: none"> • for hazardous zone / from CSA and UL 	ANSI / ISA 12.12.01, CSA C22.2 No. 213-M1987, CL. 1 / Div. 2 / GP. A, B, C, D T4, CL. 1 / Zone 2 / GP. IIC, T4
<ul style="list-style-type: none"> • for emitted interference 	EN 61000-6-4 (Class A)
<ul style="list-style-type: none"> • for interference immunity 	EN 61000-6-2
Security for industrial automation and control systems / acc. to IEC 62443-4-2:2019	Yes

Standards, specifications, approvals / CE

Certificate of suitability / CE marking	Yes
Certificate of suitability / RoHS conformity	Yes

Standards, specifications, approvals / other

Certificate of suitability	
<ul style="list-style-type: none"> • C-Tick 	Yes
<ul style="list-style-type: none"> • E1 approval 	Yes
<ul style="list-style-type: none"> • E1 approval 	Yes
<ul style="list-style-type: none"> • Railway application in accordance with EN 50155 	Yes

- Railway application in accordance with EN 50124-1
- Fire protection in accordance with EN 45545-2
- KC approval

Yes
Yes
Yes

Standards, specifications, approvals / marine classification

Marine classification association

- American Bureau of Shipping Europe Ltd. (ABS)
- Bureau Veritas (BV)
- DNV GL
- Korean Register of Shipping (KRS)
- Polski Rejestr Statkow (PRS)

Yes
Yes
Yes
Yes
Yes

accessories

Product extension / optional / C-PLUG

Yes

Further information / Internet-Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>
<http://www.siemens.com/simatic-net>
<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

05/13/2020