



SCALANCE XP208PoE EEC, managed IE switch, 8x 10/100 Mbps M12 ports, IP65, LED diagnostics, error signaling contact, Redundant power supply, PROFINET IO device, network management, operable in redundant ring, Dust caps, incl. electronic Manual on CD-ROM, C-plug optional

| | |
|--|-------------------------------|
| Product type designation | SCALANCE XP208PoE EEC |
| Transfer rate | |
| Transfer rate | 10 Mbit/s, 100 Mbit/s |
| Interfaces / for communication / Integrated | |
| Number of electrical connections | |
| • for network components or terminal equipment | 8 |
| Number of 10/100 Mbit/s M12-ports (D-coded) / Integrated | 4 |
| • with PoE | 4 |
| Interfaces / other | |
| Number of electrical connections | |
| • for operator console | 1 |
| • for signaling contact | 1 |
| • for power supply | 1 |
| • for redundant voltage supply | 1 |
| Type of electrical connection | |
| • for operator console | 5 pin M12 socket (A coded) |
| • for signaling contact | 5-pin M12 connector (B-coded) |

| | |
|--|--------------------------|
| <ul style="list-style-type: none"> • for power supply | 4-pin M12 plug (A-coded) |
| design of the removable storage | |
| <ul style="list-style-type: none"> • C-PLUG | Yes |

Signal inputs/outputs

| | |
|---|-------|
| Operating voltage / of the signaling contacts | |
| <ul style="list-style-type: none"> • at DC / Rated value | 54 V |
| Operating current / of the signaling contacts | |
| <ul style="list-style-type: none"> • at DC / maximum | 0.1 A |

Supply voltage, current consumption, power loss

| | |
|--|---------------------------|
| Type of voltage / of the supply voltage | DC |
| Supply voltage | |
| <ul style="list-style-type: none"> • external | 54 V |
| <ul style="list-style-type: none"> • external / minimum | 46 V |
| <ul style="list-style-type: none"> • external / maximum | 57 V |
| Supply voltage / 1 / Rated value | |
| <ul style="list-style-type: none"> • Consumed current / 1 / at rated supply voltage / maximum | 2.5 A |
| <ul style="list-style-type: none"> • Power loss [W] / 1 / Rated value | 9 W |
| Supply voltage / 2 / Rated value | with PoE consumers Type 1 |
| Product component / fusing at power supply input | Yes |
| Fuse protection type / at input for supply voltage | 5 A / 60 V |
| Consumed current / maximum | 2.4 A |
| Power loss [W] | |
| <ul style="list-style-type: none"> • maximum | 9 W |
| Supplied active power / of PSE / with PoE | |
| <ul style="list-style-type: none"> • per port / maximum | 30 W |
| <ul style="list-style-type: none"> • total / maximum | 120 W |

Ambient conditions

| | |
|--|--|
| Ambient temperature | |
| <ul style="list-style-type: none"> • during operation | -40 ... +70 °C |
| <ul style="list-style-type: none"> • during storage | -40 ... +70 °C |
| <ul style="list-style-type: none"> • during transport | -40 ... +70 °C |
| <ul style="list-style-type: none"> • Note | EEC variants with EN 50155 support for 10 minutes: -40 °C ... +85 °C |
| Relative humidity | |
| <ul style="list-style-type: none"> • at 25 °C / without condensation / during operation / maximum | 95 % |
| Protection class IP | IP65 |

Design, dimensions and weights

| | |
|--------|---------|
| Design | compact |
| Width | 200 mm |

| | |
|---|-------------------------|
| Height | 200 mm |
| Depth | 49 mm |
| Net weight | 1.8 kg |
| Product feature / conformal coating | Yes |
| Material / of the enclosure | Aluminum |
| Mounting type | ET200pro module carrier |
| <ul style="list-style-type: none"> • wall mounting | Yes |

Product features, product functions, product components / general

| | |
|---|---|
| Cascading in the case of a redundant ring / at reconfiguration time of $\sim 0.3\text{ s}$ | 50 |
| Cascading in cases of star topology | any (depending only on signal propagation time) |

Product functions / management, configuration, engineering

| | |
|--|---|
| Product function | |
| <ul style="list-style-type: none"> • CLI • web-based management • MIB support • TRAPs via email • Configuration with STEP 7 • RMON • Port mirroring • multiport mirroring • CoS • with IRT / PROFINET IO switch • PROFINET IO diagnosis | <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>No</p> <p>Yes</p> |
| PROFINET conformity class | B |
| Product function / switch-managed | Yes |
| Telegram length / for Ethernet / maximum | 1518 byte |
| Protocol / is supported | |
| <ul style="list-style-type: none"> • Telnet • HTTP • HTTPS • TFTP • FTP • BOOTP • DCP • LLDP • EtherNet/IP • SNMP v1 • SNMP v2 • SNMP v3 • IGMP (snooping/querier) | <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>No</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> |

| | |
|--|-----|
| Identification & maintenance function | |
| • I&M0 - device-specific information | Yes |
| • I&M1 – higher-level designation/location designation | Yes |

Product functions / Diagnostics

| | |
|--------------------------|-----|
| Product function | |
| • Port diagnostics | Yes |
| • Statistics Packet Size | Yes |
| • Statistics packet type | Yes |
| • Error statistics | Yes |
| • SysLog | Yes |
| • loopback diagnostics | Yes |

Product functions / VLAN

| | |
|---------------------------|------|
| Product function | |
| • VLAN - port based | Yes |
| • VLAN - protocol-based | No |
| • VLAN - IP-based | No |
| • VLAN dynamic | No |
| Number of VLANs / maximum | 4094 |

Product functions / DHCP

| | |
|------------------|-----|
| Product function | |
| • DHCP server | Yes |
| • DHCP client | Yes |
| • DHCP Option 82 | Yes |
| • DHCP Option 66 | Yes |
| • DHCP Option 67 | Yes |

Product functions / redundancy

| | |
|--|-----|
| Product function | |
| • of the PROFINET IO device / is supported / PROFINET system redundancy (S2) | Yes |
| • Ring redundancy | Yes |
| • High Speed Redundancy Protocol (HRP) | Yes |
| • high speed redundancy protocol (HRP) with redundancy manager | Yes |
| • high speed redundancy protocol (HRP) with standby redundancy | Yes |
| Protocol / is supported / Media Redundancy Protocol (MRP) | Yes |
| Product function | |
| • media redundancy protocol (MRP) with redundancy manager | Yes |

- of the PROFINET IO device / is supported / H-Sync forwarding
- redundancy procedure RSTP
- redundancy procedure MSTP
- Passive listening

Yes
Yes
Yes
Yes

Product functions / Security

| | |
|--|------------|
| Product function | |
| <ul style="list-style-type: none"> • RADIUS client | Yes |
| Protocol / is supported | |
| <ul style="list-style-type: none"> • SSH • SSL | Yes Yes |

Product functions / time

| | |
|--|-------------------|
| Product function | |
| <ul style="list-style-type: none"> • SICLOCK support • NTP-client • SNTP client | Yes Yes Yes |
| Protocol / is supported | |
| <ul style="list-style-type: none"> • NTP • SNTP | Yes Yes |

System modification during operation

| | |
|---|-----|
| Product function / configuration in RUN via CiR/H-CiR | Yes |
|---|-----|

Standards, specifications, approvals

| | |
|---|---|
| Standard | |
| <ul style="list-style-type: none"> • for FM • for hazardous zone • for safety / from CSA and UL • for hazardous zone / from CSA and UL • for emitted interference • for interference immunity | <p>FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4</p> <p>EN 60079-0 : 2006, EN 60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X</p> <p>UL 60950-1, CSA C22.2 No. 60950-1</p> <p>ANSI / ISA 12.12.01, CSA C22.2 No. 213-M1987, CL. 1 / Div. 2 / GP. A, B, C, D T4, CL. 1 / Zone 2 / GP. IIC, T4</p> <p>EN 61000-6-4 (Class A)</p> <p>EN 61000-6-2</p> |
| Security for industrial automation and control systems / acc. to IEC 62443-4-2:2019 | Yes |

Standards, specifications, approvals / CE

| | |
|--|-----|
| Certificate of suitability / CE marking | Yes |
| Certificate of suitability / RoHS conformity | Yes |

Standards, specifications, approvals / other

| | |
|--|-----|
| Certificate of suitability | |
| <ul style="list-style-type: none"> • C-Tick | Yes |

- E1 approval
- E1 approval
- Railway application in accordance with EN 50155
- Railway application in accordance with EN 50124-1
- Fire protection in accordance with EN 45545-2
- KC approval

Yes
Yes
Yes
Yes
Yes
Yes

accessories

Product extension / optional / C-PLUG

Yes

Further information / Internet-Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

05/13/2020