

SCALANCE XP216, managed IE switch, 12x 10/100 Mbps M12 ports, 4x 10/100/1000 Mbps M12 ports IP65, LED diagnostics, error signaling contact, Redundant power supply, PROFINET IO device, network management, operable in redundant ring, incl. dust caps, incl. electronic Manual on CD-ROM, C-plug optional



<b>Product type designation</b>	<b>SCALANCE XP216</b>
<b>Transfer rate</b>	
Transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s
<b>Interfaces / for communication / Integrated</b>	
Number of electrical connections • for network components or terminal equipment	16
Number of 10/100 Mbit/s M12-ports (D-coded) / Integrated	12
Number of 10/100/1000 Mbit/s M12-ports (X-coded) / Integrated	4
<b>Interfaces / other</b>	
Number of electrical connections • for operator console • for signaling contact • for power supply • for redundant voltage supply	1 1 1 1
Type of electrical connection • for operator console	5 pin M12 socket (A coded)

<ul style="list-style-type: none"> <li>• for signaling contact</li> </ul>	5-pin M12 connector (B-coded)
<ul style="list-style-type: none"> <li>• for power supply</li> </ul>	4-pin M12 plug (A-coded)
design of the removable storage	
<ul style="list-style-type: none"> <li>• C-PLUG</li> </ul>	Yes

#### Signal inputs/outputs

Operating voltage / of the signaling contacts	
<ul style="list-style-type: none"> <li>• at DC / Rated value</li> </ul>	24 V
Operating current / of the signaling contacts	
<ul style="list-style-type: none"> <li>• at DC / maximum</li> </ul>	0.1 A

#### Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage	
<ul style="list-style-type: none"> <li>• external</li> </ul>	24 V
<ul style="list-style-type: none"> <li>• external / minimum</li> </ul>	19.2 V
<ul style="list-style-type: none"> <li>• external / maximum</li> </ul>	28.8 V
<b>Supply voltage / 1 / Rated value</b>	
<ul style="list-style-type: none"> <li>• Consumed current / 1 / at rated supply voltage / maximum</li> </ul>	0.4 A
<ul style="list-style-type: none"> <li>• Power loss [W] / 1 / Rated value</li> </ul>	9.6 W
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	5 A / 60 V
Consumed current / maximum	0.335 A
Power loss [W]	
<ul style="list-style-type: none"> <li>• at DC / at 24 V</li> </ul>	8 W

#### Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> </ul>	-40 ... +70 °C
<ul style="list-style-type: none"> <li>• during storage</li> </ul>	-40 ... +70 °C
<ul style="list-style-type: none"> <li>• during transport</li> </ul>	-40 ... +70 °C
Relative humidity	
<ul style="list-style-type: none"> <li>• at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
Protection class IP	IP65

#### Design, dimensions and weights

Design	compact
Width	280 mm
Height	200 mm
Depth	49 mm
Net weight	2.5 kg
Material / of the enclosure	Aluminum
Mounting type	ET200pro module carrier

- wall mounting

Yes

### Product features, product functions, product components / general

Cascading in the case of a redundant ring / at reconfiguration time of <math>\sim 0.3\text{ s}</math>

50

Cascading in cases of star topology

any (depending only on signal propagation time)

### Product functions / management, configuration, engineering

Product function

- CLI
- web-based management
- MIB support
- TRAPs via email
- Configuration with STEP 7
- RMON
- Port mirroring
- multiport mirroring
- CoS
- with IRT / PROFINET IO switch
- PROFINET IO diagnosis

Yes  
Yes  
Yes  
Yes  
Yes  
Yes  
Yes  
Yes  
Yes  
No  
Yes

PROFINET conformity class

B

Product function / switch-managed

Yes

Telegram length / for Ethernet / maximum

1518 byte

Protocol / is supported

- Telnet
- HTTP
- HTTPS
- TFTP
- FTP
- BOOTP
- DCP
- LLDP
- EtherNet/IP
- SNMP v1
- SNMP v2
- SNMP v3
- IGMP (snooping/querier)

Yes  
Yes  
Yes  
Yes  
Yes  
No  
Yes  
Yes  
Yes  
Yes  
Yes  
Yes  
Yes

Identification & maintenance function

- I&M0 - device-specific information
- I&M1 – higher-level designation/location designation

Yes  
Yes

### Product functions / Diagnostics

Product function

• Port diagnostics	Yes
• Statistics Packet Size	Yes
• Statistics packet type	Yes
• Error statistics	Yes
• SysLog	Yes
• loopback diagnostics	Yes

#### Product functions / VLAN

Product function	
• VLAN - port based	Yes
• VLAN - protocol-based	No
• VLAN - IP-based	No
• VLAN dynamic	No
Number of VLANs / maximum	4094

#### Product functions / DHCP

Product function	
• DHCP server	Yes
• DHCP client	Yes
• DHCP Option 82	Yes
• DHCP Option 66	Yes
• DHCP Option 67	Yes

#### Product functions / redundancy

Product function	
• of the PROFINET IO device / is supported / PROFINET system redundancy (S2)	Yes
• Ring redundancy	Yes
• High Speed Redundancy Protocol (HRP)	Yes
• high speed redundancy protocol (HRP) with redundancy manager	Yes
• high speed redundancy protocol (HRP) with standby redundancy	Yes
Protocol / is supported / Media Redundancy Protocol (MRP)	Yes
Product function	
• media redundancy protocol (MRP) with redundancy manager	Yes
• of the PROFINET IO device / is supported / H-Sync forwarding	Yes
• redundancy procedure RSTP	Yes
• redundancy procedure MSTP	Yes
• Passive listening	Yes

#### Product functions / Security

Product function	
<ul style="list-style-type: none"> <li>• RADIUS client</li> </ul>	Yes
Protocol / is supported	
<ul style="list-style-type: none"> <li>• SSH</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SSL</li> </ul>	Yes

### Product functions / time

Product function	
<ul style="list-style-type: none"> <li>• SICLOCK support</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• NTP-client</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNTP client</li> </ul>	Yes
Protocol / is supported	
<ul style="list-style-type: none"> <li>• NTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNTP</li> </ul>	Yes

### System modification during operation

Product function / configuration in RUN via CiR/H-CiR	Yes
---	-----

### Standards, specifications, approvals

Standard	
<ul style="list-style-type: none"> <li>• for FM</li> </ul>	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4
<ul style="list-style-type: none"> <li>• for hazardous zone</li> </ul>	EN 60079-0 : 2006, EN 60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
<ul style="list-style-type: none"> <li>• for safety / from CSA and UL</li> </ul>	UL 60950-1, CSA C22.2 No. 60950-1
<ul style="list-style-type: none"> <li>• for hazardous zone / from CSA and UL</li> </ul>	ANSI / ISA 12.12.01, CSA C22.2 No. 213-M1987, CL. 1 / Div. 2 / GP. A, B, C, D T4, CL. 1 / Zone 2 / GP. IIC, T4
<ul style="list-style-type: none"> <li>• for emitted interference</li> </ul>	EN 61000-6-4 (Class A)
<ul style="list-style-type: none"> <li>• for interference immunity</li> </ul>	EN 61000-6-2
Security for industrial automation and control systems / acc. to IEC 62443-4-2:2019	Yes

### Standards, specifications, approvals / CE

Certificate of suitability / CE marking	Yes
Certificate of suitability / RoHS conformity	Yes

### Standards, specifications, approvals / other

Certificate of suitability	
<ul style="list-style-type: none"> <li>• C-Tick</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Railway application in accordance with EN 50155</li> </ul>	No
<ul style="list-style-type: none"> <li>• Railway application in accordance with EN 50124-1</li> </ul>	No
<ul style="list-style-type: none"> <li>• KC approval</li> </ul>	Yes

### Standards, specifications, approvals / marine classification

Marine classification association	
<ul style="list-style-type: none"> <li>American Bureau of Shipping Europe Ltd. (ABS)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Bureau Veritas (BV)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>DNV GL</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Korean Register of Shipping (KRS)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Polski Rejestr Statkow (PRS)</li> </ul>	Yes

<b>accessories</b>	
Product extension / optional / C-PLUG	Yes

<b>Further information / Internet-Links</b>	
---	--

Internet-Link	
<ul style="list-style-type: none"> <li>to website: Selector SIMATIC NET SELECTION TOOL</li> </ul>	<a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a>
<ul style="list-style-type: none"> <li>to website: Industrial communication</li> </ul>	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
<ul style="list-style-type: none"> <li>to website: Industry Mall</li> </ul>	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
<ul style="list-style-type: none"> <li>to website: Information and Download Center</li> </ul>	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
<ul style="list-style-type: none"> <li>to website: Image database</li> </ul>	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
<ul style="list-style-type: none"> <li>to website: CAx Download Manager</li> </ul>	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
<ul style="list-style-type: none"> <li>to website: Industry Online Support</li> </ul>	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

<b>Security information</b>	
-----------------------------	--

Security information	<p>Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <a href="http://www.siemens.com/industrialsecurity">http://www.siemens.com/industrialsecurity</a>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <a href="http://support.automation.siemens.com">http://support.automation.siemens.com</a>. (V3.4)</p>
----------------------	--

**last modified:** 05/13/2020