

SCALANCE XR524-8C; managed IE switch; Layer 3 with key plug available; power supply 2x 230 V AC; 24x 10/100/1000 Mbit/s RJ45; 8x 100/1000 Mbit/s SFP; contains 8 combo ports; in total 24 ports can be used; error signaling contact; select/set button; PROFINET IO device; redundancy functions; office features (RSTP, VLAN, IGMP, ...); C-plug in scope of delivery



<b>Product type designation</b>	<b>SCALANCE XR524-8C</b>
<b>Transfer rate</b>	
Transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s
<b>Interfaces / for communication / Integrated</b>	
Number of electrical connections • for network components or terminal equipment	24; RJ45
Number of 100 Mbit/s ST(BFOC) ports • for multimode	0
Number of electrical connections • for SFP	8
Number of combo ports / with RJ45 interface for optical plug-in transceiver	8
<b>Interfaces / for communication / plug-in</b>	
Number of electrical connections • for SFP	8
<b>Interfaces / other</b>	
Number of electrical connections • for operator console	1

<ul style="list-style-type: none"> <li>• for management purposes</li> </ul>	1
<ul style="list-style-type: none"> <li>• for signaling contact</li> </ul>	1
<ul style="list-style-type: none"> <li>• for power supply</li> </ul>	1
<ul style="list-style-type: none"> <li>• for redundant voltage supply</li> </ul>	1
Type of electrical connection	
<ul style="list-style-type: none"> <li>• for operator console</li> </ul>	RJ11
<ul style="list-style-type: none"> <li>• for management purposes</li> </ul>	RJ45
<ul style="list-style-type: none"> <li>• for signaling contact</li> </ul>	2-pole terminal block
<ul style="list-style-type: none"> <li>• for power supply</li> </ul>	4-pole terminal block
design of the removable storage	
<ul style="list-style-type: none"> <li>• C-PLUG/KEY-PLUG</li> </ul>	Yes
Product feature / hot-swappable interface modules	Yes

### Signal inputs/outputs

Operating voltage / of the signaling contacts	
<ul style="list-style-type: none"> <li>• at DC / Rated value</li> </ul>	24 V
Operating current / of the signaling contacts	
<ul style="list-style-type: none"> <li>• at DC / maximum</li> </ul>	0.1 A

### Supply voltage, current consumption, power loss

Type of voltage supply / redundant power supply unit	Yes
Type of voltage / of the supply voltage	AC
Supply voltage	
<ul style="list-style-type: none"> <li>• at AC</li> </ul>	230 V
<ul style="list-style-type: none"> <li>• at AC / rated value</li> </ul>	90 ... 264 V
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	3.15 A / 250 V
Consumed current / maximum	0.6 A

### Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> </ul>	-25 ... +60 °C
<ul style="list-style-type: none"> <li>• during storage</li> </ul>	-40 ... +85 °C
<ul style="list-style-type: none"> <li>• during transport</li> </ul>	-40 ... +85 °C
Relative humidity	
<ul style="list-style-type: none"> <li>• at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
Protection class IP	IP20

### Design, dimensions and weights

Design	19" rack
Number of modular height units / relating to 19-inch cabinet	1
Width	449 mm
Height	44 mm

Depth	305 mm
Net weight	4.5 kg
Mounting type	
• 19-inch installation	Yes
• 35 mm DIN rail mounting	No
• wall mounting	No
• S7-300 rail mounting	No
• S7-1500 rail mounting	No
Type of cable outlet	Cable outlet at front

### Product features, product functions, product components / general

Cascading in cases of star topology	any (depending only on signal propagation time)
-------------------------------------	---

### Product functions / management, configuration, engineering

Product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
• Configuration with STEP 7	Yes
• RMON	Yes
• Port mirroring	Yes
• multiport mirroring	Yes
• CoS	Yes
• PROFINET IO diagnosis	Yes
PROFINET conformity class	B
Product function / switch-managed	Yes
Telegram length / for Ethernet / maximum	9216 byte
Protocol / is supported	
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• FTP	Yes
• BOOTP	Yes
• GMRP	Yes
• DCP	Yes
• LLDP	Yes
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
• IGMP (snooping/querier)	Yes
Identification & maintenance function	

- I&M0 - device-specific information Yes
- I&M1 – higher-level designation/location designation Yes

### Product functions / Diagnostics

- |                          |     |
|--------------------------|-----|
| Product function         |     |
| • Port diagnostics       | Yes |
| • Statistics Packet Size | Yes |
| • Statistics packet type | Yes |
| • Error statistics       | Yes |
| • SysLog                 | Yes |

### Product functions / VLAN

- |                                     |     |
|-------------------------------------|-----|
| Product function                    |     |
| • VLAN - port based                 | Yes |
| • VLAN - protocol-based             | Yes |
| • VLAN - IP-based                   | Yes |
| • VLAN dynamic                      | Yes |
| Number of VLANs / maximum           | 255 |
| Number of VLANs - dynamic / maximum | 255 |
| Protocol / is supported / GVRP      | Yes |

### Product functions / DHCP

- |                  |     |
|------------------|-----|
| Product function |     |
| • DHCP client    | Yes |
| • DHCP Option 82 | Yes |
| • DHCP Option 66 | Yes |
| • DHCP Option 67 | Yes |

### Product functions / Routing

- |                           |  |
|---------------------------|--|
| Service / Routing / Note  | IP routing in combination with KEY-PLUG XR-500 |
| Product function          |  |
| • Static IP routing       | Yes  |
| • Static IP routing IPv6  | Yes  |
| • dynamic IP routing      | Yes  |
| • dynamic IP routing IPv6 | Yes  |
| Protocol / is supported   |  |
| • RIPv2                   | Yes  |
| • RIPnG for IPv6          | Yes  |
| • OSPFv2                  | Yes  |
| • OSPFv3 for IPv6         | Yes  |
| • VRRP                    | Yes  |
| • VRRP for IPv6           | Yes  |

### Product functions / redundancy

Product function	
• Ring redundancy	Yes
• High Speed Redundancy Protocol (HRP)	Yes
• high speed redundancy protocol (HRP) with redundancy manager	Yes
• high speed redundancy protocol (HRP) with standby redundancy	Yes
Protocol / is supported / Media Redundancy Protocol (MRP)	Yes
Product function	
• media redundancy protocol (MRP) with redundancy manager	Yes
• redundancy procedure STP	Yes
• redundancy procedure RSTP	Yes
• redundancy procedure MSTP	Yes
• Passive listening	Yes
Protocol / is supported	
• LACP	Yes

### Product functions / Security

Product function	
• ACL - MAC-based	Yes
• ACL - port/MAC-based	Yes
• IEEE 802.1x (radius)	Yes
• Broadcast/Multicast/Unicast Limiter	Yes
• broadcast blocking	Yes
Protocol / is supported	
• SSH	Yes

### Product functions / time

Product function	
• SICLOCK support	Yes
Protocol / is supported	
• NTP	Yes
• SNTP	Yes

### Standards, specifications, approvals

Standard	
• for safety / from CSA and UL	available soon
• for emitted interference	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2

### Standards, specifications, approvals / CE

Certificate of suitability / CE marking	Yes
---	-----

### Standards, specifications, approvals / other

Certificate of suitability	EN 61000-6-2, EN 61000-6-4
• C-Tick	Yes
• E1 approval	No
• E1 approval	No
• KC approval	Yes

### Standards, specifications, approvals / marine classification

Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	Yes
• Bureau Veritas (BV)	Yes
• DNV GL	Yes
• Korean Register of Shipping (KRS)	Yes
• Lloyds Register of Shipping (LRS)	Yes
• Nippon Kaiji Kyokai (NK)	Yes
• Polski Rejestr Statkow (PRS)	Yes
• Royal Institution of Naval Architects (RINA)	Yes

### Further information / Internet-Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	<a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a>
• to website: Industrial communication	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
• to website: Industry Mall	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
• to website: Information and Download Center	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
• to website: Image database	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
• to website: CAx Download Manager	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

### Security information

Security information	<p>Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <a href="http://www.siemens.com/industrialsecurity">http://www.siemens.com/industrialsecurity</a>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <a href="http://support.automation.siemens.com">http://support.automation.siemens.com</a>. (V3.4)</p>
----------------------	--

last modified:

05/13/2020