

IWLAN client, SCALANCE W748-1 M12, 1 radio, 3 N-CON antenna port, iFeatures support via key plug, IEEE 802.11a/b/g/h/n, 2.4/5GHz, gross 450 Mbit/s per radio, 1x M12 max. 1 Gbit/s, PoE, redundant 24 V DC, M12 A-coded IP65, -20..+60 °C, plug slot, WPA2/802.11i/e, Signaling contact observe national approvals! CERT ID: RAPN-W1-M12-E3, includes: MPCIE-R1-ABGN-U3, scope of delivery: Manuals on CD-ROM, English/German; M12 sealing caps, for operation in the USA



Transfer rate

| | |
|--|------------------------------------|
| Transfer rate | |
| <ul style="list-style-type: none"> with WLAN / maximum for Industrial Ethernet | 450 Mbit/s 10, 100, 1000 Mbit/s |
| Transfer rate / for Industrial Ethernet | |
| <ul style="list-style-type: none"> minimum maximum | 10 Mbit/s 1000 Mbit/s |

Interfaces

| | |
|--|---|
| Number of electrical connections | |
| <ul style="list-style-type: none"> for network components or terminal equipment for power supply for redundant voltage supply | 1 1 1 |
| Type of electrical connection | |
| <ul style="list-style-type: none"> for network components or terminal equipment for power supply | M12 interface (8-pole, X-coded), PoE M12 interface (4-pole, A-coded) |
| design of the removable storage | |
| <ul style="list-style-type: none"> C-PLUG KEY-PLUG | Yes Yes |

| Interfaces / wireless | |
|--|--------------------|
| Number of radio cards / permanently installed | 1 |
| Transmission mode / for multiple input multiple output (MIMO) | 3x3 |
| Number of spatial streams | 3 |
| Number of electrical connections / for external antenna(s) | 3 |
| Type of electrical connection / for external antenna(s) | N-Connect (socket) |
| Product feature / external antenna can be mounted directly on device | Yes |

| Supply voltage, current consumption, power loss | |
|--|----------------------------|
| Type of voltage / of the supply voltage | DC |
| Supply voltage / 1 <ul style="list-style-type: none"> from M12 Power Connector (A-coded) for redundant power supply | 19.2 V |
| Supply voltage / 2 <ul style="list-style-type: none"> from M12 Power Connector (A-coded) for redundant power supply | 28.8 V |
| Supply voltage <ul style="list-style-type: none"> from Power-over-Ethernet acc. to IEEE802.3at for type 1 and IEEE802.3af from Power-over-Ethernet acc. to IEEE802.3at for type 2 | 48 V 50 V |
| Consumed current <ul style="list-style-type: none"> at DC / at 24 V / typical with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical with Power-over-Ethernet according to IEEE802.3at for type 2 / typical | 0.45 A 0.22 A 0.21 A |
| Power loss [W] <ul style="list-style-type: none"> at DC / at 24 V / typical with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical with Power-over-Ethernet according to IEEE802.3at for type 2 / typical | 10.7 W 10.7 W 10.7 W |

| Ambient conditions | |
|--|--|
| Ambient temperature <ul style="list-style-type: none"> during operation during storage during transport | -20 ... +60 °C -40 ... +85 °C -40 ... +85 °C |
| Relative humidity / at 25 °C / without condensation / during operation / maximum | 100 % |

| | |
|-----------------------------------|---|
| Ambient condition / for operation | When used under hazardous conditions (Zone 2), the SCALANCE W788-x or W748-x product must be installed in an enclosure. To comply with EN 50021, this enclosure must meet the requirements of at least IP 54 in compliance with EN 60529. |
| Protection class IP | IP65 |

Design, dimensions and weights

| | |
|---|--|
| Width / of the enclosure / without antenna | 200 mm |
| Height / of the enclosure / without antenna | 176 mm |
| Depth / of the enclosure / without antenna | 79 mm |
| Net weight | 1.7 kg |
| Mounting type | For 35 mm DIN rail mounting an additional mounting adapter is required |
| <ul style="list-style-type: none"> • S7-300 rail mounting • S7-1500 rail mounting • 35 mm DIN rail mounting • wall mounting | Yes Yes Yes Yes |

Radio frequencies

| | |
|--|--|
| Operating frequency | |
| <ul style="list-style-type: none"> • for WLAN in 2.4 GHz frequency band • for WLAN in 5 GHz frequency band | 2.41 ... 2.48 GHz; depending on the country approvals 4.9 ... 5.8 GHz; depending on the country approvals |

Product features, product functions, product components / general

| | |
|---|---|
| Product function / Access Point Mode | No |
| Product function / Client Mode | Yes |
| Product function | |
| <ul style="list-style-type: none"> • iPCF client • iPCF-MC client | Yes; Only in combination with the 'KEY-PLUG W780 iFeatures' or 'KEY-PLUG W740 iFeatures' No; Only in combination with 'KEY-PLUG W780 iFeatures' or 'KEY-PLUG W740 iFeatures' |
| Number of iPCF-capable radio modules | 1 |
| Product function / iPRP | Yes; In combination with the 'KEY-PLUG W780 iFeatures' or 'KEY-PLUG W740 iFeatures' only |

Product functions / management, configuration, engineering

| | |
|--|--|
| Number of manageable IP addresses / in client | 8 |
| Product function | |
| <ul style="list-style-type: none"> • CLI • web-based management • MIB support • TRAPs via email • Configuration with STEP 7 • configuration with STEP 7 in the TIA Portal • WDS | Yes Yes Yes Yes Yes Yes No |
| Protocol / is supported | |

| | |
|--|-----|
| • Address Resolution Protocol (ARP) | Yes |
| • ICMP | Yes |
| • Telnet | Yes |
| • HTTP | Yes |
| • HTTPS | Yes |
| • TFTP | Yes |
| • DCP | Yes |
| • LLDP | Yes |
| Identification & maintenance function | |
| • I&M0 - device-specific information | Yes |
| • I&M1 – higher-level designation/location designation | Yes |

Product functions / Diagnostics

| | |
|----------------------------------|-----|
| Product function | |
| • PROFINET IO diagnosis | Yes |
| • Link Check | No |
| • connection monitoring IP-Alive | No |
| • SysLog | Yes |
| Protocol / is supported | |
| • SNMP v1 | Yes |
| • SNMP v2 | Yes |
| • SNMP v3 | Yes |

Product functions / VLAN

| | |
|----------------------------|----|
| Product function | |
| • function VLAN with IWLAN | No |

Product functions / DHCP

| | |
|-------------------------|-----|
| Product function | |
| • DHCP client | Yes |
| • DHCP server | Yes |
| • DHCP Option 82 | Yes |

Product functions / redundancy

| | |
|--------------------------------|-----|
| Protocol / is supported | |
| • STP/RSTP | Yes |
| • MSTP | Yes |
| • RSTP | Yes |

Product functions / Security

| | |
|-------------------------------------|-----|
| Product function | |
| • ACL - MAC-based | Yes |
| • Management security, ACL-IP based | Yes |
| • IEEE 802.1x (radius) | Yes |

| | |
|--|---|
| <ul style="list-style-type: none"> • NAT/NAPT | Yes |
| <ul style="list-style-type: none"> • access protection according to IEEE802.11i | Yes |
| <ul style="list-style-type: none"> • WPA/WPA2 | Yes |
| <ul style="list-style-type: none"> • TKIP/AES | Yes |
| Protocol / is supported | |
| <ul style="list-style-type: none"> • SSH | Yes |
| <ul style="list-style-type: none"> • RADIUS | Yes |
| Product functions / time | |
| Protocol / is supported | |
| <ul style="list-style-type: none"> • NTP | Yes |
| <ul style="list-style-type: none"> • SNTP | Yes |
| <ul style="list-style-type: none"> • SIMATIC time synchronization (SIMATIC Time) | Yes |
| Standards, specifications, approvals | |
| Standard | |
| <ul style="list-style-type: none"> • for FM | FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4 |
| <ul style="list-style-type: none"> • for hazardous zone | EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X |
| <ul style="list-style-type: none"> • for safety / from CSA and UL | UL 60950-1, CSA C22.2 No. 60950-1 |
| Certificate of suitability | |
| <ul style="list-style-type: none"> • EC declaration of conformity | Yes |
| <ul style="list-style-type: none"> • CE marking | Yes |
| <ul style="list-style-type: none"> • C-Tick | Yes |
| <ul style="list-style-type: none"> • E1 approval | Yes |
| <ul style="list-style-type: none"> • Railway application in accordance with EN 50155 | No |
| <ul style="list-style-type: none"> • Railway application in accordance with EN 50121-4 | No |
| <ul style="list-style-type: none"> • NEMA TS2 | No |
| <ul style="list-style-type: none"> • IEC 61375 | No |
| <ul style="list-style-type: none"> • IEC 61850-3 | No |
| <ul style="list-style-type: none"> • NEMA4X | No |
| <ul style="list-style-type: none"> • Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af | Yes |
| <ul style="list-style-type: none"> • Power-over-Ethernet according to IEEE802.3at for type 2 | Yes |
| Standard for wireless communication | |
| <ul style="list-style-type: none"> • IEEE 802.11a | Yes |
| <ul style="list-style-type: none"> • IEEE 802.11b | Yes |
| <ul style="list-style-type: none"> • IEEE 802.11e | Yes |
| <ul style="list-style-type: none"> • IEEE 802.11g | Yes |
| <ul style="list-style-type: none"> • IEEE 802.11h | Yes |

| | |
|---|---|
| <ul style="list-style-type: none"> • IEEE 802.11i • IEEE 802.11n | <p>Yes</p> <p>Yes</p> |
| Wireless approval | For operation in the USA, you will find more information under: www.siemens.de/funkzulassungen |
| <p>Marine classification association</p> <ul style="list-style-type: none"> • American Bureau of Shipping Europe Ltd. (ABS) • Bureau Veritas (BV) • DNV GL • Korean Register of Shipping (KRS) • Lloyds Register of Shipping (LRS) • Nippon Kaiji Kyokai (NK) • Polski Rejestr Statkow (PRS) • Royal Institution of Naval Architects (RINA) | <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> |

Further information / Internet-Links

| | |
|---|--|
| <p>Internet-Link</p> <ul style="list-style-type: none"> • to website: TIA Selection Tool • to the website: IWLAN • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx Download Manager • to website: Industry Online Support | <p>http://www.siemens.com/tia-selection-tool</p> <p>http://www.siemens.com/iwlan</p> <p>https://mall.industry.siemens.com</p> <p>http://www.siemens.com/industry/infocenter</p> <p>http://automation.siemens.com/bilddb</p> <p>http://www.siemens.com/cax</p> <p>https://support.industry.siemens.com</p> |
|---|--|

Security information

| | |
|----------------------|--|
| Security information | <p>Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)</p> |
|----------------------|--|

last modified: 05/28/2020