SIEMENS

Data sheet

6GK5774-1FX00-0AC0



IWLAN Access Point, SCALANCE W774-1 RJ45, 1 radio, 2 R-SMA antenna port, iFeatures support via key plug, IEEE 802.11a/b/g/h/n, 2.4/5GHz, gross data rate 300 Mbit/s, 2x RJ45 max. 100 Mbit/s, PoE integrated 2-port switch, redundant 24 V DC, terminal block, IP30, -20... 60 °C, plug slot WPA2/802.11i/e, observe national approvals! CERT ID: MSN-W1-RJ-E2, scope of delivery: Manuals on CD-ROM, German/English, 1x terminal block; for operation in Israel

Transfer rate	
Transfer rate	
with WLAN / maximum	300 Mbit/s
• for Industrial Ethernet	10, 100 Mbit/s
Transfer rate / for Industrial Ethernet	
• minimum	10 Mbit/s
• maximum	100 Mbit/s

2
1
1
RJ45 socket
4-pole screw terminal, PoE
Yes
Yes

Interfaces / wireless	
Number of radio cards / permanently installed	1
Transmission mode / for multiple input multiple output (MIMO)	2x2
Number of spatial streams	2
Number of electrical connections / for external antenna(s)	2
Type of electrical connection / for external antenna(s)	R-SMA (socket)
Product feature / external antenna can be mounted directly on device	Yes
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage / 1	
• from terminal block	19.2 V
Supply voltage / 2	
• from terminal block	28.8 V
Supply voltage	
 from Power-over-Ethernet acc. to IEEE802.3at for type 1 and IEEE802.3af 	48 V
Consumed current	
• at DC / at 24 V / typical	0.25 A
 with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical 	0.125 A
Power loss [W]	
• at DC / at 24 V / typical	6 W
 with Power-over-Ethernet according to 	6 W
IEEE802.3at for type 1 and IEEE802.3af / typical	
Ambient conditions	
Ambient temperature	20 100 00
during operation	-20 +60 °C
during storage	-40 +85 °C
during transport	-40 +85 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	97 %
Ambient condition / for operation	When used under hazardous conditions (Zone 2), the SCALANCE W774-1 RJ45 or W734-1 RJ45 product must be installed in an enclosure. To comply with EN 50021, this enclosure must meet the requirements of at least IP 54 in compliance with EN 60529.
Protection class IP	IP30
Design, dimensions and weights	
Width	26 mm
Height	156 mm
Depth	127 mm

Width / of the enclosure / without antenna	26 mm
Height / of the enclosure / without antenna	147 mm
Depth / of the enclosure / without antenna	127 mm
Net weight	0.52 kg
Mounting type	wall mounting only if flat mounted
• S7-300 rail mounting	Yes
• S7-1500 rail mounting	Yes
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes

Radio frequencies

Operating frequency

- for WLAN in 2.4 GHz frequency band 2.41 ... 2.48 GHz; depending on the country approvals
- for WLAN in 5 GHz frequency band 4.9 ... 5.8 GHz; depending on the country approvals

Product features, product functions, product components / general	
Product function / Access Point Mode	Yes
Product function / Client Mode	Yes
Number of SSIDs	4
Product function	
• iPCF Access Point	Yes; Only in combination with the 'KEY-PLUG W780 iFeatures'
• iPCF client	Yes; Only in combination with the 'KEY-PLUG W740 iFeatures'
• iPCF-MC Access Point	No
• iPCF-MC client	Yes; Only in combination with the 'KEY-PLUG W740 iFeatures'
Number of iPCF-capable radio modules	1
Product function / iREF	Yes; Only in combination with the 'KEY-PLUG W780 iFeatures' or 'KEY-PLUG W740 iFeatures'
Number of iREF-capable radio modules	1
Product function / iPRP	Yes; In combination with the 'KEY-PLUG W780 iFeatures' only

Product functions / management, configuration, engineering	
Number of manageable IP addresses / in client	8
Product function	
• CLI	Yes
 web-based management 	Yes
 MIB support 	Yes
• TRAPs via email	Yes
Configuration with STEP 7	Yes
configuration with STEP 7 in the TIA Portal	Yes
 operation with IWLAN controller 	No
 operation with Enterasys WLAN controller 	No
 forced roaming on IP down with IWLAN 	Yes
 forced roaming on link down with IWLAN 	Yes
• WDS	Yes

Protocol / is supported	
 Address Resolution Protocol (ARP) 	Yes
• ICMP	Yes
Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• DCP	Yes
• LLDP	Yes
Identification & maintenance function	
I&M0 - device-specific information	Yes
 I&M1 – higher-level designation/location 	Yes
designation	
Product functions / Diagnostics	
Product function	
 PROFINET IO diagnosis 	Yes
• Link Check	No
 connection monitoring IP-Alive 	No
 localization via Aeroscout 	Yes
SysLog	Yes
Protocol / is supported	
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
Product functions / VLAN	
Product function	
• function VLAN with IWLAN	Yes
Product functions / DHCP	
Product function	
DHCP client	Yes
DHCP server	Yes
DHCP Option 82	Yes
Product functions / redundancy	
Protocol / is supported	
• STP/RSTP	Yes
• MSTP	Yes
• RSTP	Yes
Product functions / Security	
Product function	
• ACL - MAC-based	Yes

 Management security, ACL-IP based 	Yes
• IEEE 802.1x (radius)	Yes
• NAT/NAPT	No
• access protection according to IEEE802.11i	Yes
• WPA/WPA2	Yes
• TKIP/AES	Yes
Protocol / is supported	
• SSH	Yes
• RADIUS	Yes
Product functions / time	

Product functions / time	
Protocol / is supported	
• NTP	Yes
• SNTP	Yes
 SIMATIC time synchronization (SIMATIC Time) 	Yes

otanuarus, specifications, approvais	
Standard	
• for FM	FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4
• for hazardous zone	EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
• for hazardous zone / from CSA and UL	ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, CL. 1, Div. 2, GP. A,B,C,D, T4 / CL. 1, Zone 2, GP IIC
Certificate of suitability	
 EC declaration of conformity 	Yes
CE marking	Yes
• C-Tick	Yes
● E1 approval	No
 Railway application in accordance with EN 50155 	No
 Railway application in accordance with EN 50121-4 	No
• NEMA TS2	No
• IEC 61375	No
• IEC 61850-3	No
• NEMA4X	No
 Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af 	Yes
 Power-over-Ethernet according to IEEE802.3at for type 2 	Yes
Standard for wireless communication	
● IEEE 802.11a	Yes

Standards, specifications, approvals

• IEEE 802.11b	Yes
• IEEE 802.11e	Yes
● IEEE 802.11g	Yes
• IEEE 802.11h	Yes
• IEEE 802.11i	Yes
• IEEE 802.11n	Yes
Wireless approval	You will find the current list of countries at: www.siemens.de/funkzulassungen
Marine classification association	
 American Bureau of Shipping Europe Ltd. (ABS) 	Yes
Bureau Veritas (BV)	Yes
• DNV GL	Yes
 Korean Register of Shipping (KRS) 	Yes
 Lloyds Register of Shipping (LRS) 	Yes
 Nippon Kaiji Kyokai (NK) 	Yes
 Polski Rejestr Statkow (PRS) 	Yes
Royal Institution of Naval Architects (RINA)	Yes

accessories

accessories 24 V DC screw terminal included in scope of delivery

Further information / Internet-Links

Internet-Link

• to website: TIA Selection Tool http://www.siemens.com/tia-selection-tool

to the website: IWLAN
 to website: Industry Mall
 https://mall.industry.siemens.com

• to website: Information and Download Center http://www.siemens.com/industry/infocenter

• to website: Image database http://automation.siemens.com/bilddb

• to website: CAx Download Manager http://www.siemens.com/cax

• to website: Industry Online Support

https://support.industry.siemens.com

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Thirdparty products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified:

06/22/2020