



IWLAN Access Point, SCALANCE W786-2 RJ45, 2 radios, 6 R-SMA antenna port, iFeatures support via key plug, IEEE 802.11a/b/g/h/n, 2.4/5GHz, gross 450 Mbit/s per radio, 1x RJ45 max. 1 Gbit/s, PoE, redundant 24 V DC, terminal block, 110 - 230 V AC via PS791-2AC IP65, -40..+60 °C, plug slot, WPA2/802.11i/e, observe national approvals! CERT ID: EAPN-W2-RJ-E3, includes: MPCIE-R1-ABGN-U3, scope of delivery: Manuals on CD-ROM, German/English, 1x terminal block; for operation outside of USA/Israel

Transfer rate	
Transfer rate	
<ul style="list-style-type: none"> with WLAN / maximum 	450 Mbit/s
<ul style="list-style-type: none"> for Industrial Ethernet 	10, 1000, 1000 Mbit/s
Transfer rate / for Industrial Ethernet	
<ul style="list-style-type: none"> minimum 	10 Mbit/s
<ul style="list-style-type: none"> maximum 	1000 Mbit/s
Interfaces	
Number of electrical connections	
<ul style="list-style-type: none"> for network components or terminal equipment 	1
<ul style="list-style-type: none"> for power supply 	1
<ul style="list-style-type: none"> for redundant voltage supply 	1
Type of electrical connection	
<ul style="list-style-type: none"> for network components or terminal equipment 	RJ45 socket
<ul style="list-style-type: none"> for power supply 	2-pole connector (24 V DC) or optionally available power supply adapter (4-pole 24 V DC or 3-pole 110 to 230 V AC)
design of the removable storage	
<ul style="list-style-type: none"> C-PLUG 	Yes

- KEY-PLUG

Yes

Interfaces / wireless

Number of radio cards / permanently installed	2
Transmission mode / for multiple input multiple output (MIMO)	3x3
Number of spatial streams	3
Number of electrical connections / for external antenna(s)	6
Type of electrical connection / for external antenna(s)	R-SMA (socket)
Product feature / external antenna can be mounted directly on device	No

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage / 1 <ul style="list-style-type: none"> • from terminal block 	19.2 V
Supply voltage / 2 <ul style="list-style-type: none"> • from terminal block 	28.8 V
Supply voltage <ul style="list-style-type: none"> • from Power-over-Ethernet acc. to IEEE802.3at for type 1 and IEEE802.3af • from Power-over-Ethernet acc. to IEEE802.3at for type 2 • from optional integrable power supply <ul style="list-style-type: none"> — at AC — at DC 	48 V 50 V 100 ... 240 V 12 ... 24 V
Consumed current <ul style="list-style-type: none"> • at DC / at 24 V / typical • at AC / at 230 V / typical • with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical 	0.63 A 0.07 A 0.22 A
Power loss [W] <ul style="list-style-type: none"> • at DC / at 24 V / typical • at AC / at 230 V / typical • with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical 	15 W 15 W 10.7 W

Ambient conditions

Ambient temperature <ul style="list-style-type: none"> • during operation • during storage • during transport 	-40 ... +60 °C -40 ... +85 °C -40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	100 %

Ambient condition / for operation	When using the 100 - 240 V AC power supply, an operating temperature of -40 °C to +60 °C is permissible
Protection class IP	IP65

Design, dimensions and weights

Width / of the enclosure / without antenna	251 mm
Height / of the enclosure / without antenna	251 mm
Depth / of the enclosure / without antenna	72 mm
Net weight	2.24 kg
Mounting type	For mast mounting, 35 mm DIN rail mounting and S7-300 rail mounting, an additional support plate is required
<ul style="list-style-type: none"> • S7-300 rail mounting • S7-1500 rail mounting • 35 mm DIN rail mounting • wall mounting 	Yes No Yes Yes

Radio frequencies

Operating frequency	
<ul style="list-style-type: none"> • for WLAN in 2.4 GHz frequency band • for WLAN in 5 GHz frequency band 	2.41 ... 2.48 GHz; depending on the country approvals 4.9 ... 5.8 GHz; depending on the country approvals

Product features, product functions, product components / general

Product function / Access Point Mode	Yes
Product function / Client Mode	Yes
Number of SSIDs	16
Product function	
<ul style="list-style-type: none"> • iPCF Access Point • iPCF client • iPCF-MC Access Point • iPCF-MC client 	Yes; Only in combination with the 'KEY-PLUG W780 iFeatures' Yes; Only in combination with the 'KEY-PLUG W780 iFeatures' or 'KEY-PLUG W740 iFeatures' Yes; Only in combination with the 'KEY-PLUG W780 iFeatures' Yes; Only in combination with 'KEY-PLUG W780 iFeatures' or 'KEY-PLUG W740 iFeatures'
Number of iPCF-capable radio modules	2
Product function / iREF	Yes; In combination only with 'KEY-PLUG W780 iFeatures'
Number of iREF-capable radio modules	2
Product function / iPRP	Yes; In combination with the 'KEY-PLUG W780 iFeatures' only

Product functions / management, configuration, engineering

Number of manageable IP addresses / in client	8
Product function	
<ul style="list-style-type: none"> • CLI • web-based management • MIB support • TRAPs via email • Configuration with STEP 7 	Yes Yes Yes Yes Yes

<ul style="list-style-type: none"> • configuration with STEP 7 in the TIA Portal • operation with IWLAN controller • operation with Enterasys WLAN controller • forced roaming on IP down with IWLAN • forced roaming on link down with IWLAN • WDS 	<p>Yes</p> <p>No</p> <p>No</p> <p>Yes</p> <p>Yes</p> <p>Yes</p>
Protocol / is supported <ul style="list-style-type: none"> • Address Resolution Protocol (ARP) • ICMP • Telnet • HTTP • HTTPS • TFTP • DCP • LLDP 	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p>
Identification & maintenance function <ul style="list-style-type: none"> • I&M0 - device-specific information • I&M1 – higher-level designation/location designation 	<p>Yes</p> <p>Yes</p>

Product functions / Diagnostics

Product function <ul style="list-style-type: none"> • PROFINET IO diagnosis • Link Check • connection monitoring IP-Alive • localization via Aeroscout • SysLog 	<p>Yes</p> <p>No</p> <p>No</p> <p>Yes</p> <p>Yes</p>
Protocol / is supported <ul style="list-style-type: none"> • SNMP v1 • SNMP v2 • SNMP v3 	<p>Yes</p> <p>Yes</p> <p>Yes</p>

Product functions / VLAN

Product function <ul style="list-style-type: none"> • function VLAN with IWLAN 	<p>Yes</p>
--	------------

Product functions / DHCP

Product function <ul style="list-style-type: none"> • DHCP client • DHCP server • DHCP Option 82 	<p>Yes</p> <p>Yes</p> <p>Yes</p>
--	----------------------------------

Product functions / redundancy

Protocol / is supported	
--------------------------------	--

• STP/RSTP	Yes
• MSTP	Yes
• RSTP	Yes

Product functions / Security

Product function	
• ACL - MAC-based	Yes
• Management security, ACL-IP based	Yes
• IEEE 802.1x (radius)	Yes
• NAT/NAPT	No
• access protection according to IEEE802.11i	Yes
• WPA/WPA2	Yes
• TKIP/AES	Yes
Protocol / is supported	
• SSH	Yes
• RADIUS	Yes

Product functions / time

Protocol / is supported	
• NTP	Yes
• SNTP	Yes
• SIMATIC time synchronization (SIMATIC Time)	Yes

Standards, specifications, approvals

Standard	
• for FM	FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4
• for hazardous zone	EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
Certificate of suitability	
• EC declaration of conformity	Yes
• CE marking	Yes
• C-Tick	Yes
• E1 approval	Yes
• Railway application in accordance with EN 50155	No
• Railway application in accordance with EN 50121-4	Yes
• NEMA TS2	No
• IEC 61375	No
• IEC 61850-3	No
• NEMA4X	Yes

<ul style="list-style-type: none"> • Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af 	Yes
<ul style="list-style-type: none"> • Power-over-Ethernet according to IEEE802.3at for type 2 	Yes
Standard for wireless communication	
<ul style="list-style-type: none"> • IEEE 802.11a 	Yes
<ul style="list-style-type: none"> • IEEE 802.11b 	Yes
<ul style="list-style-type: none"> • IEEE 802.11e 	Yes
<ul style="list-style-type: none"> • IEEE 802.11g 	Yes
<ul style="list-style-type: none"> • IEEE 802.11h 	Yes
<ul style="list-style-type: none"> • IEEE 802.11i 	Yes
<ul style="list-style-type: none"> • IEEE 802.11n 	Yes
Wireless approval	You will find the current list of countries at: www.siemens.de/funkzulassungen
Marine classification association	
<ul style="list-style-type: none"> • American Bureau of Shipping Europe Ltd. (ABS) 	Yes
<ul style="list-style-type: none"> • Bureau Veritas (BV) 	Yes
<ul style="list-style-type: none"> • DNV GL 	Yes
<ul style="list-style-type: none"> • Korean Register of Shipping (KRS) 	Yes
<ul style="list-style-type: none"> • Lloyds Register of Shipping (LRS) 	Yes
<ul style="list-style-type: none"> • Nippon Kaiji Kyokai (NK) 	Yes
<ul style="list-style-type: none"> • Polski Rejestr Statkow (PRS) 	Yes
<ul style="list-style-type: none"> • Royal Institution of Naval Architects (RINA) 	Yes

accessories

accessories	24 V DC screw terminal included in scope of delivery
-------------	--

Further information / Internet-Links

Internet-Link	
<ul style="list-style-type: none"> • to website: TIA Selection Tool 	http://www.siemens.com/tia-selection-tool
<ul style="list-style-type: none"> • to the website: IWLAN 	http://www.siemens.com/iwlan
<ul style="list-style-type: none"> • to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> • to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
<ul style="list-style-type: none"> • to website: Image database 	http://automation.siemens.com/bilddb
<ul style="list-style-type: none"> • to website: CAx Download Manager 	http://www.siemens.com/cax
<ul style="list-style-type: none"> • to website: Industry Online Support 	https://support.industry.siemens.com

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

05/28/2020