



IWLAN Access Point, SCALANCE W786-2 SFP, 2 radios, 6 R-SMA antenna port, iFeatures support via key plug, IEEE 802.11a/b/g/h/n, 2.4/5GHz, gross 450 Mbit/s per radio, 2x SFP 1 Gbit/s switches, redundant 24 V DC, terminal block, 110 - 230 V AC via PS791-2AC IP65, -40..+60 °C, plug slot, Temperature range dependent on SFP WPA2/802.11i/e, observe national approvals! CERT ID: EAPN-W2-SFP-E3 includes: MPCIE-R1-ABGN-U3, scope of delivery: Manuals on CD-ROM, German/English, for operation outside of USA/Israel

| Transfer rate | |
|--|--|
| Transfer rate | |
| <ul style="list-style-type: none"> with WLAN / maximum | 450 Mbit/s |
| <ul style="list-style-type: none"> for Industrial Ethernet | 1000 Mbit/s |
| Transfer rate / for Industrial Ethernet | |
| <ul style="list-style-type: none"> minimum | 1000 Mbit/s |
| <ul style="list-style-type: none"> maximum | 1000 Mbit/s |
| Interfaces | |
| Number of electrical connections | |
| <ul style="list-style-type: none"> for power supply | 1 |
| <ul style="list-style-type: none"> for redundant voltage supply | 0 |
| Type of electrical connection | |
| <ul style="list-style-type: none"> for power supply | 2-pole connector (24 V DC) or optionally available power supply adapter (4-pole 24 V DC or 3-pole 110 to 230 V AC) |
| Number of optical interfaces | |
| <ul style="list-style-type: none"> for fiber optic cable / at 1000 Mbit/s | 2 |
| Design of the optical interface | |
| <ul style="list-style-type: none"> for fiber optic cable / at 1000 Mbit/s | SFP slot |

| | |
|---------------------------------|-----|
| design of the removable storage | |
| • C-PLUG | Yes |
| • KEY-PLUG | Yes |

Interfaces / wireless

| | |
|--|----------------|
| Number of radio cards / permanently installed | 2 |
| Transmission mode / for multiple input multiple output (MIMO) | 3x3 |
| Number of spatial streams | 3 |
| Number of electrical connections / for external antenna(s) | 6 |
| Type of electrical connection / for external antenna(s) | R-SMA (socket) |
| Product feature / external antenna can be mounted directly on device | No |

Supply voltage, current consumption, power loss

| | |
|---|---------------|
| Type of voltage / of the supply voltage | DC |
| Supply voltage / 1 | |
| • from terminal block | 19.2 V |
| Supply voltage / 2 | |
| • from terminal block | 28.8 V |
| Supply voltage | |
| • from optional integrable power supply | |
| — at AC | 100 ... 240 V |
| — at DC | 12 ... 24 V |

Ambient conditions

| | |
|--|---|
| Ambient temperature | |
| • during operation | -40 ... +60 °C |
| • during storage | -40 ... +85 °C |
| • during transport | -40 ... +70 °C |
| Relative humidity / at 25 °C / without condensation / during operation / maximum | 100 % |
| Ambient condition / for operation | When using the 100 - 240 V AC power supply, an operating temperature of -40 °C to +60 °C is permissible |
| Protection class IP | IP65 |

Design, dimensions and weights

| | |
|---|--|
| Width / of the enclosure / without antenna | 251 mm |
| Height / of the enclosure / without antenna | 251 mm |
| Depth / of the enclosure / without antenna | 72 mm |
| Net weight | 2.24 kg |
| Mounting type | For mast mounting, 35 mm DIN rail mounting and S7-300 rail mounting, an additional support plate is required |
| • S7-300 rail mounting | Yes |
| • S7-1500 rail mounting | No |

- 35 mm DIN rail mounting
- wall mounting

Yes
Yes

Radio frequencies

Operating frequency

- for WLAN in 2.4 GHz frequency band
- for WLAN in 5 GHz frequency band

2.41 ... 2.48 GHz; depending on the country approvals
4.9 ... 5.8 GHz; depending on the country approvals

Product features, product functions, product components / general

| | |
|--|--|
| Product function / Access Point Mode | Yes |
| Product function / Client Mode | Yes |
| Number of SSIDs | 16 |
| Product function | |
| <ul style="list-style-type: none"> • iPCF Access Point • iPCF client | Yes; Only in combination with the 'KEY-PLUG W780 iFeatures' |
| <ul style="list-style-type: none"> • iPCF-MC Access Point • iPCF-MC client | Yes; Only in combination with the 'KEY-PLUG W780 iFeatures' or 'KEY-PLUG W740 iFeatures' |
| Number of iPCF-capable radio modules | 2 |
| Product function / iREF | Yes; In combination only with 'KEY-PLUG W780 iFeatures' |
| Number of iREF-capable radio modules | 2 |
| Product function / iPRP | Yes; In combination with the 'KEY-PLUG W780 iFeatures' only |

Product functions / management, configuration, engineering

| | |
|---|---|
| Number of manageable IP addresses / in client | 8 |
| Product function | |
| <ul style="list-style-type: none"> • CLI • web-based management • MIB support • TRAPs via email • Configuration with STEP 7 • configuration with STEP 7 in the TIA Portal • operation with IWLAN controller • operation with Enterasys WLAN controller • forced roaming on IP down with IWLAN • forced roaming on link down with IWLAN • WDS | Yes Yes Yes Yes Yes Yes No No Yes Yes Yes |
| Protocol / is supported | |
| <ul style="list-style-type: none"> • Address Resolution Protocol (ARP) • ICMP • Telnet • HTTP • HTTPS | Yes Yes Yes Yes Yes |

| | |
|--|-----|
| • TFTP | Yes |
| • DCP | Yes |
| • LLDP | Yes |
| Identification & maintenance function | |
| • I&M0 - device-specific information | Yes |
| • I&M1 – higher-level designation/location designation | Yes |

Product functions / Diagnostics

| | |
|----------------------------------|-----|
| Product function | |
| • PROFINET IO diagnosis | Yes |
| • Link Check | No |
| • connection monitoring IP-Alive | No |
| • localization via Aeroscout | Yes |
| • SysLog | Yes |
| Protocol / is supported | |
| • SNMP v1 | Yes |
| • SNMP v2 | Yes |
| • SNMP v3 | Yes |

Product functions / VLAN

| | |
|----------------------------|-----|
| Product function | |
| • function VLAN with IWLAN | Yes |

Product functions / DHCP

| | |
|-------------------------|-----|
| Product function | |
| • DHCP client | Yes |
| • DHCP server | Yes |
| • DHCP Option 82 | Yes |

Product functions / redundancy

| | |
|--------------------------------|-----|
| Protocol / is supported | |
| • STP/RSTP | Yes |
| • MSTP | Yes |
| • RSTP | Yes |

Product functions / Security

| | |
|--|-----|
| Product function | |
| • ACL - MAC-based | Yes |
| • Management security, ACL-IP based | Yes |
| • IEEE 802.1x (radius) | Yes |
| • NAT/NAPT | No |
| • access protection according to IEEE802.11i | Yes |
| • WPA/WPA2 | Yes |
| • TKIP/AES | Yes |

| | |
|--|--|
| Protocol / is supported | |
| • SSH | Yes |
| • RADIUS | Yes |
| Product functions / time | |
| Protocol / is supported | |
| • NTP | Yes |
| • SNTP | Yes |
| • SIMATIC time synchronization (SIMATIC Time) | Yes |
| Standards, specifications, approvals | |
| Standard | |
| • for FM | FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4 |
| • for hazardous zone | EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X |
| • for safety / from CSA and UL | UL 60950-1, CSA C22.2 No. 60950-1 |
| • for hazardous zone / from CSA and UL | ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, CL. 1, Div. 2, GP. A,B,C,D, T4 / CL. 1, Zone 2, GP IIC |
| Certificate of suitability | |
| • EC declaration of conformity | Yes |
| • CE marking | Yes |
| • C-Tick | Yes |
| • E1 approval | Yes |
| • Railway application in accordance with EN 50155 | No |
| • Railway application in accordance with EN 50121-4 | Yes |
| • NEMA TS2 | No |
| • IEC 61375 | No |
| • IEC 61850-3 | No |
| • NEMA4X | Yes |
| • Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af | No |
| • Power-over-Ethernet according to IEEE802.3at for type 2 | No |
| Standard for wireless communication | |
| • IEEE 802.11a | Yes |
| • IEEE 802.11b | Yes |
| • IEEE 802.11e | Yes |
| • IEEE 802.11g | Yes |
| • IEEE 802.11h | Yes |
| • IEEE 802.11i | Yes |
| • IEEE 802.11n | Yes |

| | |
|--|---|
| Wireless approval | You will find the current list of countries at: www.siemens.de/funkzulassungen |
| Marine classification association | |
| <ul style="list-style-type: none"> American Bureau of Shipping Europe Ltd. (ABS) Bureau Veritas (BV) DNV GL Korean Register of Shipping (KRS) Lloyds Register of Shipping (LRS) Nippon Kaiji Kyokai (NK) Polski Rejestr Statkow (PRS) Royal Institution of Naval Architects (RINA) | <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> |

accessories

| | |
|-------------|--|
| accessories | 24 V DC screw terminal included in scope of delivery |
|-------------|--|

Further information / Internet-Links

| | |
|--|--|
| Internet-Link | |
| <ul style="list-style-type: none"> to website: TIA Selection Tool to the website: IWLAN to website: Industry Mall to website: Information and Download Center to website: Image database to website: CAx Download Manager to website: Industry Online Support | <p>http://www.siemens.com/tia-selection-tool</p> <p>http://www.siemens.com/iwlan</p> <p>https://mall.industry.siemens.com</p> <p>http://www.siemens.com/industry/infocenter</p> <p>http://automation.siemens.com/bilddb</p> <p>http://www.siemens.com/cax</p> <p>https://support.industry.siemens.com</p> |

Security information

| | |
|----------------------|--|
| Security information | <p>Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)</p> |
|----------------------|--|

last modified: 05/28/2020