

SCALANCE M804PB; Router for secure remote connection of PROFIBUS / MPI programmable controllers at Ethernet networks medium VPN and firewall. Further functions: address conversion (NAT/NAPT), connection to SINEMA RC, 2-port switch; 1x digital input, 1x digital output.



Transfer rate	
Transfer rate	10 Mbit/s, 100 Mbit/s
Interfaces	
Number of electrical connections	
• for internal network	2
• for external network	1
Number of interfaces / acc. to RS 485	1
Number of electrical connections	
• for power supply	2
Type of electrical connection	
• for internal network	RJ45 port (10/100 Mbit/s, TP, autocrossover), SUB-D
• for external network	RJ45 port (10/100 Mbit/s, TP, autocrossover)
• for power supply	Terminal strip
Signal inputs/outputs	
Number of electrical connections	
• for digital input signals	1
• for digital output signals	1
Type of electrical connection	

- for digital input signals
- for digital output signals

Terminal block

Terminal block

Supply voltage, current consumption, power loss

Supply voltage / Rated value	24 V
Supply voltage / rated value	10.8 ... 28.8
Type of voltage / of the supply voltage	DC
Consumed current / at rated supply voltage / maximum	250 mA
Power loss [W]	
<ul style="list-style-type: none"> • maximum 	8 W

Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> • during operation • during storage 	-20 ... +60 °C -40 ... +85 °C
Relative humidity / at 25 °C / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weights

Design	compact
Depth	127 mm
Height	147 mm
Width	35 mm
Mounting type	
<ul style="list-style-type: none"> • 35 mm DIN rail mounting • S7-300 rail mounting • S7-1500 rail mounting • wall mounting 	Yes Yes Yes Yes

Product features, product functions, product components / general

Product function	
<ul style="list-style-type: none"> • DynDNS client • no-ip.com client 	Yes Yes

Product functions / management, configuration, engineering

Product function	
<ul style="list-style-type: none"> • CLI • web-based management • MIB support • TRAPs via email 	Yes Yes Yes Yes
Protocol / is supported	
<ul style="list-style-type: none"> • Telnet • HTTP 	Yes Yes

• HTTPS	Yes
Type of configuration	Web-based management
Product functions / Diagnostics	
Protocol / is supported	
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v2c	Yes
• SNMP v3	Yes
Product function	
• Statistics Packet Size	No
• Statistics packet type	No
• Error statistics	No
• SysLog	Yes
• Packet Filter Log	Yes
Product functions / DHCP	
Product function	
• DHCP client	Yes
• DHCP server - internal network	Yes
Product functions / Routing	
Router function	
• NAT (IP masquerading)	Yes
• Port forwarding	Yes
• NAT traversal	Yes
• 1:1 NAT	Yes
• DNS cache	Yes
Product functions / Security	
Suitability for operation / Virtual Private Network	Yes
Firewall version	Statefull Inspection
Product function	
• Password protection	Yes
• packet filter	Yes
• Broadcast/Multicast/Unicast Limiter	No
Product function	
• broadcast blocking	No
• with VPN connection	IPsec, OpenVPN (as Client)
Number of possible connections / with VPN connection	20
Type of authentication / with Virtual Private Network / PSK	Yes
Protocol / is supported	
• IPsec tunnel and transport mode	Yes

Key length	
<ul style="list-style-type: none"> • 1 / with IPsec AES / with Virtual Private Network 	128 bit
<ul style="list-style-type: none"> • 2 / with IPsec AES / with Virtual Private Network 	192 bit
<ul style="list-style-type: none"> • 3 / with IPsec AES / with Virtual Private Network 	256 bit
<ul style="list-style-type: none"> • with IPsec 3DES / with Virtual Private Network 	168 bit
Type of Internet key exchange / with Virtual Private Network	
<ul style="list-style-type: none"> • main mode 	Yes
<ul style="list-style-type: none"> • quick mode 	Yes
Type of packet authentication / with Virtual Private Network	MD5, SHA-1, SHA-256, SHA-384, SHA-512
IETF profile / with Virtual Private Network / X.509v3 certificate	Yes

Product functions / time

Protocol / is supported	
<ul style="list-style-type: none"> • NTP 	Yes
<ul style="list-style-type: none"> • SNTP 	Yes

Further information / Internet-Links

Internet-Link	
<ul style="list-style-type: none"> • to website: Selector for cables and connectors 	http://www.siemens.com/snst
<ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL 	http://www.siemens.com/snst
<ul style="list-style-type: none"> • to website: Industrial communication 	http://www.siemens.com/simatic-net
<ul style="list-style-type: none"> • to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> • to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
<ul style="list-style-type: none"> • to website: Image database 	http://automation.siemens.com/bilddb
<ul style="list-style-type: none"> • to website: CAx Download Manager 	http://www.siemens.com/cax
<ul style="list-style-type: none"> • to website: Industry Online Support 	https://support.industry.siemens.com

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

05/12/2020