

SCALANCE M826-2 SHDSL router; for the IP communication via 2-wire and 4-wire cables from Ethernet-based Programmable controllers; SHDSL topology: Point-to-point, bonding, line bridge mode; Routing mode with VPN, Firewall, NAT; 4-port switch; 1x digital input, 1x digital output



Transfer rate	
Transfer rate	10 Mbit/s, 100 Mbit/s
Transfer rate	
<ul style="list-style-type: none"> for SHDSL transmission / maximum 	15.3 Mbit/s
Interfaces	
Number of electrical connections	
<ul style="list-style-type: none"> for internal network 	4
<ul style="list-style-type: none"> for external network 	2
Number of electrical connections	
<ul style="list-style-type: none"> for power supply 	2
Type of electrical connection	
<ul style="list-style-type: none"> for internal network 	RJ45 port (10/100 Mbit/s, TP, autocrossover)
<ul style="list-style-type: none"> for external network 	Terminal strip
<ul style="list-style-type: none"> for power supply 	Terminal strip
Signal inputs/outputs	
Number of electrical connections	
<ul style="list-style-type: none"> for digital input signals 	1
<ul style="list-style-type: none"> for digital output signals 	1

Type of electrical connection	
<ul style="list-style-type: none"> • for digital input signals • for digital output signals 	Terminal block
	Terminal block

WAN connection

Type of WAN connection / is supported / SHSDL	Yes
---	-----

Supply voltage, current consumption, power loss

Supply voltage / Rated value	24 V
Supply voltage / rated value	10.8 ... 28.8
Type of voltage / of the supply voltage	DC
Consumed current / at rated supply voltage / maximum	290 mA

Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> • during operation • during storage 	-40 ... +70 °C
	-40 ... +80 °C
Relative humidity / at 25 °C / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weights

Design	compact
Depth	127 mm
Height	147 mm
Width	35 mm
Mounting type	
<ul style="list-style-type: none"> • 35 mm DIN rail mounting • S7-300 rail mounting • S7-1500 rail mounting • wall mounting 	Yes
	Yes
	Yes
	Yes

Product features, product functions, product components / general

Product function	
<ul style="list-style-type: none"> • DynDNS client • no-ip.com client 	Yes
	Yes

Product functions / management, configuration, engineering

Product function	
<ul style="list-style-type: none"> • CLI • web-based management • MIB support • TRAPs via email 	Yes
	Yes
	Yes
	Yes
Protocol / is supported	
<ul style="list-style-type: none"> • Telnet 	Yes

• HTTP	Yes
• HTTPS	Yes
Type of configuration	Web-based management

Product functions / Diagnostics

Protocol / is supported	
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v2c	Yes
• SNMP v3	Yes
Product function	
• Statistics Packet Size	No
• Statistics packet type	No
• Error statistics	No
• SysLog	Yes
• Packet Filter Log	Yes

Product functions / DHCP

Product function	
• DHCP client	Yes
• DHCP server - internal network	Yes

Product functions / Routing

Router function	
• NAT (IP masquerading)	Yes
• Port forwarding	Yes
• NAT traversal	Yes
• 1:1 NAT	Yes
• DNS cache	Yes

Product functions / Security

Suitability for operation / Virtual Private Network	Yes
Firewall version	Statefull Inspection
Product function	
• Password protection	Yes
• packet filter	Yes
• Broadcast/Multicast/Unicast Limiter	No
Product function	
• broadcast blocking	No
• with VPN connection	IPsec, OpenVPN (as Client)
Number of possible connections / with VPN connection	20
Type of authentication / with Virtual Private Network / PSK	Yes
Protocol / is supported	

<ul style="list-style-type: none"> • IPsec tunnel and transport mode 	Yes
Key length <ul style="list-style-type: none"> • 1 / with IPsec AES / with Virtual Private Network • 2 / with IPsec AES / with Virtual Private Network • 3 / with IPsec AES / with Virtual Private Network • with IPsec 3DES / with Virtual Private Network 	128 bit 192 bit 256 bit 168 bit
Type of Internet key exchange / with Virtual Private Network <ul style="list-style-type: none"> • main mode • quick mode 	Yes Yes
Type of packet authentication / with Virtual Private Network	MD5, SHA-1, SHA-256, SHA-384, SHA-512
IETF profile / with Virtual Private Network / X.509v3 certificate	Yes

Product functions / time	
Protocol / is supported <ul style="list-style-type: none"> • NTP • SNTP 	Yes Yes

Standards, specifications, approvals	
Standard <ul style="list-style-type: none"> • for FM • for hazardous zone • for safety / from CSA and UL • for hazardous zone / from CSA and UL 	FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4 EN 60079-15, EN 60079-0, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X UL E115352 Vol. X2 ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, CL. 1, Div. 2, GP. A,B,C,D, T4 / CL. 1, Zone 2, GP IIC
Certificate of suitability <ul style="list-style-type: none"> • CE marking • Railway application in accordance with EN 50121-3-2 • Railway application in accordance with EN 50121-4 • Railway application in accordance with EN 50155 • railway application in accordance with EN 61373 	Yes Yes Yes Yes; no coated printed circuit boards Yes; cat. 1, cl.A and cl. B
Marine classification association <ul style="list-style-type: none"> • American Bureau of Shipping Europe Ltd. (ABS) • Bureau Veritas (BV) 	Yes Yes

- DNV GL
- Korean Register of Shipping (KRS)
- Lloyds Register of Shipping (LRS)
- Nippon Kaiji Kyokai (NK)
- Polski Rejestr Statkow (PRS)
- Royal Institution of Naval Architects (RINA)

Yes
Yes
Yes
Yes
Yes
Yes

Further information / Internet-Links

Internet-Link

- to website: Selector for cables and connectors
- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>
<http://www.siemens.com/snst>
<http://www.siemens.com/simatic-net>
<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

05/12/2020