

Product type designation

CP 1243-7 LTE EU

Communications processor CP 1243-7 LTE EU for Connection of SIMATIC S7-1200 to LTE network in European Frequency range



Transfer rate

Transfer rate

- for LTE transmission
 - with downlink / maximum 42 Mbit/s
 - with uplink / maximum 5.76 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet	0
Number of electrical connections <ul style="list-style-type: none"> • for external antenna(s) • for power supply 	1 1
Number of slots <ul style="list-style-type: none"> • for SIM cards 	1
Type of electrical connection <ul style="list-style-type: none"> • for external antenna(s) • for power supply 	SMA socket (50 ohms) 3-pole terminal block
Slot version <ul style="list-style-type: none"> • for SIM card 	Standard

Wireless technology

Type of mobile wireless service	
• is supported / SMS	Yes
• is supported / GPRS	Yes
• Note	GPRS (Multislot Class 10)
Type of mobile network / is supported	
• GSM	Yes
• UMTS	Yes
• LTE	Yes
Operating frequency / for GSM transmission	900 MHz, 1800 MHz
Operating frequency / with UMTS transmission	900 MHz, 2100 MHz
Operating frequency / for LTE transmission	800 MHz, 1800 MHz, 2600 MHz

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage / external	24 V
Supply voltage / external / at DC / Rated value	24 V
Relative positive tolerance / at DC / at 24 V	20 %
Relative negative tolerance / at DC / at 24 V	20 %
Consumed current	
• from external supply voltage / at DC / at 24 V / typical	0.1 A
• from external supply voltage / at DC / at 24 V / maximum	0.22 A

Ambient conditions

Ambient temperature	
• for vertical installation / during operation	-20 ... +60 °C
• for horizontally arranged busbars / during operation	-20 ... +70 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weights

Module format	Compact module S7-1200 single width
Width	30 mm
Height	100 mm
Depth	75 mm
Net weight	0.133 kg
Mounting type	
• 35 mm DIN rail mounting	Yes

- S7-300 rail mounting
- wall mounting

No
Yes

Product features, product functions, product components / general

Number of units

- per CPU / maximum

3

Performance data

Number of users/telephone numbers / definable / maximum

10

Performance data / open communication

Number of possible connections / for open communication

- by means of T blocks / maximum

like CPU

Performance data / IT functions

Number of possible connections

- as e-mail client / maximum

1

Performance data / telecontrol

Suitability for use

- substation

Yes

Control center connection

- by means of a permanent connection
- by means of demand-oriented connection
- Note

Telecontrol Server Basic

supported

supported

Connection to SCADA system using OPC interface

Protocol / is supported

- DNP3
- IEC 60870-5

No

No

Product function / data buffering if connection is aborted

Yes; 64,000 events

Number of stations / for direct communication / with Telecontrol Server Basic

- in send direction / maximum
- in receive direction / maximum

3

15

Performance data / teleservice

Diagnostics function / online diagnostics with SIMATIC STEP 7

Yes

Product function

- program download with SIMATIC STEP 7
- Remote firmware update

Yes

Yes

Product functions / management, configuration, engineering

Configuration software

- required

STEP 7 Basic/Professional

Product functions / Diagnostics

Product function / Web-based diagnostics	Yes
--	-----

Product functions / Security

Firewall version	stateful inspection
Product function / with VPN connection	IPsec, SINEMA RC
Type of encryption algorithms / with VPN connection	AES-256, AES-192, AES-128, 3DES-168, DES-56
Type of authentication procedure / with VPN connection	Preshared key (PSK), X.509v3 certificates
Type of hashing algorithms / with VPN connection	MD5, SHA-1
Number of possible connections / with VPN connection	1
Product function	
• password protection for teleservice access	Yes
• encrypted data transmission	Yes

Product functions / time

Protocol / is supported	
• NTP	Yes
time synchronization	
• from control center	Yes

Further information / Internet-Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

05/12/2020