

Product type designation

CP 1243-7 LTE US

Communications processor CP 1243-7 LTE US for Connection of SIMATIC S7-1200 to LTE network in American frequency band



Transfer rate

Transfer rate

- for LTE transmission
 - with downlink / maximum 42 Mbit/s
 - with uplink / maximum 5.76 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet	0
Number of electrical connections	
<ul style="list-style-type: none"> • for external antenna(s) • for power supply 	1 1
Number of slots	
<ul style="list-style-type: none"> • for SIM cards 	1
Type of electrical connection	
<ul style="list-style-type: none"> • for external antenna(s) • for power supply 	SMA socket (50 ohms) 3-pole terminal block
Slot version	
<ul style="list-style-type: none"> • for SIM card 	Standard

Wireless technology

Type of mobile wireless service	
• is supported / SMS	Yes
• is supported / GPRS	Yes
• Note	GPRS (Multislot Class 10)
Type of mobile network / is supported	
• GSM	Yes
• UMTS	Yes
• LTE	Yes
Operating frequency	
• 850 MHz	Yes
• 1900 MHz	Yes
Operating frequency / for LTE transmission	700 MHz, 1700 MHz

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage / external	24 V
Supply voltage / external / at DC / Rated value	24 V
Relative positive tolerance / at DC / at 24 V	20 %
Relative negative tolerance / at DC / at 24 V	20 %
Consumed current	
• from external supply voltage / at DC / at 24 V / typical	0.1 A
• from external supply voltage / at DC / at 24 V / maximum	0.22 A

Ambient conditions

Ambient temperature	
• for vertical installation / during operation	-20 ... +60 °C
• for horizontally arranged busbars / during operation	-20 ... +70 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weights

Module format	Compact module S7-1200 single width
Width	30 mm
Height	100 mm
Depth	75 mm
Net weight	0.133 kg
Mounting type	

- 35 mm DIN rail mounting Yes
- S7-300 rail mounting No
- wall mounting Yes

Product features, product functions, product components / general

- Number of units
- per CPU / maximum 3

Performance data

- Number of users/telephone numbers / definable / maximum 10

Performance data / open communication

- Number of possible connections / for open communication
- by means of T blocks / maximum like CPU

Performance data / IT functions

- Number of possible connections
- as e-mail client / maximum 1

Performance data / telecontrol

- Suitability for use
- substation Yes
- Control center connection
- by means of a permanent connection Telecontrol Server Basic supported
 - by means of demand-oriented connection supported
 - Note Connection to SCADA system using OPC interface
- Protocol / is supported
- DNP3 No
 - IEC 60870-5 No
- Product function / data buffering if connection is aborted Yes; 64,000 events
- Number of stations / for direct communication / with Telecontrol Server Basic
- in send direction / maximum 3
 - in receive direction / maximum 15

Performance data / teleservice

- Diagnostics function / online diagnostics with SIMATIC STEP 7 Yes
- Product function
- program download with SIMATIC STEP 7 Yes
 - Remote firmware update Yes

Product functions / management, configuration, engineering

- Configuration software

- required

STEP 7 Basic/Professional

Product functions / Diagnostics

Product function / Web-based diagnostics	Yes
--	-----

Product functions / Security

Firewall version	stateful inspection
Product function / with VPN connection	IPsec, SINEMA RC
Type of encryption algorithms / with VPN connection	AES-256, AES-192, AES-128, 3DES-168, DES-56
Type of authentication procedure / with VPN connection	Preshared key (PSK), X.509v3 certificates
Type of hashing algorithms / with VPN connection	MD5, SHA-1
Number of possible connections / with VPN connection	1
Product function	
<ul style="list-style-type: none"> • password protection for teleservice access 	Yes
<ul style="list-style-type: none"> • encrypted data transmission 	Yes

Product functions / time

Protocol / is supported	
<ul style="list-style-type: none"> • NTP 	Yes
time synchronization	
<ul style="list-style-type: none"> • from control center 	Yes

Further information / Internet-Links

Internet-Link	
<ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL 	http://www.siemens.com/snst
<ul style="list-style-type: none"> • to website: Industrial communication 	http://www.siemens.com/simatic-net
<ul style="list-style-type: none"> • to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> • to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
<ul style="list-style-type: none"> • to website: Image database 	http://automation.siemens.com/bilddb
<ul style="list-style-type: none"> • to website: CAx Download Manager 	http://www.siemens.com/cax
<ul style="list-style-type: none"> • to website: Industry Online Support 	https://support.industry.siemens.com

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

05/12/2020