

Product type designation

CP 443-5 Extended

Communications processor CP 443-5 Extended for connection of SIMATIC S7-400 to PROFIBUS DP, S5-compatible, PG/OP and S7 communication Conformal coating



Figure similar

Transfer rate

Transfer rate

- at the 1st interface / acc. to PROFIBUS 9.6 kbit/s ... 12 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet

0

Number of electrical connections

- at the 1st interface / acc. to PROFIBUS 1

Type of electrical connection

- at the 1st interface / acc. to PROFIBUS 9-pin Sub-D socket (RS485)

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Supply voltage / 1 / from backplane bus

5 V

Relative symmetrical tolerance / at DC

- at 5 V 5 %

Consumed current

- from backplane bus / at DC / at 5 V / typical 0.6 A

Power loss [W]	3 W
----------------	-----

Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> during operation 	0 ... 60 °C
<ul style="list-style-type: none"> during storage 	-40 ... +70 °C
<ul style="list-style-type: none"> during transport 	-40 ... +70 °C
Relative humidity	
<ul style="list-style-type: none"> at 25 °C / without condensation / during operation / maximum 	95 %
Protection class IP	IP20

Design, dimensions and weights

Module format	Compact module S7-400 single width
Width	25 mm
Height	290 mm
Depth	210 mm
Net weight	0.65 kg

Product features, product functions, product components / general

Number of units	
<ul style="list-style-type: none"> per CPU / maximum 	14
<ul style="list-style-type: none"> Note 	The number of CPs that can be operated as DP masters depends on the number of CP 443-1 Advanced processors operating in the S7-400 station as PROFINET IO controllers. Up to 10 CPs can be operated in total: up to 4 as PROFINET IO controllers (CP 443-1 Advanced); up to 10 as DP masters (CP 443-5 Extended)

Performance data / open communication

Number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	32
Amount of data	
<ul style="list-style-type: none"> as user data per connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	240 byte

Performance data / PROFIBUS DP

Service / as DP master	
<ul style="list-style-type: none"> DPV1 	Yes
Number of DP slaves	
<ul style="list-style-type: none"> on DP master / usable 	125
Amount of data	
<ul style="list-style-type: none"> of the address area of the inputs / as DP master / total 	4096 byte
<ul style="list-style-type: none"> of the address area of the outputs / as DP master / total 	4096 byte

- of the address area of the inputs / per DP slave 244 byte
- of the address area of the outputs / per DP slave 244 byte

Performance data / S7 communication

- Number of possible connections / for S7 communication
- maximum 48

Performance data / multi-protocol mode

- Number of active connections / with multi-protocol mode
- without DP / maximum 59
 - with DP / maximum 54

Product functions / management, configuration, engineering

- Configuration software
- required STEP 7 V5.4 SP4 or higher / STEP 7 Professional V12 (TIA Portal) or higher

Further information / Internet-Links

- Internet-Link
- to website: Selector SIMATIC NET SELECTION TOOL <http://www.siemens.com/snst>
 - to website: Industrial communication <http://www.siemens.com/simatic-net>
 - to website: Industry Mall <https://mall.industry.siemens.com>
 - to website: Information and Download Center <http://www.siemens.com/industry/infocenter>
 - to website: Image database <http://automation.siemens.com/bilddb>
 - to website: CAx Download Manager <http://www.siemens.com/cax>
 - to website: Industry Online Support <https://support.industry.siemens.com>

Security information

- Security information
- Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

05/12/2020