

Product type designation

Product description

Communication cable without connector

Highly flexible communication line (6-core)
RFID systems connecting cable ASM reader without connector,
loose PUR, trailing, 800 m



Suitability for use	Cord for self-assembly of a cable between reader and a communication module
Cable designation	L-YC11Y 6x1x0.25 6x24AWG CM
Wire length	800 m
Electrical data	
Loop resistance per length / maximum	160 mΩ/m
Insulation resistance coefficient	20 GΩ·m
Operating voltage	300 V
• maximum	
Mechanical data	
Number of electrical cores	6
Design of the shield	Braided shield made of tin-plated copper wires
Outer diameter	5.4 mm
• of cable sheath	
Symmetrical tolerance of the outer diameter / of cable sheath	0.2 mm
Material	

<ul style="list-style-type: none"> • of the wire insulation • of cable sheath 	PVC PUR
Color <ul style="list-style-type: none"> • of the insulation of data wires • of cable sheath 	DIN 47100 Black
Bending radius <ul style="list-style-type: none"> • with single bend / minimum permissible • with multiple bends / minimum permissible • with continuous bending 	21.6 mm 43 mm 75 mm
Number of bending cycles	3000000
Tensile load / maximum	200 N
Weight per length	45 kg/km

Ambient conditions	
Ambient temperature <ul style="list-style-type: none"> • during operation • during storage • during transport • during installation 	-30 ... +80 °C -30 ... +80 °C -30 ... +80 °C -30 ... +80 °C
Burning behavior	flame resistant according to IEC 60332-1-2
Chemical resistance <ul style="list-style-type: none"> • to mineral oil • to grease 	resistant resistant
Radiological resistance / to UV radiation	resistant

Product features, product functions, product components / general	
Product feature <ul style="list-style-type: none"> • halogen-free • silicon-free 	No Yes

Standards, specifications, approvals	
UL/ETL listing / 300 V Rating	Yes; CM

Further information / Internet-Links	
Internet-Link <ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx Download Manager • to website: Industry Online Support 	https://support.industry.siemens.com/cs/ww/en/view/67384964 http://www.siemens.com/ident/rfid https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com

last modified: 05/07/2020