

Product type designation

Product description

Y-Adapter for MOBY I

Adapter with EN 175201-804 for connecting an existing SLG cable, EN 175201-804 for connecting a MOBY I SLGs, M12 8-pin for connecting to an RF300 reader and M12 4-pin plug for connecting to 24 Volts

Y-Adapter for connection of an RF300 reader and a MOBY I reader to any MOBY I ASM



Suitability for use	For soft migration of a MOBY I application to RF300
---------------------	---

Supply voltage, current consumption, power loss

Supply voltage / at DC	24 V
------------------------	------

Electrical data

Number of electrical connections	4
Type of electrical connection	EN 175201-804 plug, M12 plug 4-pin, EN 175201-804 socket on 2 m cable, M12 socket 8-pin on 2 m cable

Mechanical data

Material	aluminum
Color	black

Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> during operation 	-25 ... +70 °C
Protection class IP	IP65

Design, dimensions and weights

Width	89 mm
Height	41 mm
Depth	101 mm

Further information / Internet-Links

Internet-Link

- to website: TIA Selection Tool <http://www.siemens.com/tia-selection-tool>
- to website: Selector SIMATIC NET SELECTION TOOL <https://support.industry.siemens.com/WW/view/en/67384964>
- to the website: IWLAN <http://www.siemens.com/iwlan>
- to website: Industrial communication <http://www.siemens.com/ident/rfid>
- to website: Industry Mall <https://mall.industry.siemens.com>
- to website: Information and Download Center <http://www.siemens.com/industry/infocenter>
- to website: Image database <http://automation.siemens.com/bilddb>
- to website: CAx Download Manager <http://www.siemens.com/cax>
- to website: Industry Online Support <https://support.industry.siemens.com>

last modified:

06/10/2020