

### Product type designation

### MDS D165 label

HF label MDS D165 for RF200/RF300 ISO/MOBY D, PET label, adhesive, ISO 15693, Chip type NXP ICODE SLI, 112 byte user memory; 86x 54x 0.3 mm (LxWxH); Minimum order quantity 1000 units



### Suitability for operation

RF200, RF300, MOBY D

### Radio frequencies

Operating frequency / Rated value	13.56 MHz
Range / maximum	500 mm; range is reader dependent: observe <a href="http://support.automation.siemens.com/WW/view/en/67384964">http://support.automation.siemens.com/WW/view/en/67384964</a>
Protocol / with radio transmission	ISO 15693
Transfer rate / with radio transmission / maximum	26.5 kbit/s
Product feature / multitag-capable	Yes

### Electrical data

Product component / Backup battery	No
------------------------------------	----

### Memory

Type of memory	EEPROM
Storage capacity / of the user memory	112 byte
Type of memory organization	UID (fixed code) 8 bytes, user memory 112 bytes, configuration memory 8 bytes
Number of read cycles / at ambient temperature < 40 °C / maximum	10000000000000

Number of write cycles / at ambient temperature < 40 °C / maximum	1000000
Data retention time / at ambient temperature < 40 °C / not less than	10 y
Property of memory	Block-by-block write protection of the user memory
Type of transponder chip used	NXP I-Code SLI

#### Mechanical data

Material	Top side + inlay: PET, antenna aluminum
Color	white
Mounting distance / relating to metal surfaces / recommended / minimum	25 mm

#### Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> <li>during read/write access</li> </ul>	-25 ... +85 °C
<ul style="list-style-type: none"> <li>outside the read/write area</li> </ul>	-25 ... +85 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	20 ... 30 °C
Protection class IP	IP65
Resistance to mechanical stress	Maximum storage period: 2 years (determined by durability of the adhesive)

#### Design, dimensions and weights

Width	54 mm
Height	0.3 mm
Depth	86 mm
Net weight	1 g
Mounting type	one-side adhesible

#### Product features, product functions, product components / general

Product feature	
<ul style="list-style-type: none"> <li>printable</li> </ul>	Yes
Printing process	Thermal transfer process

#### Standards, specifications, approvals

Certificate of suitability	
<ul style="list-style-type: none"> <li>IECEX</li> </ul>	No

#### Further information / Internet-Links

Internet-Link	
<ul style="list-style-type: none"> <li>to website: Selector SIMATIC NET SELECTION TOOL</li> </ul>	<a href="https://support.industry.siemens.com/cs/ww/en/view/67384964">https://support.industry.siemens.com/cs/ww/en/view/67384964</a>
<ul style="list-style-type: none"> <li>to website: Industrial communication</li> </ul>	<a href="http://www.siemens.com/ident/rfid">http://www.siemens.com/ident/rfid</a>
<ul style="list-style-type: none"> <li>to website: Industry Mall</li> </ul>	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
<ul style="list-style-type: none"> <li>to website: Information and Download Center</li> </ul>	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
<ul style="list-style-type: none"> <li>to website: Image database</li> </ul>	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
<ul style="list-style-type: none"> <li>to website: CAx Download Manager</li> </ul>	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>

- to website: Industry Online Support

<https://support.industry.siemens.com>

**last modified:**

05/12/2020