

Product type designation

RF380T transponder

SIMATIC RF300 Transponder RF380T heat resistant, 32 KB FRAM
IP68, -25 to max.+220 °C cyclically, D=114 mm, H=83 mm



Suitability for operation

RF300

Radio frequencies	
Operating frequency / Rated value	13.56 MHz
Range / maximum	160 mm; range is reader dependent: observe http://support.automation.siemens.com/WW/view/en/67384964
Protocol / with radio transmission	RF300-specific
Transfer rate / with radio transmission / maximum	106 kbit/s
Product feature / multitag-capable	Yes

Electrical data	
Product component / Backup battery	No

Memory	
Type of memory	FRAM / EEPROM
Storage capacity / of the user memory	32765 byte
Type of memory organization	UID (fixed code) 4 bytes, user memory 32765 bytes, OTP memory 20 bytes
Number of read cycles / at ambient temperature < 40 °C / maximum	10000000000

Number of write cycles / at ambient temperature < 40 °C / maximum	10000000000
Data retention time / at ambient temperature < 40 °C / not less than	10 y
Property of memory	Block-by-block write protection of the OTP memory

Mechanical data

Material	PPS
Color	brown
Mounting distance / relating to metal surfaces / recommended / minimum	0 mm

Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> during read/write access 	-25 ... +110 °C
<ul style="list-style-type: none"> outside the read/write area 	-40 ... +220 °C
<ul style="list-style-type: none"> during storage 	-40 ... +110 °C
Ambient condition / for operation	Cyclic operation at ambient temperature >110 °C
Protection class IP	IP68
Shock resistance	According to DIN EN 60721-3-7 Class 7 M3
Shock acceleration	500 m/s ²
Vibrational acceleration	200 m/s ²

Design, dimensions and weights

Height	83 mm
Diameter	114 mm
Net weight	900 g
Mounting type	mount (see accessories)

Product features, product functions, product components / general

Product feature	
<ul style="list-style-type: none"> silicon-free 	Yes
<ul style="list-style-type: none"> printable 	No

Standards, specifications, approvals

Certificate of suitability	
<ul style="list-style-type: none"> IECEX 	Yes
MTBF	1200 y

accessories

accessories	Skid holder, shrouding cover, universal holder
-------------	--

Further information / Internet-Links

Internet-Link	
<ul style="list-style-type: none"> to website: Selector SIMATIC NET SELECTION TOOL 	https://support.industry.siemens.com/cs/ww/en/view/67384964
<ul style="list-style-type: none"> to website: Industrial communication 	http://www.siemens.com/ident/rfid

- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

last modified:

05/12/2020